



Test Report issued under the responsibility of:



TEST REPORT
IEC 60335-2-7
Safety of household and similar electrical appliances
Part 2: Particular requirements for washing machines

Report Number.....: NBES200400110901

Date of issue 2020-05-19

Total number of pages.....: 112 pages

Name of Testing Laboratory
preparing the Report.....: SGS-CSTC Standards Technical Services Co., Ltd. Ningbo Branch

Applicant's name Cixi Runsun Electrical Appliance Co., Ltd.

Address Longtouchang Industrial Park, Longshan Town, Cixi, 315300
Zhejiang, China

Test specification:

Standard.....: IEC 60335-2-7:2019 in conjunction with IEC 60335-1:2010,
COR1:2010, COR2:2011, AMD1:2013, COR1:2014, AMD2:2016,
COR1:2016

Test procedure.....: CB Scheme

Non-standard test method.....: N/A

Test Report Form No.: IEC60335_2_7P

Test Report Form(s) Originator: LCIE

Master TRF.....: Dated 2019-11-19

Copyright © 2019 IEC System of Conformity Assessment Schemes for Electrotechnical Equipment and Components (IECEE System). All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the IECEE is acknowledged as copyright owner and source of the material. IECEE takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

If this Test Report Form is used by non-IECEE members, the IECEE/IEC logo and the reference to the CB Scheme procedure shall be removed.

This report is not valid as a CB Test Report unless signed by an approved CB Testing Laboratory and appended to a CB Test Certificate issued by an NCB in accordance with IECEE 02.

General disclaimer:

The test results presented in this report relate only to the object tested.

This report shall not be reproduced, except in full, without the written approval of the Issuing CB Testing Laboratory. The authenticity of this Test Report and its contents can be verified by contacting the NCB, responsible for this Test Report.

Test item description	Single-tub Washing Machine (Mini Washing Machine)		
Trade Mark(s)	-		
Original Product/Equipment Manufacturer	Same as applicant		
Branding Manufacturer(s).....	-		
Model/Type reference	XPBy-800D (y=15, 18, 20, 25, 28, 30, 35, 38, 42, 48, 52, 58, 62, 68, 78)		
Ratings	220 V - 240 V~; 50/60 Hz; Class I; IPX4;		
	Model	Wash capacity	Power
	XPB15-800D	0,5 kg	170 W
	XPB18-800D		
	XPB20-800D		
	XPB25-800D	1,0 kg	240 W
	XPB28-800D	2,8 kg	
	XPB30-800D	3,0 kg	
	XPB35-800D	3,5 kg	
	XPB38-800D	3,8 kg	
	XPB42-800D	4,0 kg	
	XPB48-800D		
	XPB52-800D	4,8 kg	320 W
	XPB58-800D		
	XPB62-800D		
	XPB68-800D	6,0 kg	400 W
	XPB78-800D		

Responsible Testing Laboratory (as applicable), testing procedure and testing location(s):		
☒	CB Testing Laboratory:	SGS-CSTC Standards Technical Services Co., Ltd. Ningbo Branch
Testing location/ address		No.1177, Lingyun Road, Hi-Tech Zone, Ningbo, Zhejiang, China
Tested by (name, function, signature)		Zed Dong / Project Engineer 
Approved by (name, function, signature) ..		Austin Xuan / Reviewer 
☐	Testing procedure: CTF Stage 1:	N/A
Testing location/ address		
Tested by (name, function, signature)		
Approved by (name, function, signature) ..		
☐	Testing procedure: CTF Stage 2:	N/A
Testing location/ address		
Tested by (name + signature)		
Witnessed by (name, function, signature) . :		
Approved by (name, function, signature) ..		
☐	Testing procedure: CTF Stage 3:	N/A
☐	Testing procedure: CTF Stage 4:	N/A
Testing location/ address		
Tested by (name, function, signature)		
Witnessed by (name, function, signature) . :		
Approved by (name, function, signature) ..		
Supervised by (name, function, signature) :		

List of Attachments (including a total number of pages in each attachment): - Attachment 1 – Photo documentation – 31 pages - Attachment 2 – Circuit diagram – 2 pages - Attachment 3 – EU Differences + EMF – 15 pages - Attachment 4 – EN 60335-1:2012/A13: 2017 – 2 pages - Attachment 5 – EN 60335 1:2012/A1:2019 + A14:2019 + A2:2019 – 11 pages	
Summary of testing:	
Tests performed (name of test and test clause): IEC 60335-2-7:2019 IEC 60335-1:2010 + A1:2013 + A2:2016 EN 60335-2-7:2010 + A1:2013 + A11:2013 + A2:2019 EN 60335-1:2012 + A11:2014 + A13:2017 + A1:2019 + A14:2019 + A2:2019 EN 62233:2008 Full tests were carried out on model XPB78-800D. Tests of clause 10, 11, 13, 19.7, 22.5, 24.5, 29, 30 and Annex D were carried out on model XPBy-800D (y=25, 48, 62) Tests of clause 8, 29 and 30 were carried out on model XPB78-800D. The test data was based on CB report No. NBES140800074901, NBES140800074902-M1, NBES140800074903-M2. Compared with the original test report including its amendments, the following changes and additions were considered: 1. Requirements of IEC 60335-2-7:2019, IEC 60335-1:2010/A1:2013, IEC 60335-1:2010/A2:2016, EN 60335-2-7:2010/A2:2019, EN 60335-1:2012/A13:2017, EN 60335 1:2012/A1:2019 + A14:2019 + A2:2019 were evaluated. 2. Alternative components (plug, internal wire, running capacitor) were added. 3. Some components with expired certificates(fuse, washing switch, washing timer) were replaced. After reviewing, tests of Cl.23.5, 30.2 were performed on new added alternative components.	Testing location: CBTL
Summary of compliance with National Differences (List of countries addressed): -EU Group Differences	

Statement concerning the uncertainty of the measurement systems used for the tests

☐ Internal procedure used for type testing through which traceability of the measuring uncertainty has been established:

Procedure number, issue date and title:

Calculations leading to the reported values are on file with the NCB and testing laboratory that conducted the testing.

☒ Statement not required by the standard used for type testing

Copy of marking plate:

The artwork below may be only a draft. The use of certification marks on a product must be authorized by the respective National Certification Body that own these marks.



The marking plates of all models are the same as model XPB20-800D except the model name, rated washing capacity and washing input power.

Test item particulars.....	: Single-tub Washing Machine (Mini Washing machine)
Classification of installation and use	: Portable appliance for unattended use
Supply Connection	: Flexible supply cord fitted with un-detachable plug
..... :	
Possible test case verdicts:	
- test case does not apply to the test object: N/A	
- test object does meet the requirement: P (Pass)	
- test object does not meet the requirement: F (Fail)	
Testing	
Date of receipt of test item	: 2014-08-14, 2015-03-25, 2016-01-05, 2020-04-16
Date (s) of performance of tests.....	: 2014-08-14 to 2014-10-09, 2015-03-25 to 2015-03-31, 2016-01-05 to 2016-01-19 2020-04-16 to 2020-05-19
General remarks:	
“(See Attachment #)” refers to additional information appended to the report. “(See appended table)” refers to a table appended to the report. Throughout this report a ☒ comma / ☐ point is used as the decimal separator. This document is issued by the Company subject to its General Conditions of Service, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company’s findings at the time of its intervention only and within the limits of Client’s instructions, if any. The Company’s sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 1 month only.	
Manufacturer’s Declaration per sub-clause 4.2.5 of IEC 60335-1:	
The application for obtaining a CB Test Certificate includes more than one factory location and a declaration from the Manufacturer stating that the sample(s) submitted for evaluation is (are) representative of the products from each factory has been provided:	☐ Yes ☒ Not applicable
When differences exist; they shall be identified in the General product information section.	
Name and address of factory (ies) : Same as applicant	

General product information and other remarks:

All models had similar construction and share the same components. Refer to below table for detailed differences:

Model	Wash capacity	Power	Motor	Capacitor	Impeller blade	Out appearance
XPB15-800D	0,5 kg	170 W	XPD-50	4 uF	A	a
XPB18-800D						b
XPB20-800D						c
XPB25-800D	1,0 kg	240 W	XPD-90	6 uF	B	d
XPB28-800D	2,8 kg					
XPB30-800D	3,0 kg					
XPB35-800D	3,5 kg					e
XPB38-800D	3,8 kg					
XPB42-800D	4,0 kg					f
XPB48-800D						
XPB52-800D	4,8 kg	320 W	XPD-120	10 uF	C	g
XPB58-800D						
XPB62-800D						
XPB68-800D	6,0 kg	400 W	XPD-150	12 uF	D	h
XPB78-800D						i

Details of impeller blade and out appearance see attachment 1.

IEC 60335-2-7			
Clause	Requirement + Test	Result - Remark	Verdict
5	GENERAL CONDITIONS FOR THE TESTS		—
	Tests performed according to clause 5, e.g. nature of supply, sequence of testing, etc.		P
5.2	The relevant tests of 21.101, 21.102 and 22.104 shall be carried out on the same appliance used for the test of clause 18 (IEC 60335-2-7)		P
5.3	Test of 15.101 carried out before test of 15.3 (IEC 60335-2-7)		P
	Relevant tests of 21.101 and 21.102 carried out before test of clause 18. test of 22.104 carried out after test of clause 18. (IEC 60335-2-7)		P
5.7	Doubt is considered to exist if the temperature of the water is within 6 K of the boiling point and the difference between the temperature rise of the relevant part and the limit specified does not exceed 25 K minus the room temperature. (IEC 60335-2-7)		N/A
6	CLASSIFICATION		—
6.1	Protection against electric shock: Class 0, 0I, I, II, III..... :	Class I	P
	Appliances shall be of class I, class II or class III. (IEC 60335-2-7)	Class I	P
6.2	Protection against harmful ingress of water		P
	Appliances at least IPX4 (IEC 60335-2-7)	IPX4	P
7	MARKING AND INSTRUCTIONS		—
7.1	Rated voltage or voltage range (V)..... :	220 V - 240 V~	P
	Symbol for nature of supply, or..... :		P
	Rated frequency (Hz)..... :	50/60 Hz	P
	Rated power input (W), or..... :	See page 2	P
	Rated current (A)		N/A
	Manufacturer's or responsible vendor's name, trademark or identification mark	Cixi Runsun Electrical Appliance Co., Ltd.	P
	Model or type reference	XPBy-800D (y=15, 18, 20, 25, 28, 30, 35, 38, 42, 48, 52, 58, 62, 68, 78)	P
	Symbol IEC 60417-5172, for class II appliances		N/A
	IP number, other than IPX0..... :	IPX4	P
	Maximum water level for appliances without automatic water level control (IEC 60335-2-7)	Marked in the tub	P

IEC 60335-2-7			
Clause	Requirement + Test	Result - Remark	Verdict
	Symbol IEC 60417-5180, for class III appliances, unless		N/A
	the appliance is operated by batteries only, or		N/A
	for appliances powered by rechargeable batteries recharged in the appliance		N/A
	Symbol IEC 60417-5018, for class II and class III appliances incorporating a functional earth		N/A
	Symbol IEC 60417-5036, for the enclosure of electrically-operated water valves in external hose-sets for connection of an appliance to the water mains, if the working voltage exceeds extra-low voltage		N/A
	Appliances not intended for connection to the hot water supply and not provided with heating elements shall be marked with the substance of the following: "Do not connect to the hot water supply" (IEC 60335-2-7)		P
7.2	Warning for stationary appliances for multiple supply		N/A
	Warning placed in vicinity of terminal cover		N/A
7.3	Range of rated values marked with the lower and upper limits separated by a hyphen	220 V - 240 V~	P
	Different rated values marked with the values separated by an oblique stroke	50/60 Hz	P
7.4	Appliances adjustable for different rated voltages or rated frequencies, the voltage or the frequency setting is clearly discernible		N/A
	Requirement met if frequent changes are not required and the rated voltage or rated frequency to which the appliance is to be adjusted is determined from a wiring diagram		N/A
7.5	Appliances with more than one rated voltage or one or more rated voltage ranges, marked with rated input or rated current for each rated voltage or range, unless		N/A
	the power input is related to the arithmetic mean value of the rated voltage range		P
	Relation between marking for upper and lower limits of rated power input or rated current and voltage is clear		N/A
7.6	Correct symbols used		P

IEC 60335-2-7			
Clause	Requirement + Test	Result - Remark	Verdict
	Symbol for nature of supply placed next to rated voltage		P
	Symbol for class II appliances placed unlikely to be confused with other marking		N/A
	Units of physical quantities and their symbols according to international standardized system		P
7.7	Connection diagram fixed to appliances to be connected to more than two supply conductors and appliances for multiple supply, unless		N/A
	correct mode of connection is obvious		N/A
7.8	Except for type Z attachment, terminals for connection to the supply mains indicated as follows:		—
	- marking of terminals exclusively for the neutral conductor (letter N)		N/A
	- marking of protective earthing terminals (symbol IEC 60417-5019)		P
	- marking of functional earthing terminals (symbol IEC 60417-5018)		N/A
	- marking not placed on removable parts		P
7.9	Marking or placing of switches which may cause a hazard		P
7.10	Indications of switches on stationary appliances and controls on all appliances by use of figures, letters or other visual means :	Figures and letters were used	P
	This applies also to switches which are part of a control		N/A
	If figures are used, the off position indicated by the figure 0		P
	The figure 0 indicates only OFF position, unless no confusion with the OFF position		N/A
	If the off position is only indicated by letters, the word "off" is used. (IEC 60335-2-7)		N/A
7.11	Indication for direction of adjustment of controls		P
7.12	Instructions for safe use provided		P
	Details concerning precautions during user maintenance		P
	The instructions state that:		—

IEC 60335-2-7			
Clause	Requirement + Test	Result - Remark	Verdict
	- the appliance is not to be used by persons (including children) with reduced physical, sensory or mental capabilities, or lack of experience and knowledge, unless they have been given supervision or instruction		P
	- children being supervised not to play with the appliance		P
	For a part of class III construction supplied from a detachable power supply unit, the instructions state that the appliance is only to be used with the unit provided		N/A
	Instructions for class III appliances state that it must only be supplied at SELV, unless		N/A
	it is a battery-operated appliance, the battery being charged outside the appliance		N/A
	For appliances for altitudes exceeding 2000 m, the maximum altitude is stated :		N/A
	The instructions for appliances incorporating a functional earth states that the appliance incorporates an earth connection for functional purposes only		N/A
	Maximum mass of dry cloth in kilograms, specified (IEC 60335-2-7)	See page 2	P
	This appliance is intended to be used in household and similar applications such as: (IEC 60335-2-7) – staff kitchen areas in shops, offices and other working environments; – farm houses; – by clients in hotels, motels and other residential type environments; – bed and breakfast type environments; – areas for communal use in blocks of flats or in launderettes.		P
	If the manufacturer wants to limit the use of the appliance to less than the above, this shall be clearly stated in the instructions. (IEC 60335-2-7)		N/A
7.12.1	Sufficient details for installation supplied		P
	For an appliance intended to be permanently connected to the water mains and not connected by a hose-set, this is stated		N/A
	If different rated voltages or different rated frequencies are marked, the instructions state what action to be taken to adjust the appliance		N/A

IEC 60335-2-7			
Clause	Requirement + Test	Result - Remark	Verdict
	- carpet does not obstruct the openings for washing machines with ventilation openings in the base (IEC 60335-2-7)		P
7.12.2	Stationary appliances not fitted with means for disconnection from the supply mains having a contact separation in all poles that provide full disconnection under overvoltage category III, the instructions state that means for disconnection must be incorporated in the fixed wiring in accordance with the wiring rules		N/A
7.12.3	Insulation of the fixed wiring in contact with parts exceeding 50 K during clause 11; instructions state that the fixed wiring must be protected		N/A
7.12.4	Instructions for built-in appliances:		—
	- dimensions of space		N/A
	- dimensions and position of supporting and fixing		N/A
	- minimum distances between parts and surrounding structure		N/A
	- minimum dimensions of ventilating openings and arrangement		N/A
	- connection to supply mains and interconnection of separate components		N/A
	- allow disconnection of the appliance after installation, by accessible plug or a switch in the fixed wiring, unless		N/A
	a switch complying with 24.3		N/A
7.12.5	Replacement cord instructions, type X attachment with a specially prepared cord		N/A
	Replacement cord instructions, type Y attachment		P
	Replacement cord instructions, type Z attachment		N/A
7.12.6	Caution in the instructions for appliances incorporating a non-self-resetting thermal cut-out that is reset by disconnection of the supply mains, if this cut-out is required to comply with the standard		N/A
7.12.7	Instructions for fixed appliances stating how the appliance is to be fixed		N/A
7.12.8	Instructions for appliances connected to the water mains:		—
	- max. inlet water pressure (Pa) :	0,85 MPa	P
	- min. inlet water pressure, if necessary (Pa) :	0,01 MPa	P

IEC 60335-2-7			
Clause	Requirement + Test	Result - Remark	Verdict
	Instructions concerning new and old hose-sets for appliances connected to the water mains by detachable hose-sets		P
7.12.9	Instructions specified in 7.12 and from 7.12.1 to 7.12.8 appear together before any other instructions supplied with the appliance		P
	These instructions may be supplied with the appliance separately from any functional use booklet		N/A
	They may follow the description of the appliance that identifies parts, or follow the drawings/sketches		P
	In addition, instructions are also available in an alternative format such as on a website or on request from the user in a format such as a DVD		P
	In addition, instructions are also available in an alternative format such as on a website or in a format such as a DVD:	By service email	P
7.13	Instructions and other texts in an official language	English	P
7.14	Marking clearly legible and durable, rubbing test as specified		P
	Signal words WARNING, CAUTION, DANGER in uppercase having a height as specified:		N/A
	Uppercase letter of the text explaining the signal word not smaller than 1,6 mm :		N/A
	Moulded in, engraved, or stamped markings either raised above or have a depth below the surface of at least 0,25 mm, unless		N/A
	contrasting colours are used		N/A
	Markings checked by inspection, measurement and rubbing test as specified		P
7.15	Markings on a main part		P
	Marking clearly discernible from the outside, if necessary after removal of a cover		P
	For portable appliances, cover can be removed or opened without a tool		P
	For stationary appliances, name, trademark or identification mark and model or type reference visible after installation		N/A
	For fixed appliances, name, trademark or identification mark and model or type reference visible after installation according to the instructions		N/A

IEC 60335-2-7			
Clause	Requirement + Test	Result - Remark	Verdict
	Indications for switches and controls placed on or near the components. Marking not on parts which can be positioned or repositioned in such a way that the marking is misleading		P
	The symbol IEC 60417-5018 placed next to the symbol IEC 60417-5172 or IEC 60417-5180		N/A
	The caution relating to connection to the hot water supply shall be on the appliance at its point of attachment to the water supply (IEC 60335-2-7)		P
7.16	Marking of a possible replaceable thermal link or fuse link clearly visible with regard to replacing the link		N/A
8	PROTECTION AGAINST ACCESS TO LIVE PARTS		—
8.1	Adequate protection against accidental contact with live parts		P
8.1.1	Requirement applies for all positions, detachable parts removed		P
	Lamps behind a detachable cover not removed, if conditions met		N/A
	Insertion or removal of lamps, protection against contact with live parts of the lamp cap		N/A
	Use of test probe B of IEC 61032, with a force not exceeding 1 N: no contact with live parts		P
8.1.2	Use of test probe 13 of IEC 61032, with a force not exceeding 1 N, through openings in class 0 appliances and class II appliances/constructions: no contact with live parts		P
	Test probe 13 also applied through openings in earthed metal enclosures having a non-conductive coating: no contact with live parts		N/A
8.1.3	For appliances other than class II, use of test probe 41 of IEC 61032, with a force not exceeding 1 N: no contact with live parts of visible glowing heating elements		N/A
	For a single switching action obtained by a switching device, requirements as specified		N/A
	For appliances with a supply cord and without a switching device, the single switching action may be obtained by the withdrawal of the plug		N/A
8.1.4	Accessible part not considered live if:		—
	- safety extra-low a.c. voltage: peak value not exceeding 42.4 V		N/A

IEC 60335-2-7			
Clause	Requirement + Test	Result - Remark	Verdict
	- safety extra-low d.c. voltage: not exceeding 42.4 V		N/A
	- or separated from live parts by protective impedance		N/A
	If protective impedance: d.c. current not exceeding 2 mA, and		N/A
	a.c. peak value not exceeding 0.7 mA		N/A
	- for peak values over 42.4 V up to and including 450 V, capacitance not exceeding 0,1 μ F		N/A
	- for peak values over 450 V up to and including 15 kV, discharge not exceeding 45 μ C		N/A
	- for peak values over 15kV, the energy in the discharge not exceeding 350 mJ		N/A
8.1.5	Live parts protected at least by basic insulation before installation or assembly:		—
	- built-in appliances		N/A
	- fixed appliances		N/A
	- appliances delivered in separate units		N/A
8.2	Class II appliances and constructions constructed so that there is adequate protection against accidental contact with basic insulation and metal parts separated from live parts by basic insulation only		P
	Only possible to touch parts separated from live parts by double or reinforced insulation		P
9	STARTING OF MOTOR-OPERATED APPLIANCES		—
	Requirements and tests are specified in part 2 when necessary		N/A
10	POWER INPUT AND CURRENT		—
10.1	Power input at normal operating temperature, rated voltage and normal operation not deviating from rated power input by more than shown in table 1. :	(see appended table)	P
	If the power input varies throughout the operating cycle and the maximum value of the power input exceeds, by a factor greater than two, the arithmetic mean value of the power input occurring during a representative period, the power input is the maximum value that is exceeded for more than 10 % of the representative period		N/A
	Otherwise the power input is the arithmetic mean value		P

IEC 60335-2-7			
Clause	Requirement + Test	Result - Remark	Verdict
	Test carried out at upper and lower limits of the ranges for appliances with one or more rated voltage ranges, unless		N/A
	the rated power input is related to the arithmetic mean value		P
	The selected representative period is the period, such as filling with water, washing, rinsing, water extraction, spinning or braking, during which the power input is the highest (IEC 60335-2-7)		P
10.2	Current at normal operating temperature, rated voltage and normal operation not deviating from rated current by more than shown in table 2..... :		N/A
	If the current varies throughout the operating cycle and the maximum value of the current exceeds, by a factor greater than two, the arithmetic mean value of the current occurring during a representative period, the current is the maximum value that is exceeded for more than 10 % of the representative period		N/A
	Otherwise the current is the arithmetic mean value		N/A
	Test carried out at upper and lower limits of the ranges for appliances with one or more rated voltage ranges, unless		N/A
	the rated current is related to the arithmetic mean value of the range		N/A
	The selected representative period is the period, such as filling with water, washing, rinsing, water extraction, spinning or braking, during which the current is the highest (IEC 60335-2-7)		N/A
11	HEATING		—
11.1	No excessive temperatures in normal use		P
11.2	The appliance is held, placed or fixed in position as described..... :	In a test corner	P
11.3	Temperature rises, other than of windings, determined by thermocouples		P
	Temperature rises of windings determined by resistance method, unless	Wash motor	P
	the windings are non-uniform or it is difficult to make the necessary connections		N/A
	Where the external accessible surfaces are suitably flat and access permits, then the test probe of Figure 101 may be used to measure the temperature rises of external accessible surfaces specified in Table 101. (IEC 60335-2-7)		N/A

IEC 60335-2-7			
Clause	Requirement + Test	Result - Remark	Verdict
11.4	Heating appliances operated under normal operation at 1.15 times rated power input (W) :		N/A
11.5	Motor-operated appliances operated under normal operation at most unfavourable voltage between 0.94 and 1.06 times rated voltage (V)..... :	254,4 V was considered as more unfavourable condition	P
11.6	Combined appliances operated under normal operation at most unfavourable voltage between 0.94 and 1.06 times rated voltage (V)..... :		N/A
11.7	Appliances with a programmer (IEC 60335-2-7)		N/A
	-3 cycles with programme that results in highest temperature rises		N/A
	-rest period of 4 min between cycles		N/A
	Others appliances sequences of test as specified (IEC 60335-2-7)		N/A
	-for appliances without means for water extraction and for washing machines with a hand-operated wringer: washing		P
	-for appliances having a single drum for washing and water extraction: washing followed by water extraction		N/A
	-for appliances having separate drums for washing and water extraction, which can-not be used simultaneously: washing and water extraction separated by an additional 4 min rest period		N/A
	-for appliances having separate drums for washing and water extraction, which can be used simultaneously washing together with water extraction so that the operations terminate simultaneously		N/A
	- for appliances having a single drum (dried=washed) washing followed by water extraction, followed by drying		N/A
	- for appliances having a single drum (dried<washed) washing followed by water extraction, followed by 2 drying periods, with an additional rest period 4 min before each drying period. In this case only 2 cycles of operation are carried out.		N/A
	For appliances with a timer, the washing period, the water extraction period and the drying are equal to the maximum period allowed by the timer (IEC 60335-2-7)		P
	For appliance without a timer (IEC 60335-2-7)		N/A

IEC 60335-2-7			
Clause	Requirement + Test	Result - Remark	Verdict
	Type of washing machine:		N/A
	Duration of washing (min)		N/A
	Duration of water extraction : 5min		N/A
	The rest period, including any braking time, has a duration of 4 min. (IEC 60335-2-7)		N/A
	After the specified sequence of operation, discharge pumps that are driven by a separate motor and switched on and off manually, are subjected to 3 operating periods separated by rest periods of 4 min. (IEC 60335-2-7)		N/A
	Duration of each operating period :		N/A
11.8	Temperature rises monitored continuously and not exceeding the values in table 3	(see appended table)	P
	If the temperature rise of a motor winding exceeds the value of table 3, or		N/A
	if there is doubt with regard to classification of insulation,		N/A
	tests of Annex C are carried out		N/A
	Sealing compound does not flow out		N/A
	Protective devices do not operate, except		P
	components in protective electronic circuits tested for the number of cycles specified in 24.1.4		N/A
	During the test, the temperature rises are monitored continuously for one cycle and shall not exceed the values shown in Table 101. (IEC 60335-2-7)		P
13	LEAKAGE CURRENT AND ELECTRIC STRENGTH AT OPERATING TEMPERATURE		—
13.1	Leakage current not excessive and electric strength adequate		P
	Heating appliances operated at 1.15 times the rated power input (W)		N/A
	Motor-operated appliances and combined appliances supplied at 1.06 times the rated voltage (V)	1,06 x 240 = 254,4 V	P
	Protective impedance and radio interference filters disconnected before carrying out the tests		N/A
13.2	The leakage current is measured by means of the circuit described in Figure 4 of IEC 60990:1999		P

IEC 60335-2-7			
Clause	Requirement + Test	Result - Remark	Verdict
	For class 0I appliances and class I appliances, except parts of class II construction, C may be replaced by a low impedance ammeter		N/A
	Leakage current measurements..... :	(see appended table)	P
	For stationary class I appliances, the leakage current not exceeding 3,5 mA, or 1 mA/kW of rated power input with a limit of 5 mA, whichever is greater (IEC 60335-2-7)		N/A
13.3	The appliance is disconnected from the supply		P
	Electric strength tests according to table 4 :	(see appended table)	P
	No breakdown during the tests		P
14	TRANSIENT OVERVOLTAGES		—
	Appliances withstand the transient over-voltages to which they may be subjected		N/A
	Clearances having a value less than specified in table 16 subjected to an impulse voltage test, the test voltage specified in table 6 :		N/A
	No flashover during the test, unless		N/A
	of functional insulation if the appliance complies with clause 19 with the clearance short-circuited		N/A
15	MOISTURE RESISTANCE		—
15.1	Enclosure provides the degree of moisture protection according to classification of the appliance		P
	Compliance checked as specified in 15.1.1, taking into account 15.1.2, followed by the electric strength test of 16.3		P
	No trace of water on insulation which can result in a reduction of clearances or creepage distances below values specified in clause 29		P
15.1.1	Appliances, other than IPX0, subjected to tests as specified in IEC 60529 :	IPX4	P
	Water valves containing live parts in external hoses for connection of an appliance to the water mains tested as specified for IPX7 appliances		N/A
15.1.2	Hand-held appliance turned continuously through the most unfavourable positions during the test		N/A
	Built-in appliances installed according to the instructions		N/A
	Appliances placed or used on the floor or table placed on a horizontal unperforated support		P

IEC 60335-2-7			
Clause	Requirement + Test	Result - Remark	Verdict
	Appliances normally fixed to a wall and appliances with pins for insertion into socket-outlets are mounted on a wooden board		N/A
	For IPX3 appliances, the base of wall mounted appliances is placed at the same level as the pivot axis of the oscillating tube		N/A
	For IPX4 appliances, the horizontal centre line of the appliance is aligned with the pivot axis of the oscillating tube, and		P
	for appliances normally used on the floor or table, the movement is limited to two times 90° for a period of 5 min, the support being placed at the level of the pivot axis of the oscillating tube		P
	Wall-mounted appliances, take into account the distance to the floor stated in the instructions		N/A
	Appliances normally fixed to a ceiling are mounted underneath a horizontal unperforated support, the pivot axis of the oscillating tube located at the level of the underside of the support, and		N/A
	for IPX4 appliances, the movement of the tube is limited to two times 90° from the vertical for a period of 5 min		P
	Appliances with type X attachment fitted with a flexible cord as described		N/A
	Detachable parts subjected to the relevant treatment with the main part		P
	However, if a part has to be removed for user maintenance and a tool is needed, this part is not removed		N/A
15.2	Spillage of liquid does not affect the electrical insulation even if an inlet valve fails to close (IEC 60335-2-7)		P
	Appliances with type X attachment fitted with a flexible cord as described (IEC 60335-2-7)		N/A
	Appliances incorporating an appliance inlet tested with or without an connector, whichever is most unfavourable (IEC 60335-2-7)		N/A
	Appliances intended to be filled in by the user : Overfilling test with additional amount of water, over a period of 1 min (l) (IEC60335-2-7) .. :		N/A
	Other appliances are operated until maximum water level, detergent added, then inlet valve is held open..... (IEC 60335-2-7)	5 g detergent specified in annex AA for each litre of water	P

IEC 60335-2-7			
Clause	Requirement + Test	Result - Remark	Verdict
	For appliances loaded from the front, door is then opened manually without damaging door interlock system (IEC 60335-2-7)		P
	For all appliances: 0,5l of water containing approximately 1% NaCl and 0,6% of rinsing agent, is poured over the top of the appliance, the controls being placed in the on position. The controls are operated through their working range, this operating being repeated after a period of 5mn (IEC 60335-2-7)		P
	Any commercially available non-ionic rinsing agent may be used, but if there is any doubt with regards to the test results, the rinsing agent shall have the described properties and composition (IEC 60335-2-7)		N/A
	The appliance withstands the electric strength test of 16.3 (IEC 60335-2-7)		P
	No trace of water on insulation that can result in a reduction of clearances or creepage distances below values specified in clause 29 (IEC 60335-2-7)		P
15.3	Appliances proof against humid conditions		P
	Checked by test Cab: Damp heat steady state in IEC 60068-2-78		P
	Detachable parts removed and subjected, if necessary, to the humidity test with the main part		P
	Humidity test for 48 h in a humidity cabinet	25 °C, 93% R.H.	P
	Reassembly of those parts that may have been removed		P
	The appliance withstands the tests of clause 16		P
15.101	Foaming does not affect electrical insulation – Electric strength test according subclause 16.3 (IEC 60335-2-7)		P
16	LEAKAGE CURRENT AND ELECTRIC STRENGTH		—
16.1	Leakage current not excessive and electric strength adequate		P
	Protective impedance disconnected from live parts before carrying out the tests		N/A
	Tests carried out at room temperature and not connected to the supply		P
16.2	Single-phase appliances: test voltage 1.06 times rated voltage (V) :	1,06 x 240 V = 254,4 V	P

IEC 60335-2-7			
Clause	Requirement + Test	Result - Remark	Verdict
	Three-phase appliances: test voltage 1.06 times rated voltage divided by $\sqrt{3}$ (V)..... :		N/A
	Leakage current measurements..... :	(see appended table)	P
	Limit values doubled if:		—
	- all controls have an off position in all poles, or		N/A
	- the appliance has no control other than a thermal cut-out, or		N/A
	- all thermostats, temperature limiters and energy regulators do not have an off position, or		N/A
	- the appliance has radio interference filters		N/A
	With the radio interference filters disconnected, the leakage current do not exceed limits specified..... :		N/A
16.3	Electric strength tests according to table 7 :	(see appended table)	P
	Test voltage applied between the supply cord and inlet bushing and cord guard and cord anchorage as specified :	(see appended table)	P
	No breakdown during the tests		P
17	OVERLOAD PROTECTION OF TRANSFORMERS AND ASSOCIATED CIRCUITS		—
	No excessive temperatures in transformer or associated circuits in event of short-circuits likely to occur in normal use :	No transformer	N/A
	Appliance supplied with 1.06 or 0.94 times rated voltage under the most unfavourable short-circuit or overload likely to occur in normal use (V) :		N/A
	Basic insulation is not short-circuited		N/A
	Temperature rise of insulation of the conductors of safety extra-low voltage circuits not exceeding the relevant value specified in table 3 by more than 15 K		N/A
	Temperature of the winding not exceeding the value specified in table 8		N/A
	However, limits do not apply to fail-safe transformers complying with sub-clause 15.5 of IEC 61558-1		N/A
18	ENDURANCE		—
18.101	Appliances shall be constructed so that the lid or door interlock withstands the stresses to which it may be exposed in normal use. (IEC 60335-2-7)		N/A

IEC 60335-2-7			
Clause	Requirement + Test	Result - Remark	Verdict
	The lid or door is subjected to 10 000 cycles of opening and closing		N/A
	For appliances having a drying function, the number of cycles is 13 000		N/A
	After the test, compliance with 20.103 to 20.105 shall not be impaired		N/A
18.102	The braking mechanism of appliances having a lid that can be opened during the water extraction period shall withstand the stresses to which it may be exposed in normal use. (IEC 60335-2-7)		N/A
	Appliance supplied at 1.06 rated voltage		N/A
	Test carried out 1000 times, the textile material re-saturated with water at least every 250 times		N/A
	After the test, the appliance shall be fit for further use and compliance with this standard shall not be impaired.		N/A
19	ABNORMAL OPERATION		—
19.1	The risk of fire, mechanical damage or electric shock under abnormal or careless operation obviated		P
	Electronic circuits so designed and applied that a fault will not render the appliance unsafe		N/A
	Appliances incorporating heating elements subjected to the tests of 19.2 and 19.3, and		N/A
	if the appliance also has a control that limit the temperature during clause 11 it is subjected to the test of 19.4, and		N/A
	if applicable, to the test of 19.5		N/A
	Appliances incorporating PTC heating elements are also subjected to the test of 19.6		N/A
	Appliances incorporating motors subjected to the tests of 19.7 to 19.10, as applicable		P
	Appliances incorporating electronic circuits subjected to the tests of 19.11 and 19.12, as applicable		N/A
	Appliances incorporating contactors or relays subjected to the test of 19.14, being carried out before the tests of 19.11		N/A
	Appliances incorporating voltage selector switches subjected to the test of 19.15		N/A

IEC 60335-2-7			
Clause	Requirement + Test	Result - Remark	Verdict
	Unless otherwise specified, the tests are continued until a non-self-resetting thermal cut-out operates, or		N/A
	until steady conditions are established		P
	If a heating element or intentionally weak part becomes open-circuited, the relevant test is repeated on a second sample		N/A
	For appliances incorporating a programmer or timer, the tests of 19.2 and 19.3 are replaced by the tests of 19.101 (IEC 60335-2-7)		P
	Test of 19.7 is not carried out on motor driving moving parts of oscillating agitator (IEC 60335-2-7)		N/A
	Appliances not intended for connection to the hot water supply and not provided with heating elements are also subjected to the test of 19.102. (IEC 60335-2-7)		N/A
19.2	Test of appliances with heating elements with restricted heat dissipation; test voltage (V), power input of 0.85 times rated power input (W) :	Replaced by 19.101	N/A
	Restricted heat dissipation is obtained without water, with just sufficient water to cover the heating elements..... (IEC 60335-2-7)		N/A
19.3	Test of 19.2 repeated; test voltage (V), power input of 1.24 times rated power input (W)..... :	Replaced by 19.101	N/A
19.4	Test conditions as in clause 11, any control limiting the temperature during tests of clause 11 short-circuited		N/A
19.5	Test of 19.4 repeated on Class 0I and I appliances with tubular sheathed or embedded heating elements. No short-circuiting, but one end of the element connected to the sheath		N/A
	The test repeated with reversed polarity and the other end of the heating element connected to the sheath		N/A
	The test is not carried out on appliances intended to be permanently connected to fixed wiring and on appliances where an all-pole disconnection occurs during the test of 19.4		N/A
19.6	Appliances with PTC heating elements tested at rated voltage, establishing steady conditions		N/A

IEC 60335-2-7			
Clause	Requirement + Test	Result - Remark	Verdict
	The working voltage of the PTC heating element is increased by 5% and the appliance is operated until steady conditions are re-established. The voltage is then increased in similar steps until 1.5 times working voltage or until the PTC heating element ruptures (V) :		N/A
19.7	Stalling test by locking the rotor if the locked rotor torque is smaller than the full load torque, or	Wash motor	P
	locking moving parts of other appliances		N/A
	Locked rotor, capacitors open-circuited one at a time		P
	Test repeated with capacitors short-circuited one at a time, unless		N/A
	capacitor is of class S2 or S3 of IEC 60252-1		P
	Appliances with timer or programmer supplied with rated voltage for each of the tests, for a period equal to the maximum period allowed :	According to wash timer	P
	An electronic timer or programmer that operates to ensure compliance with the test before the maximum period under the conditions of Clause 11 is reached, is a protective electronic circuit		N/A
	Other appliances supplied with rated voltage for a period as specified..... :		N/A
	Winding temperatures not exceeding values specified in table 8..... :	(see appended table)	P
	Appliances without a programmer or timer are operated for 5 min..... (IEC 60335-2-7)		N/A
19.8	Multi-phase motors operated at rated voltage with one phase disconnected		N/A
19.9	The running overload test is carried out on appliances that have overload protective devices incorporating electronic circuits to protect the windings of the drum motor. However, the test is not carried out if the protective device senses the winding temperature directly. (IEC 60335-2-7)		N/A
19.10	Series motor operated at 1.3 times rated voltage for 1 min (V)..... :	No such motor	N/A
	During the test, parts not being ejected from the appliance		N/A
19.11	Electronic circuits, compliance checked by evaluation of the fault conditions specified in 19.11.2 for all circuits or parts of circuits, unless		N/A
	they comply with the conditions specified in 19.11.1		N/A

IEC 60335-2-7			
Clause	Requirement + Test	Result - Remark	Verdict
	Appliances incorporating an electronic circuit that relies upon a programmable component to function correctly, subjected to the test of 19.11.4.8, unless		N/A
	restarting does not result in a hazard		N/A
	Appliances having a device with an off position obtained by electronic disconnection, or a device placing the appliance in a stand-by mode, subjected to the tests of 19.11.4		N/A
	If the safety of the appliance under any of the fault conditions depends on the operation of a miniature fuse-link complying with IEC 60127, the test of 19.12 is carried out		N/A
	During and after each test the following is checked:		—
	- the temperature of the windings do not exceed the values specified in table 8		N/A
	- the appliance complies with the conditions specified in 19.13		N/A
	- any current flowing through protective impedance not exceeding the limits specified in 8.1.4		N/A
	If a conductor of a printed board becomes open-circuited, the appliance is considered to have withstood the particular test, provided both of the following conditions are met:		—
	- the base material of the printed circuit board withstands the test of Annex E		N/A
	- any loosened conductor does not reduce clearance or creepage distances between live parts and accessible metal parts below the values specified in clause 29		N/A
19.11.1	Fault conditions a) to g) in 19.11.2 are not applied to circuits or parts of circuits meeting both of the following conditions:		—
	- the electronic circuit is a low-power circuit, that is, the maximum power at low-power points does not exceed 15 W according to the tests specified		N/A
	- the protection against electric shock, fire hazard, mechanical hazard or dangerous malfunction of other parts of the appliance does not rely on the correct functioning of the electronic circuit		N/A
19.11.2	Fault conditions applied one at a time, the appliance operating under conditions specified in clause 11, but supplied at rated voltage, duration of the tests as specified:		—
	a) short circuit of functional insulation if clearances or creepage distances are less than the values specified in clause 29		N/A

IEC 60335-2-7			
Clause	Requirement + Test	Result - Remark	Verdict
	b) open circuit at the terminals of any component		N/A
	c) short circuit of capacitors, unless		N/A
	they comply with IEC 60384-14		N/A
	d) short circuit of any two terminals of an electronic component, other than integrated circuits		N/A
	This fault condition is not applied between the two circuits of an optocoupler		N/A
	e) failure of triacs in the diode mode		N/A
	f) failure of microprocessors and integrated circuits		N/A
	g) failure of an electronic power switching device		N/A
	Each low power circuit is short-circuited by connecting the low-power point to the pole of the supply source from which the measurements were made		N/A
19.11.3	If the appliance incorporates a protective electronic circuit that operates to ensure compliance with clause 19, the appliance is tested as specified		N/A
19.11.4	Appliances having a device with an off position obtained by electronic disconnection, or		N/A
	a device that can be placed in the stand-by mode,		N/A
	subjected to the tests of 19.11.4.1 to 19.11.4.7, the device being set in the off position or in the stand-by mode		N/A
	Appliances incorporating a protective electronic circuit subjected to the tests of 19.11.4.1 to 19.11.4.7, the tests being carried out after the protective electronic circuit has operated, except that		N/A
	Appliances operated for 30 s or 5 min during the test of 19.7 are not subjected to the tests for electromagnetic phenomena.		N/A
	Surge protective devices disconnected, unless		N/A
	They incorporate spark gaps		N/A
19.11.4.1	The appliance is subjected to electrostatic discharges in accordance with IEC 61000-4-2, test level 4		N/A
19.11.4.2	The appliance is subjected to radiated fields in accordance with IEC 61000-4-3, test level 3		N/A
19.11.4.3	The appliance is subjected to fast transient bursts in accordance with IEC 61000-4-4, test level 3 or 4 as specified		N/A

IEC 60335-2-7			
Clause	Requirement + Test	Result - Remark	Verdict
19.11.4.4	The power supply terminals of the appliance subjected to voltage surges in accordance with IEC 61000-4-5, test level 3 or 4 as specified		N/A
	An open circuit test voltage of 2 kV is applicable for the line-to-line coupling mode		N/A
	An open circuit test voltage of 4 kV is applicable for the line-to-earth coupling		N/A
	Earthed heating elements in class I appliances disconnected		N/A
19.11.4.5	The appliance is subjected to injected currents in accordance with IEC 61000-4-6, test level 3		N/A
19.11.4.6	Appliances having a rated current not exceeding 16 A are subjected to the Class 3 voltage dips and interruptions in accordance with IEC 61000-4-11		N/A
	Appliances having a rated current exceeding 16 A are subjected to the Class 3 voltage dips and interruptions in accordance with IEC 61000-4-34		N/A
19.11.4.7	The appliance is subjected to mains signals in accordance with IEC 61000-4-13, test level class 2		N/A
19.11.4.8	The appliance is supplied at rated voltage and operated under normal operation. After 60s the power supply is reduced to a level such that the appliance ceases to respond or parts controlled by the programmable component cease to operate		N/A
	The appliance continues to operate normally, or		N/A
	requires a manual operation to restart		N/A
19.12	If the safety of the appliance for any of the fault conditions specified in 19.11.2 depends on the operation of a miniature fuse-link complying with IEC 60127, the test is repeated, measuring the current flowing through the fuse-link; measured current (A); rated current of the fuse-link (A)..... :		N/A
19.13	During the tests the appliance does not emit flames, molten metal, poisonous or ignitable gas in hazardous amounts		P
	Temperature rises not exceeding the values shown in table 9..... :	(see appended table)	P
	Compliance with clause 8 not impaired		P
	If the appliance can still be operated it complies with 20.2		P
	Insulation, other than of class III appliances or class III constructions that do not contain live parts, withstands the electric strength test of 16.3, the test voltage as specified in table 4:		—

IEC 60335-2-7			
Clause	Requirement + Test	Result - Remark	Verdict
	- basic insulation (V)	1060 V	P
	- supplementary insulation (V).....	1810 V	P
	- reinforced insulation (V)	3120 V	P
	After operation or interruption of a control, clearances and creepage distances across the functional insulation withstand the electric strength test of 16.3, the test voltage being twice the working voltage		P
	The appliance does not undergo a dangerous malfunction, and		P
	no failure of protective electronic circuits, if the appliance is still operable		N/A
	Appliances tested with an electronic switch in the off position, or in the stand-by mode:		—
	- do not become operational, or		N/A
	- if they become operational, do not result in a dangerous malfunction during or after the tests of 19.11.4		N/A
	If the appliance contains lids or doors that are controlled by one or more interlocks, one of the interlocks may be released provided that:		—
	- the lid or door does not move automatically to an open position when the interlock is released, and		N/A
	- the appliance does not start after the cycle in which the interlock was released		N/A
	The textile material shall not ignite and shall not show any charring or glowing (IEC 60335-2-7)		N/A
	During the tests of 19.101 and 19.102, the temperature of windings shall not exceed the values specified in table 8. (IEC 60335-2-7)		N/A
	The appliance shall comply with 20.103 to 20.105 if it can still be operated. (IEC 60335-2-7)		N/A
19.14	Appliances operated under the conditions of clause 11, any contactor or relay contact operating under the conditions of clause 11 being short-circuited		N/A
	For a relay or contactor with more than one contact, all contacts are short-circuited at the same time		N/A
	A relay or contactor operating only to ensure the appliance is energized for normal use is not short-circuited		N/A
	If more than one relay or contactor operates in clause 11, they are short-circuited in turn		N/A

IEC 60335-2-7			
Clause	Requirement + Test	Result - Remark	Verdict
19.15	For appliances with a mains voltage selector switch, the switch is set to the lowest rated voltage position and the highest value of rated voltage is applied		N/A
19.101	Fault conditions applied, appliance supplied at rated voltage and operated under normal operation. (IEC 60335-2-7)		—
	-programmer stopping in any position		N/A
	-disconnection and reconnection of one or more phases of the supply		N/A
	-open-circuiting or short-circuiting of components		N/A
	-failure of magnetic valve		N/A
	-failure or blocking the mechanical parts of water-level switch, except if		N/A
	-the cross-sectional area of the tube supplying the air chamber is greater than 500mm ² with a minimum dimension of 10mm, -the outlet of the chamber is at least 20mm above the highest water level, and -the tube connecting the air chamber to the water-level switch is fixed so that there is no likelihood of bending or pinching		N/A
	-puncture of the capillary tube of a thermostat		N/A
	-the steam generator is operating without water.		N/A
	If operation without water in appliance is a more unfavourable condition for starting any programme, tests with that programme are carried out with water valve closed. This valve is not closed after programme stated to operate (IEC 60335-2-7)		N/A
19.102	Appliances not intended for connection to the hot water supply and not provided with heating elements are operated under the conditions of cl. 11, except that they are supplied at rated voltage and filled with water at a temperature of 65 °C± 5°C (IEC 60335-2-7)		P
20	STABILITY AND MECHANICAL HAZARDS		—
20.1	Appliances having adequate stability		P
	The appliance is empty or filled as specified for normal operation, whichever is more unfavourable (IEC 60335-2-7)		P
	Doors and lids are closed and any castors turned to the most unfavourable position (IEC 60335-2-7)		P

IEC 60335-2-7			
Clause	Requirement + Test	Result - Remark	Verdict
	Tilting test through an angle of 10°, appliance placed on an inclined plane/horizontal support, not connected to the supply mains; appliance does not overturn		P
	Tilting test repeated on appliances with heating elements, angle of inclination increased to 15°		N/A
	Possible heating test in overturned position; temperature rise does not exceed values shown in table 9		N/A
20.2	Moving parts adequately arranged or enclosed as to provide protection against personal injury		N/A
	Protective enclosures, guards and similar parts are non-detachable, and		N/A
	have adequate mechanical strength		N/A
	Enclosures that can be opened by overriding an interlock are considered to be detachable parts		N/A
	Self-resetting thermal cut-outs and overcurrent protective devices not causing a hazard by unexpected closure		N/A
	Not possible to touch dangerous moving parts with the test probe described		N/A
20.101	Drum washing machines that are loaded from the top through an opening with a hinged lid shall incorporate an interlock that de-energizes the motor before door or lid opening exceeds 50mm (IEC 60335-2-7)		N/A
	If a removable or sliding lid is provided, the motor shall be de-energized as soon as the lid is removed or displaced and not possible to start motor unless the lid is in the closed position (IEC 60335-2-7)		N/A
	Compliance checked by inspection, by measurement and by the following test: test probe B of IEC 61032 is applied in order to try and release any interlock that is needed to comply with the requirement. The interlock shall not release. (IEC 60335-2-7)		N/A
20.102	Appliances shall not be affected by an unbalanced load (IEC 60335-2-7)		N/A
20.103	Drum washing machines that are loaded from the front or from the top, the door or lid shall be interlocked so that the appliance can only be operated when the door or lid is in the closed position (IEC 60335-2-7)		N/A

IEC 60335-2-7			
Clause	Requirement + Test	Result - Remark	Verdict
	Compliance checked by inspection, by measurement and by the following test: test probe B of IEC 61032 is applied in order to try and release any interlock that is needed to comply with the requirement. The interlock shall not release. (IEC 60335-2-7)		N/A
20.104	It shall not be possible to open the lid or door of the appliance while the speed exceeds 60 r/min if the drum has a rotational kinetic energy exceeding 1 500J, or a maximum peripheral speed exceeding (IEC 60335-2-7)		N/A
	-20 m/s for drums that rotate about the horizontal axis,		N/A
	-40 m/s for drums that rotate about the vertical axis,		N/A
	If compliance relies on the operation of an electronic circuit, the test is repeated under the following conditions applied separately: (IEC 60335-2-7): - the fault conditions in a) to g) of 19.11.2 applied one at a time to the electronic circuit; - the electromagnetic phenomena tests of 19.11.4.2 to 19.11.4.5 applied to the appliance.		N/A
	If the electronic circuit is programmable, the software shall contain measures to control the fault/error conditions specified in Table R.1 and is evaluated in accordance with the relevant requirements of Annex R. (IEC 60335-2-7)		N/A
20.105	Appliances shall have an automatic means for switching off the motor, or for reducing the drum speed to 60 r/min, when the lid or door is opened if the drum has a rotational kinetic energy not exceeding 1 500J, and a peripheral speed not exceeding -20 m/s for drums that rotate about the horizontal axis, -40 m/s for drums that rotate about the vertical axis (IEC 60335-2-7)		N/A
	If compliance relies on the operation of an electronic circuit, the test is repeated under the following conditions applied separately: (IEC 60335-2-7): - the fault conditions in a) to g) of 19.11.2 applied one at a time to the electronic circuit; - the electromagnetic phenomena tests of 19.11.4.2 to 19.11.4.5 applied to the appliance		N/A

IEC 60335-2-7			
Clause	Requirement + Test	Result - Remark	Verdict
	If the electronic circuit is programmable, the software shall contain measures to control the fault/error conditions specified in Table R.1 and is evaluated in accordance with the relevant requirements of Annex R. (IEC 60335-2-7)		N/A
20.106	For appliances with a front opening door having an opening dimension exceeding 200 mm, and drum volume exceeding 60 dm ³ , it shall not be possible to start or recommence the washing cycle until a separate means which controls the movement of the drum is operated manually, even after the door has been opened and closed again. (IEC 60335-2-7)		N/A
	Compliance is checked by inspection, measurement ignoring any non-metallic seal fitted in the door opening, and by the test described		N/A
	If compliance relies on the operation of an electronic circuit, the test is repeated under the following conditions applied separately: - the fault conditions in a) to g) of 19.11.2 applied one at a time to the electronic circuit; - the electromagnetic phenomena tests of 19.11.4.2 to 19.11.4.5 applied to the appliance.		N/A
	The washing cycle shall not start or recommence.		N/A
20.107	For appliances with a front opening door having an opening dimension exceeding 200 mm, and drum volume exceeding 60 dm ³ , it shall be possible to open from the inside the closed door, when the appliance is not energized or in a standby mode, with a force not exceeding 70 N. (IEC 60335-2-7)		N/A
	Compliance is checked by measurement, ignoring any non-metallic seal fitted in the door opening, and by applying a force of 70 N perpendicular to the plane of the closed door at a point furthest from the hinges accessible from the inside of the door..		N/A
	If the appliance is supplied with an additional decorative door, the test is carried out with this door closed		N/A
21	MECHANICAL STRENGTH		—
21.1	Appliance has adequate mechanical strength and is constructed as to withstand rough handling		P
	Checked by applying 3 blows to every point of the enclosure like to be weak, in accordance with test Ehb of IEC 60068-2-75, spring hammer test, with an impact energy of 0,5 J	Applied on control panel, timer/switch knob and rear enclosure cover.	P
	The appliance shows no damage impairing compliance with this standard, and		P

IEC 60335-2-7			
Clause	Requirement + Test	Result - Remark	Verdict
	compliance with 8.1, 15.1 and clause 29 not impaired		P
	If doubt, supplementary or reinforced insulation subjected to the electric strength test of 16.3		N/A
	If necessary, repetition of groups of three blows on a new sample		N/A
21.2	Accessible parts of solid insulation having strength to prevent penetration by sharp implements		P
	Test not applicable if the thickness of supplementary insulation is at least 1 mm and reinforced insulation at least 2 mm	Reinforced insulation: 2,2 mm for enclosure; Supplementary insulation: timer/switch knob:1,0 mm	P
	The insulation is tested as specified, and does withstand the electric strength test of 16.3		N/A
21.101	Lids and doors shall have adequate mechanical strength (IEC 60335-2-7)		N/A
	Compliance is checked by 21.101.1 for lids, and 21.101.2 for doors		N/A
21.101.1	A rubber hemisphere –diameter 70 mm, hardness between 40 and 50 HIR- is fixed to a cylinder – mass 20 kg- and dropped from a height of 100 mm onto the centre of the lid (IEC 60335-2-7)		N/A
	Test carried out 3 times, after which the lid shall not be damaged to such an extent that moving parts become accessible.		N/A
21.101.2	A vertically downwards force of 150 N is applied I the most unfavourable position to the door while it is open at an angle of $90^\circ \pm 5^\circ$. The force is maintained for 1 mm. (IEC 60335-2-7)		N/A
	After the test, the appliance shall not be damaged or deformed to such an extent that compliance with 20.103 to 20.105 is impaired (IEC 60335-2-7)		N/A
21.102	Lids shall have adequate resistance to distortion (IEC 60335-2-7)		N/A
	A force of 50 N is applied to the open lid in the most unfavourable direction and position. Test carried out 3 times , after which the hinges shall not have worked loose and the appliance shall not be damaged or deformed to such an extent that compliance with 20.103 to 20.105 is impaired (IEC 60335-2-7)		N/A
22	CONSTRUCTION		—

IEC 60335-2-7			
Clause	Requirement + Test	Result - Remark	Verdict
22.1	Appliance marked with the first numeral of the IP system, relevant requirements of IEC 60529 are fulfilled		N/A
22.2	Stationary appliance: means to ensure all-pole disconnection from the supply being provided:		—
	- a supply cord fitted with a plug, or		P
	- a switch complying with 24.3, or		N/A
	- a statement in the instruction sheet that a disconnection incorporated in the fixed wiring is to be provided, or		N/A
	- an appliance inlet		N/A
	Single-pole switches and single-pole protective devices for the disconnection of heating elements in single-phase, permanently connected class 01 and class I appliances, connected to the phase conductor		N/A
22.3	Appliance provided with pins: no undue strain on socket-outlets		N/A
	Applied torque not exceeding 0.25 Nm		N/A
	Pull force of 50N to each pin after the appliance has being placed in the heating cabinet; when cooled to room temperature the pins are not displaced by more than 1mm		N/A
	Each pin subjected to a torque of 0.4Nm; the pins are not rotating, unless		N/A
	rotating does not impair compliance with this standard		N/A
22.4	Appliance for heating liquids and appliance causing undue vibration not provided with pins for insertion into socket-outlets		N/A
22.5	No risk of electric shock when touching the pins of the plug, for appliances having a capacitor with rated capacitance equal to or greater than 0,1μF, the appliance being disconnected from the supply at the instant of voltage peak		P
	Voltage not exceeding 34 V (V)..... :	17 V	P
	If compliance relies on the operation of an electronic circuit, the electromagnetic phenomena tests of 19.11.4.3 and 19.11.4.4 are applied		N/A
	The discharge test is then repeated three times, voltage not exceeding 34 V (V) :		N/A

IEC 60335-2-7			
Clause	Requirement + Test	Result - Remark	Verdict
22.6	Electrical insulation not affected by condensing water or leaking liquid		P
	Electrical insulation of Class II appliances not affected if a hose ruptures or seal leaks	Class II construction	P
	Requirements relating to leakage from containers, hoses, coupling and similar parts of the appliance is not applicable to parts that withstand the ageing test specified in annex BB (IEC 60335-2-7)		N/A
22.7	Adequate safeguards against the risk of excessive pressure in appliances containing liquid or gases or having steam-producing devices		N/A
22.8	Electrical connections not subject to pulling during cleaning of compartments to which access can be gained without the aid of a tool, and that are likely to be cleaned in normal use		P
22.9	Insulation, internal wiring, windings, commutators and slip rings not exposed to oil, grease or similar substances, unless		P
	the substance has adequate insulating properties		N/A
22.10	Not possible to reset voltage-maintained non-self-resetting thermal cut-outs by the operation of an automatic switching device incorporated within the appliance, if:		N/A
	- a non-self-resetting thermal cut-out is required by the standard, and		N/A
	- a voltage maintained non-self-resetting thermal cut-out is used to meet it		N/A
	Non-self-resetting thermal motor protectors have a trip-free action, unless		N/A
	they are voltage maintained		N/A
	Reset buttons of non-self-resetting controls so located or protected that accidental resetting is unlikely		N/A
22.11	Reliable fixing of non-detachable parts that provide the necessary degree of protection against electric shock, moisture or contact with moving parts		P
	Obvious locked position of snap-in devices used for fixing such parts		P
	No deterioration of the fixing properties of snap-in devices used in parts that are likely to be removed during installation or servicing		N/A

IEC 60335-2-7			
Clause	Requirement + Test	Result - Remark	Verdict
	Tests as described	Push =pull=50 N forced on control panel and timer/switch knob	P
22.12	Handles, knobs etc. fixed in a reliable manner, if loosening result in a hazard		P
	Removing or fixing in wrong position of handles, knobs etc. indicating position of switches or similar components not possible, if resulting in a hazard		P
	A choking hazard does not apply to appliances for commercial use		N/A
	Axial force 15 N applied to parts, the shape being so that an axial pull is unlikely to be applied		N/A
	Axial force 30 N applied to parts, the shape being so that an axial pull is likely to be applied	Timer/switch knob	P
	If the part is removed and can be contained within the small parts cylinder, it is considered to be a choking hazard		N/A
22.13	Unlikely that handles, when gripped as in normal use, make the operator's hand touch parts having a temperature rise exceeding the value specified for handles which are held for short periods only		N/A
22.14	No ragged or sharp edges creating a hazard for the user in normal use, or during user maintenance		P
	No exposed pointed ends of self-tapping screws or other fasteners, likely to be touched by the user in normal use or during user maintenance		P
22.15	Storage hooks and the like for flexible cords smooth and well rounded		N/A
22.16	Automatic cord reels cause no undue abrasion or damage to the sheath of the flexible cord, no breakage of conductors strands and no undue wear of contacts		N/A
	Cord reel tested with 6000 operations, as specified		N/A
	Electric strength test of 16.3, voltage of 1000 V applied		N/A
22.17	Spacers not removable from the outside by hand or by means of a screwdriver or a spanner		N/A
22.18	Current-carrying parts and other metal parts resistant to corrosion		P
22.19	Driving belts not relied upon to provide the required level of insulation, unless		P
	constructed to prevent inappropriate replacement		N/A

IEC 60335-2-7			
Clause	Requirement + Test	Result - Remark	Verdict
22.20	Direct contact between live parts and thermal insulation effectively prevented, unless		P
	material used is non-corrosive, non-hygroscopic and non-combustible		N/A
22.21	Wood, cotton, silk, ordinary paper and fibrous or hygroscopic material not used as insulation, unless	No such materials	N/A
	impregnated		N/A
	This requirement does not apply to magnesium oxide and mineral ceramic fibres used for the electrical insulation of heating elements		N/A
22.22	Appliances not containing asbestos		P
22.23	Oils containing polychlorinated biphenyl (PCB) not used	No such materials	N/A
22.24	Bare heating elements, except in class III appliances or class III constructions that do not contain live parts, adequately supported		N/A
	In case of rupture, the heating conductor is unlikely to come in contact with accessible metal parts		N/A
22.25	Sagging heating conductors, except in class III appliances or class III constructions that do not contain live parts, cannot come into contact with accessible metal parts		N/A
22.26	For class III constructions the insulation between parts operating at safety extra-low voltage and other live parts complies with the requirements for double or reinforced insulation		N/A
22.27	Parts connected by protective impedance separated by double or reinforced insulation		N/A
22.28	Metal parts of Class II appliances conductively connected to gas pipes or in contact with water, separated from live parts by double or reinforced insulation		N/A
22.29	Class II appliances permanently connected to fixed wiring so constructed that the required degree of access to live parts is maintained after installation		N/A
22.30	Parts serving as supplementary or reinforced insulation fixed so that they cannot be removed without being seriously damaged, or		P
	so constructed that they cannot be replaced in an incorrect position, and so that if they are omitted, the appliance is rendered inoperable or manifestly incomplete		P

IEC 60335-2-7			
Clause	Requirement + Test	Result - Remark	Verdict
22.31	Neither clearances nor creepage distances over supplementary and reinforced insulation reduced below values specified in clause 29 as a result of wear		P
	Neither clearances nor creepage distances between live parts and accessible parts reduced below values for supplementary insulation if wires, screws etc. become loose		P
22.32	Supplementary and reinforced insulation constructed or protected against pollution so that clearances or creepage distances are not reduced below the values in clause 29		P
	Supplementary insulation of natural or synthetic rubber resistant to ageing, or arranged and dimensioned so that creepage distances are not reduced below values specified in 29.2		N/A
	Ceramic material not tightly sintered, similar materials or beads alone not used as supplementary or reinforced insulation		N/A
	Ceramic and similar porous material in which heating conductors are embedded is considered to be basic insulation, not reinforced insulation		N/A
	Oxygen bomb test at 70 °C for 96 h and 16 h at room temperature		N/A
22.33	Conductive liquids that are or may become accessible in normal use and conductive liquids that are in contact with unearthed accessible metal parts are not in direct contact with live parts,		P
	Electrodes not used for heating liquids		N/A
	For class II constructions, conductive liquids that are or may become accessible in normal use and conductive liquids that are in contact with unearthed accessible metal parts, not in direct contact with basic or reinforced insulation, unless		P
	the reinforced insulation consists of at least 3 layers		N/A
	For class II constructions, conductive liquids which are in contact with live parts, not in direct contact with reinforced insulation, unless		P
	the reinforced insulation consists of at least 3 layers		N/A
	An air layer not used as basic or supplementary insulation in a double insulation system if likely to be bridged by leaking liquid		N/A
22.34	Shafts of operating knobs, handles, levers etc. not live, unless		P

IEC 60335-2-7			
Clause	Requirement + Test	Result - Remark	Verdict
	the shaft is not accessible when the part is removed		N/A
22.35	For other than class III constructions, handles, levers and knobs, held or actuated in normal use, not becoming live in the event of a failure of basic insulation		P
	Such parts being of metal, and their shafts or fixings are likely to become live in the event of a failure of basic insulation, are either adequately covered by insulation material or their accessible parts are separated from their shafts or fixings by supplementary insulation		N/A
	This requirement does not apply to handles, levers and knobs on stationary appliances and cordless appliances, other than those of electrical components, provided they are reliably connected to an earthing terminal or earthing contact, or separated from live parts by earthed metal		N/A
	Insulating material covering metal handles, levers and knobs withstand the electric strength test of 16.3 for supplementary insulation		N/A
22.36	For appliances other than class III, handles continuously held in the hand in normal use so constructed that when gripped as in normal use, the operators hand is not likely to touch metal parts, unless		N/A
	they are separated from live parts by double or reinforced insulation		N/A
22.37	Capacitors in Class II appliances not connected to accessible metal parts and their casings, if of metal, separated from accessible metal parts by supplementary insulation, unless		N/A
	the capacitors comply with 22.42		N/A
22.38	Capacitors not connected between the contacts of a thermal cut-out		P
22.39	Lamp holders used only for the connection of lamps		N/A
22.40	Motor-operated appliances and combined appliances intended to be moved while in operation, or having accessible moving parts, fitted with a switch to control the motor. The actuating member of the switch being easily visible and accessible		N/A

IEC 60335-2-7			
Clause	Requirement + Test	Result - Remark	Verdict
	If the appliance cannot operate continuously, automatically or remotely without giving rise to a hazard, appliances for remote operation being fitted with a switch for stopping the operation. The actuating member of the switch being easily visible and accessible		N/A
22.41	No components, other than lamps, containing mercury	No such materials	N/A
22.42	Protective impedance consisting of at least two separate components		N/A
	Values specified in 8.1.4 not exceeded if any one of the components are short-circuited or open-circuited		N/A
	Resistors checked by the test of 14.1 a) in IEC 60065		N/A
	Capacitors checked by the tests for class Y capacitors in IEC 60384-14		N/A
22.43	Appliances adjustable for different voltages, accidental changing of the setting of the voltage unlikely to occur		N/A
22.44	Appliances not having an enclosure that is shaped or decorated like a toy		P
22.45	When air is used as reinforced insulation, clearances not reduced below the values specified in 29.1.3 due to deformation as a result of an external force applied to the enclosure		P
22.46	For programmable protective electronic circuits used to ensure compliance with the standard, the software contains measures to control the fault/error conditions in table R.1		N/A
	Software that contains measures to control the fault/error conditions specified in table R.2 is to be specified in parts 2 for particular constructions or to address specific hazards		N/A
	These requirements are not applicable to software used for functional purpose or compliance with clause 11		N/A
22.47	Appliances connected to the water mains withstand the water pressure expected in normal use		P
	No leakage from any part, including any inlet water hose		P
22.48	Appliances connected to the water mains constructed to prevent backsiphonage of non-potable water		P

IEC 60335-2-7			
Clause	Requirement + Test	Result - Remark	Verdict
22.49	For remote operation, the duration of operation is to be set before the appliance can be started, unless		N/A
	the appliance switches off automatically or can operate continuously without hazard		N/A
22.50	Controls incorporated in the appliance take priority over controls actuated by remote operation		N/A
22.51	There is a control on the appliance manually adjusted to the setting for remote operation before the appliance can be operated in this mode		N/A
	There is a visual indication showing that the appliance is adjusted for remote operation		N/A
	These requirements not necessary on appliances that can operate as follows, without giving rise to a hazard:		—
	- continuously, or		N/A
	- automatically, or		N/A
	- remotely		N/A
22.52	Socket-outlets on appliances accessible to the user in accordance with the socket-outlet system used in the country in which the appliance is sold		N/A
22.53	Class II appliances and class III appliances that incorporate functionally earthed parts have at least double insulation or reinforced insulation between live parts and the functionally earthed parts		N/A
22.54	Button cells and batteries designated R1 not accessible without the aid of a tool, unless		N/A
	the cover of their compartment can only be opened after at least two independent movements have been applied simultaneously		N/A
22.55	Devices operated to stop the intended function of the appliance, if any, are to be distinguished from other manual devices by means of shape, size, surface texture or position	Position	P
	The requirement concerning position does not preclude use of a push on push off switch		N/A
	An indication when the device has been operated is given by:		—
	– tactile feedback from the actuator or from the appliance, or		P
	– reduction in heat output; or		N/A
	– audible and visible feedback		N/A
22.56	Detachable power supply part provided with the part of class III construction		N/A

IEC 60335-2-7			
Clause	Requirement + Test	Result - Remark	Verdict
22.57	The properties of non-metallic materials do not degrade from exposure to UV-C radiation, as specified in Annex T		N/A
	This requirement does not apply to glass, ceramics or similar materials		N/A
22. 101	Appliances shall be constructed so that when the water level is above the lower edge of the door opening, it shall not be possible to open the door by a simple action while the appliance is operating. (IEC 60335-2-7)		N/A
	Requirement not applicable to appliance fitted with interlocked doors or doors that are opened by means of a key or by 2 separate actions, such as pushing and turning.		N/A
	If compliance relies on the operation of an electronic circuit and the appliance is capable of providing a wash water temperature of 60 °C or higher or is marked as having a wash water temperature of 60 °C or higher, the test is repeated under the following conditions applied: separately: - fault conditions 19.11.2 - electromagnetic phenomena test 19.11.4.2 and .5 It shall not be possible to open the lid or door by a simple action		N/A
	If the electronic circuit is programmable, the software shall contain measures to control the fault/error conditions specified in Table R.1 and is evaluated in accordance with the relevant requirements of Annex R.		N/A
22.102	Textile material cannot come in contact with heating element (IEC 60335-2-7)		N/A
22.103	Appliances shall be constructed so that, during normal use, filter compartments cannot be opened by a simple action. (IEC 60335-2-7)		N/A
	This requirement is not applicable to appliances intended for connection to the cold water supply only and without means to heat the water or to appliances fitted with filter compartment covers that are : (IEC 60335-2-7) – interlocked; – opened by means of a key; – opened by two separate actions such as pushing and turning; or – opened by rotating by more than 180 °.		N/A
22.104	Lid and door interlocks shall be constructed so that they are unlikely to be forced open in normal use (IEC 60335-2-7)		N/A

IEC 60335-2-7			
Clause	Requirement + Test	Result - Remark	Verdict
22.105	Any mechanical release mechanism intended to open the loading door after a failure shall only be accessible by using a tool. (IEC 60335-2-7)		N/A
22.106	Steam generators shall be vented to the atmosphere. The aperture shall be at least 5 mm in diameter or at least 20 mm ² in area with a minimum dimension of 3 mm. (IEC 60335-2-7)		N/A
22.107	Appliances with steam generators shall be constructed in such a way that there is no spillage of water or sudden jets of steam or hot water likely to expose the user to a hazard when the appliance is used in accordance with the instructions. (IEC 60335-2-7)		N/A
	If jets of steam or liquids are emitted through protective devices, the electrical insulation shall not be affected or the user exposed to a hazard.		N/A
22.108	For appliances that are controlled by programmable electronic circuits that limit the number of heating elements and motors from being energised at the same time, simultaneous activation of any combination of heating elements and motors shall not render the appliance unsafe. (IEC 60335-2-7)		N/A
23	INTERNAL WIRING		—
23.1	Wireways smooth and free from sharp edges		P
	Wires protected against contact with burrs, cooling fins etc.		P
	Wire holes in metal well-rounded or provided with bushings		N/A
	Wiring effectively prevented from coming into contact with moving parts		P
23.2	Beads etc. on live wires cannot change their position, and are not resting on sharp edges		N/A
	Beads inside flexible metal conduits contained within an insulating sleeve		N/A
23.3	Electrical connections and internal conductors movable relatively to each other not exposed to undue stress		N/A
	Flexible metallic tubes not causing damage to insulation of conductors		N/A
	Open-coil springs not used		N/A
	Adequate insulating lining provided inside a coiled spring, the turns of which touch one another		N/A
	No damage after 10 000 flexings for conductors flexed during normal use, or		N/A

IEC 60335-2-7			
Clause	Requirement + Test	Result - Remark	Verdict
	100 flexings for conductors flexed during user maintenance		N/A
	Electric strength test of 16.3, 1000 V between live parts and accessible metal parts		N/A
	Not more than 10% of the strands of any conductor broken, and		N/A
	not more than 30% for wiring supplying circuits that consume no more than 15W		N/A
23.4	Bare internal wiring sufficiently rigid and fixed		N/A
23.5	The insulation of internal wiring subjected to the supply mains voltage withstanding the electrical stress likely to occur in normal use		P
	Basic insulation electrically equivalent to the basic insulation of cords complying with IEC 60227 or IEC 60245, or		P
	no breakdown when a voltage of 2000 V is applied for 15 min between the conductor and metal foil wrapped around the insulation		P
	For class II construction, the requirements for supplementary insulation and reinforced insulation apply,		N/A
	except that the sheath of a cord complying with IEC 60227 or IEC 60245 may provide supplementary insulation.		N/A
	A single layer of internal wiring insulation does not provide reinforced insulation		N/A
23.6	Sleeving used as supplementary insulation on internal wiring retained in position by clamping at both ends, or		P
	be such that it can only be removed by breaking or cutting		P
23.7	The colour combination green/yellow only used for earthing conductors		P
23.8	Aluminium wires not used for internal wiring	No aluminium wiring was used.	P
23.9	Stranded conductors not consolidated by soldering where they are subjected to contact pressure, unless		N/A
	the contact pressure is provided by spring terminals		N/A

IEC 60335-2-7			
Clause	Requirement + Test	Result - Remark	Verdict
23.10	The insulation and sheath of internal wiring, incorporated in external hoses for the connection of an appliance to the water mains, at least equivalent to that of light polyvinyl chloride sheathed flexible cord (60227 IEC 52)		N/A
23.101	Insulation and sheath of internal wiring for the supply of magnetic valves and similar components shall be at least equivalent to the electrical characteristics of light polyvinyl chloride sheathed flexible cord (code designation 60227 IEC 52) (IEC 60335-2-7)		N/A
24	COMPONENTS		—
24.1	Components comply with safety requirements in relevant IEC standards		P
	List of components..... :	(see appended table)	P
	Motors not required to comply with IEC 60034-1, they are tested as part of the appliance		P
	Relays tested as part of the appliance, or		N/A
	alternatively acc. to IEC 60730-1, and meeting the additional requirements in IEC 60335-1		P
	The requirements of Clause 29 apply between live parts of components and accessible parts of the appliance		P
	Components can comply with the requirements for clearances and creepage distances for functional insulation in the relevant component standard		P
	30.2 of this standard apply to parts of non-metallic material in components including parts of non-metallic material supporting current-carrying connections		P
	Components that have not been previously tested to comply with the IEC standard for the relevant component are tested according to the requirements of 30.2		P
	Components that have been previously tested to comply with the resistance to fire requirements in the IEC standard for the relevant component need not be retested provided the specified conditions are met		N/A
	If these conditions are not satisfied, the component is tested as part of the appliance.		P
	Power electronic converter circuits not required to comply with IEC 62477-1, they are tested as part of the appliance		N/A

IEC 60335-2-7			
Clause	Requirement + Test	Result - Remark	Verdict
	If components have not been tested and found to comply with relevant IEC standard for the number of cycles specified, they are tested in accordance with 24.1.1 to 24.1.9		N/A
	For components mentioned in 24.1.1 to 24.1.9 no additional tests specified in the relevant component standard are necessary other than those specified in 24.1.1 to 24.1.9		N/A
	Components not tested and found to comply with relevant IEC standard and components not marked or not used in accordance with its marking, tested under the conditions occurring in the appliance		P
	Lampholders and starterholders that have not being tested and found to comply with the relevant IEC standard, tested as a part of the appliance and additionally according to the gauging and interchangeability requirements of the relevant IEC standard		N/A
	No additional tests specified for nationally standardized plugs such as those detailed in IEC/TR 60083 or connectors complying with the standard sheets of IEC 60320-1 and IEC 60309		P
24.1.1	Capacitors likely to be permanently subjected to the supply voltage and used for radio interference suppression or for voltage dividing, complying with IEC 60384-14		N/A
	If the capacitors have to be tested, they are tested according to Annex F		N/A
24.1.2	Transformers in associated switch mode power supplies comply with Annex BB of IEC 61558-2-16		N/A
	Safety isolating transformers complying with IEC 61558-2-6		N/A
	If they have to be tested, they are tested according to Annex G		N/A
24.1.3	Switches complying with IEC 61058-1, the number of cycles of operation being at least 10 000	Washing switch: XZK	N/A
	If they have to be tested, they are tested according to Annex H	Approved select switch	P
	If the switch operates a relay or contactor, the complete switching system is subjected to the test		N/A
	If the switch only operates a motor starting relay complying with IEC 60730-2-10 with the number of cycles of a least 10 000 as specified, the complete switching system need not be tested		N/A

IEC 60335-2-7			
Clause	Requirement + Test	Result - Remark	Verdict
24.1.4	Automatic controls complying with IEC 60730-1 with the relevant part 2. The number of cycles of operation being at least:		—
	- thermostats: 10 000		N/A
	- temperature limiters: 1 000		N/A
	- self-resetting thermal cut-outs: 300		N/A
	- voltage maintained non-self-resetting thermal cut-outs: 1 000		N/A
	- other non-self-resetting thermal cut-outs: 30		N/A
	- timers: 3 000	Approved wash timer	P
	- energy regulators: 10 000		N/A
	- programmers : (IEC 60335-2-7) 3 000		N/A
	The number of cycles for controls operating during clause 11 need not be declared, if the appliance meets the requirements of this standard when they are short-circuited		N/A
	Thermal motor protectors are tested in combination with their motor under the conditions specified in Annex D		P
	For water valves containing live parts and that are incorporated in external hoses for connection of an appliance to the water mains, the degree of protection declared for subclause 6.5.2 of IEC 60730-2-8 is IPX7		N/A
	Thermal cut-outs of the capillary type comply with the requirements for type 2.K controls in IEC 60730-2-9		N/A
	For lid or door interlocks, the number of cycles of operation declared for subclauses 6.10 and 6.11 of IEC 60730-2-12 shall not be less than (IEC 60335-2-7)		—
	-6 000		N/A
	-for washing machines including drying operation: 9 000		N/A
	-interlock operates more than once during normal operation, the minimum number of cycles is increased accordingly.		N/A
24.1.5	Appliance couplers complying with IEC 60320-1		N/A
	However, for appliances classified higher than IPX0, the appliance couplers complying with IEC 60320-2-3		N/A

IEC 60335-2-7			
Clause	Requirement + Test	Result - Remark	Verdict
	Interconnection couplers complying with IEC 60320-2-2		N/A
24.1.6	Small lamp holders similar to E10 lampholders complying with IEC 60238, the requirements for E10 lampholders being applicable		N/A
24.1.7	For remote operation of the appliance via a telecommunication network, the relevant standard for the telecommunication interface circuitry in the appliance is IEC 62151		N/A
24.1.8	The relevant standard for thermal links is IEC 60691		N/A
	Thermal links not complying with IEC 60691 are considered to be an intentionally weak part for the purposes of Clause 19		N/A
24.1.9	Contactors and relays, other than motor starting relays, tested as part of the appliance		N/A
	They are also tested in accordance with Clause 17 of IEC 60730-1, the number of cycles of operations in 24.1.4 selected according to the contactor or relay function in the appliance..... :		N/A
24.2	Appliances not fitted with:		—
	- switches, automatic controls or power supplies in flexible cords		P
	- devices causing the protective device in the fixed wiring to operate in the event of a fault in the appliance		P
	- thermal cut-outs that can be reset by soldering, unless		N/A
	the solder has a melting point of at least 230 °C		N/A
24.3	Switches intended for all-pole disconnection of stationary appliances are directly connected to the supply terminals and have a contact separation in all poles, providing full disconnection under overvoltage category III conditions		N/A
24.4	Plugs and socket-outlets for extra-low voltage circuits and heating elements, not interchangeable with plugs and socket-outlets listed in IEC/TR 60083 or IEC 60906-1 or with connectors and appliance inlets complying with the standard sheets of IEC 60320-1		N/A
24.5	Capacitors in auxiliary windings of motors marked with their rated voltage and capacitance, and used accordingly		P

IEC 60335-2-7			
Clause	Requirement + Test	Result - Remark	Verdict
	Voltage across capacitors in series with a motor winding does not exceed 1,1 times rated voltage, when the appliance is supplied at 1,1 times rated voltage under minimum load	Rated: 450 V, Measured: 330 V	P
24.6	Working voltage of motors connected to the supply mains and having basic insulation that is inadequate for the rated voltage of the appliance, not exceeding 42 V		N/A
	In addition, the motors comply with the requirements of Annex I		N/A
24.7	Detachable hose-sets for connection of appliances to the water mains comply with IEC 61770		N/A
	They are supplied with the appliance		N/A
	Appliances intended to be permanently connected to the water mains not connected by a detachable hose-set		N/A
24.8	Motor running capacitors in appliances for which 30.2.3 is applicable and that are permanently connected in series with a motor winding, not causing a hazard in event of a failure		P
	One or more of the following conditions are to be met:		—
	- the capacitors are of class S2 or S3 according to IEC 60252-1		P
	- the capacitors are housed within a metallic or ceramic enclosure		N/A
	- the distance of separation of the outer surface to adjacent non-metallic parts exceeds 50 mm		N/A
	- adjacent non-metallic parts within 50 mm withstand the needle-flame test of Annex E		N/A
	- adjacent non-metallic parts within 50 mm classified as at least V-1 according to IEC 60695-11-10		N/A
24.101	Thermal cut-outs incorporated in washing machines for compliance with 19.4 shall be not self-resetting (IEC 60335-2-7)		N/A
	Compliance is checked by inspection		N/A
25	SUPPLY CONNECTION AND EXTERNAL FLEXIBLE CORDS		—
25.1	Appliance not intended for permanent connection to fixed wiring, means for connection to the supply:		—

IEC 60335-2-7			
Clause	Requirement + Test	Result - Remark	Verdict
	- supply cord fitted with a plug, the current rating and voltage rating of the plug being not less than the corresponding ratings of its associated appliance		P
	- an appliance inlet having at least the same degree of protection against moisture as required for the appliance, or		N/A
	- pins for insertion into socket-outlets		N/A
25.2	Appliance not provided with more than one means of connection to the supply mains		P
	Stationary appliance for multiple supply may be provided with more than one means of connection, provided electric strength test of 1250 V for 1 min between each means of connection causes no breakdown		N/A
25.3	Appliance intended to be permanently connected to fixed wiring provided with one of the following means for connection to the supply mains:		—
	- a set of terminals allowing the connection of a flexible cord		N/A
	- a fitted supply cord		N/A
	- a set of supply leads accommodated in a suitable compartment		N/A
	- a set of terminals for the connection of cables of fixed wiring, cross-sectional areas specified in 26.6, and the appliance allows the connection of the supply conductors after the appliance has been fixed to its support		N/A
	- a set of terminals and cable entries, conduit entries, knock-outs or glands, allowing connection of appropriate types of cable or conduit, and the appliance allows the connection of the supply conductors after the appliance has been fixed to its support		N/A
	For a fixed appliance constructed so that parts can be removed to facilitate easy installation, this requirement is met if it is possible to connect the fixed wiring without difficulty after a part of the appliance has been fixed to its support		N/A
25.4	Cable and conduit entries, rated current of appliance not exceeding 16 A, dimension according to table 10 (mm)..... :		N/A
	Introduction of conduit or cable does not reduce clearances or creepage distances below values specified in clause 29		N/A

IEC 60335-2-7			
Clause	Requirement + Test	Result - Remark	Verdict
25.5	Method for assembling the supply cord to the appliance:		—
	- type X attachment		N/A
	- type Y attachment		P
	- type Z attachment, if allowed in relevant part 2		N/A
	Type X attachment, other than those with a specially prepared cord, not used for flat twin tinsel cords		N/A
	For multi-phase appliances supplied with a supply cord and that are intended to be permanently connected to fixed wiring, the supply cord is assembled to the appliance by type Y attachment		N/A
25.6	Plugs fitted with only one flexible cord		P
25.7	Supply cords, other than for class III appliances, being one of the following types:		—
	- rubber sheathed (at least 60245 IEC 53)		N/A
	- polychloroprene sheathed (at least 60245 IEC 57)		N/A
	- polyvinyl chloride sheathed. Not used if they are likely to touch metal parts having a temperature rise exceeding 75 K during the test of clause 11		—
	light polyvinyl chloride sheathed cord (60227 IEC 52), for appliances not exceeding 3 kg		N/A
	ordinary polyvinyl chloride sheathed cord (60227 IEC 53), for other appliances	H05VV-F 60227 IEC 53	P
	- heat resistant polyvinyl chloride sheathed. Not used for type X attachment other than specially prepared cords		—
	heat-resistant light polyvinyl chloride sheathed cord (60227 IEC 56), for appliances not exceeding 3 kg		N/A
	heat-resistant polyvinyl chloride sheathed cord (60227 IEC 57), for other appliances		N/A
	- halogen-free, low smoke, thermoplastic insulated and sheathed		—
	light duty halogen-free low smoke flexible cable (62821 IEC 101) for circular cable and (62821 IEC 101f) for flat cable		N/A
	Ordinary duty halogen-free low smoke flexible cable (62821 IEC 102) for circular cable and (62821 IEC 102f) for flat cable		N/A
	Supply cords for class III appliances adequately insulated		N/A
	Test with 500 V for 2 min for supply cords of class III appliances that contain live parts		N/A

IEC 60335-2-7			
Clause	Requirement + Test	Result - Remark	Verdict
25.8	Nominal cross-sectional area of supply cords not less than table 11; rated current (A); cross-sectional area (mm ²)..... :	Current measured: max. 1,8 A; Supply cord: 0,75 mm ²	P
25.9	Supply cords not in contact with sharp points or edges		P
25.10	Supply cord of class I appliances have a green/yellow core for earthing		P
	In multi-phase appliances, the colour of the neutral conductor of the supply cord is blue.		N/A
	Where additional neutral conductors are provided in the supply cord:		—
	– other colours may be used for these additional neutral conductors;		N/A
	– all of the neutral conductors and line conductors are identified by marking using the alpha numeric notation specified in IEC 60445		N/A
	– the supply cord is fitted to the appliance		N/A
25.11	Conductors of supply cords not consolidated by soldering where they are subject to contact pressure, unless		P
	the contact pressure is provided by spring terminals		N/A
25.12	Insulation of the supply cord not damaged when moulding the cord to part of the enclosure		P
25.13	Inlet openings so constructed as to prevent damage to the supply cord		P
	If it is not evident that the supply cord can be introduced without risk of damage,, a non-detachable lining or bushing complying with 29.3 for supplementary insulation provided		P
	If unsheathed supply cord, a similar additional bushing or lining is required, unless the appliance is		N/A
	class 0, or		N/A
	a class III appliance not containing live parts		N/A
25.14	Supply cords moved while in operation adequately protected against excessive flexing		N/A
	Flexing test, as described:		—
	- applied force (N) :		N/A
	- number of flexings :		N/A
	The test does not result in:		—

IEC 60335-2-7			
Clause	Requirement + Test	Result - Remark	Verdict
	- short-circuit between the conductors, such that the current exceeds a value of twice the rated current		N/A
	- breakage of more than 10% of the strands of any conductor		N/A
	- separation of the conductor from its terminal		N/A
	- loosening of any cord guard		N/A
	- damage to the cord or the cord guard		N/A
	- broken strands piercing the insulation and becoming accessible		N/A
25.15	For appliances with supply cord and appliances to be permanently connected to fixed wiring by a flexible cord, conductors of the supply cord relieved from strain, twisting and abrasion by use of cord anchorage		P
	The cord cannot be pushed into the appliance to such an extent that the cord or internal parts of the appliance can be damaged		P
	Pull and torque test of supply cord:		—
	- fixed appliances: pull 100 N; torque (not on automatic cord reel) (Nm) :		N/A
	- other appliances: values shown in table 12: mass (kg); pull (N); torque (not on automatic cord reel) (Nm) :	Pull force:100 N Torque: 0,35 Nm	P
	Cord not damaged and max. 2 mm displacement of the cord	0,8 mm	P
25.16	Cord anchorages for type X attachments constructed and located so that:		—
	- replacement of the cord is easily possible		N/A
	- it is clear how the relief from strain and the prevention of twisting are obtained		N/A
	- they are suitable for different types of supply cord		N/A
	- cord cannot touch the clamping screws of cord anchorage if these screws are accessible, unless		N/A
	they are separated from accessible metal parts by supplementary insulation		N/A
	- the cord is not clamped by a metal screw which bears directly on the cord		N/A
	- at least one part of the cord anchorage securely fixed to the appliance, unless		N/A
	it is part of a specially prepared cord		N/A

IEC 60335-2-7			
Clause	Requirement + Test	Result - Remark	Verdict
	- screws which have to be operated when replacing the cord do not fix any other component, unless		N/A
	the appliance becomes inoperative or incomplete or the parts cannot be removed without a tool		N/A
	- if labyrinths can be bypassed the test of 25.15 is nevertheless withstood		N/A
	- for class 0, 0I and I appliances they are of insulating material or are provided with an insulating lining, unless		N/A
	failure of the insulation of the cord does not make accessible metal parts live		N/A
	- for class II appliances they are of insulating material, or		N/A
	if of metal, they are insulated from accessible metal parts by supplementary insulation		N/A
	After the test of 25.15, under the conditions specified, the conductors have not moved by more than 1 mm in the terminals		N/A
25.17	Adequate cord anchorages for type Y and Z attachment, test with the cord supplied with the appliance	Type Y attachment	P
25.18	Cord anchorages only accessible with the aid of a tool, or		N/A
	Constructed so that the cord can only be fitted with the aid of a tool		P
25.19	Type X attachment, glands not used as cord anchorage in portable appliances		N/A
	Tying the cord into a knot or tying the cord with string not used		N/A
25.20	The conductors of the supply cord for type Y and Z attachment insulated from accessible metal parts		P
25.21	Space for supply cord for type X attachment or for connection of fixed wiring constructed:		—
	- to permit checking of conductors with respect to correct positioning and connection before fitting any cover		N/A
	- so there is no risk of damage to the conductors or their insulation when fitting the cover		N/A
	- for portable appliances, so that the uninsulated end of a conductor, if it becomes free from the terminal, prevented from contact with accessible metal parts		N/A

IEC 60335-2-7			
Clause	Requirement + Test	Result - Remark	Verdict
	2 N test to the conductor for portable appliances; no contact with accessible metal parts		N/A
25.22	Appliance inlets:		—
	- live parts not accessible during insertion or removal		N/A
	Requirement not applicable to appliance inlets complying with IEC 60320-1		N/A
	- connector can be inserted without difficulty		N/A
	- the appliance is not supported by the connector		N/A
	- not for cold conditions if temp. rise of external metal parts exceeds 75 K during clause 11, unless		N/A
	the supply cord is unlikely to touch such metal parts		N/A
25.23	Interconnection cords comply with the requirements for the supply cord, except that:		N/A
	- the cross-sectional area of the conductors is determined on the basis of the maximum current during clause 11		N/A
	- the thickness of the insulation may be reduced		N/A
	- for class I or class II appliance with class III construction, the cross sectional areas of the conductors need not comply with 25.8 if specified conditions are met		N/A
	If necessary, electric strength test of 16.3		N/A
25.24	Interconnection cords not detachable without the aid of a tool if compliance with this standard is impaired when they are disconnected		N/A
25.25	Dimensions of pins that are inserted into socket-outlets compatible with the dimensions of the relevant socket-outlet.		N/A
	Dimensions of pins and engagement face in accordance with the dimensions of the relevant plug in IEC/TR 60083		N/A
26	TERMINALS FOR EXTERNAL CONDUCTORS		—
26.1	Appliances provided with terminals or equally effective devices for connection of external conductors		P
	Terminals only accessible after removal of a non-detachable cover, except		P
	for class III appliances that do not contain live parts		N/A

IEC 60335-2-7			
Clause	Requirement + Test	Result - Remark	Verdict
	Earthing terminals may be accessible if a tool is required to make the connections and means are provided to clamp the wire independently from its connection		N/A
26.2	Appliances with type X attachment and appliances for the connection of cables to fixed wiring provided with terminals in which connections are made by means of screws, nuts or similar devices, unless		N/A
	the connections are soldered		N/A
	Screws and nuts not used to fix any other component, except		N/A
	internal conductors, if so arranged that they are unlikely to be displaced when fitting the supply conductors		N/A
	If soldered connections used, the conductor so positioned or fixed that reliance is not placed on soldering alone, unless		N/A
	barriers provided so that neither clearances nor creepage distances between live parts and other metal parts reduced below the values for supplementary insulation if the conductor becomes free at the soldered joint		N/A
26.3	Terminals for type X attachment and for connection of cables of fixed wiring so constructed that the conductor is clamped between metal surfaces with sufficient contact pressure but without damaging the conductor		N/A
	Terminals fixed so that when the clamping means is tightened or loosened:		—
	- the terminal does not become loose		N/A
	- internal wiring is not subjected to stress		N/A
	- neither clearances nor creepage distances are reduced below the values in clause 29		N/A
	Compliance checked by inspection and by the test of subclause 9.6 of IEC 60999-1, the torque applied being equal to two-thirds of the torque specified (Nm)		N/A
	No deep or sharp indentations of the conductors		N/A
26.4	Terminals for type X attachment, except those having a specially prepared cord and those for the connection of cables of fixed wiring, no special preparation of conductors such as by soldering, use of cable lugs, eyelets or similar, and		N/A

IEC 60335-2-7			
Clause	Requirement + Test	Result - Remark	Verdict
	so constructed or placed that conductors prevented from slipping out when clamping screws or nuts are tightened		N/A
26.5	Terminals for type X attachment so located or shielded that if a wire of a stranded conductor escapes, no risk of accidental connection to other parts that result in a hazard		N/A
	Stranded conductor test, 8 mm insulation removed		N/A
	No contact between live parts and accessible metal parts and,		N/A
	for class II constructions, between live parts and metal parts separated from accessible metal parts by supplementary insulation only		N/A
26.6	Terminals for type X attachment and for connection of cables of fixed wiring suitable for connection of conductors with cross-sectional area according to table 13; rated current (A); nominal cross-sectional area (mm ²)..... :		N/A
	If a specially prepared cord is used, terminals need only be suitable for that cord		N/A
26.7	Terminals for type X attachment, except in class III appliances not containing live parts, accessible after removal of a cover or part of the enclosure		N/A
26.8	Terminals for the connection of fixed wiring, including the earthing terminal, located close to each other		N/A
26.9	Terminals of the pillar type constructed and located as specified		N/A
26.10	Terminals with screw clamping and screwless terminals not used for flat twin tinsel cords, unless		P
	conductors ends fitted with means suitable for screw terminals		P
	Pull test of 5 N to the connection		P
26.11	For type Y and Z attachment, soldered, welded, crimped or similar connections may be used	Crimped connections were used.	P
	For Class II appliances, the conductor so positioned or fixed that reliance is not placed on soldering, welding or crimping alone		N/A

IEC 60335-2-7			
Clause	Requirement + Test	Result - Remark	Verdict
	If soldering, welding or crimping alone used, barriers provided so that clearances and creepage distances between live parts and other metal parts are not reduced below the values for supplementary insulation if the conductor becomes free		N/A
27	PROVISION FOR EARTHING		—
27.1	Accessible metal parts of Class 0I and I appliances permanently and reliably connected to an earthing terminal or earthing contact of the appliance inlet		P
	Earthing terminals and earthing contacts not connected to the neutral terminal		P
	Class 0, II and III appliances have no provision for earthing		N/A
	Class II appliances and class III appliances can incorporate an earth for functional purposes		N/A
	Safety extra-low voltage circuits not earthed, unless		N/A
	protective extra-low voltage circuits		N/A
27.2	Clamping means of earthing terminals adequately secured against accidental loosening		P
	Terminals for the connection of external equipotential bonding conductors allow connection of conductors of 2.5 to 6 mm ² , and		N/A
	do not provide earthing continuity between different parts of the appliance, and		N/A
	conductors cannot be loosened without the aid of a tool		P
	Requirements not applicable to class II appliances and class III appliances that incorporate an earth for functional purposes		N/A
27.3	For a detachable part having an earth connection and being plugged into another part of the appliance, the earth connection is made before and separated after current-carrying connections when removing the part		N/A
	For appliances with supply cords, current-carrying conductors become taut before earthing conductor, if the cord slips out of the cord anchorage		P
	Requirements not applicable to class II appliances and class III appliances that incorporate an earth for functional purposes		N/A

IEC 60335-2-7			
Clause	Requirement + Test	Result - Remark	Verdict
27.4	No risk of corrosion resulting from contact between parts of the earthing terminal and the copper of the earthing conductor or other metal		P
	Parts providing earthing continuity, other than parts of a metal frame or enclosure, have adequate resistance to corrosion		P
	If of steel, these parts provided with an electroplated coating with a thickness at least 5 μm		N/A
	Adequate protection against rusting of parts of coated or uncoated steel, only intended to provide or transmit contact pressure		P
	In the body of the earthing terminal is a part of a frame or enclosure of aluminium or aluminium alloys, precautions taken to avoid risk of corrosion		N/A
	Requirements not applicable to class II appliances and class III appliances that incorporate an earth for functional purposes		N/A
27.5	Low resistance of connection between earthing terminal and earthed metal parts		P
	This requirement does not apply to connections providing earthing continuity in the protective extra-low voltage circuit, provided the clearances of basic insulation are based on the rated voltage of the appliance		N/A
	Requirements not applicable to class II appliances and class III appliances that incorporate an earth for functional purposes		N/A
	Resistance not exceeding 0,1 Ω at the specified low-resistance test (Ω)	0,02 Ω	P
27.6	The printed conductors of printed circuit boards not used to provide earthing continuity in hand-held appliances.		N/A
	They may be used to provide earthing continuity in other appliances if at least two tracks are used with independent soldering points and the appliance complies with 27.5 for each circuit		N/A
	Requirements not applicable to class II appliances and class III appliances that incorporate an earth for functional purposes		N/A
28	SCREWS AND CONNECTIONS		—
28.1	Fixings, electrical connections and connections providing earthing continuity withstand mechanical stresses		P

IEC 60335-2-7			
Clause	Requirement + Test	Result - Remark	Verdict
	Screws not of soft metal liable to creep, such as zinc or aluminium		P
	Diameter of screws of insulating material min. 3 mm		N/A
	Screws of insulating material not used for any electrical connections or connections providing earthing continuity		N/A
	Screws used for electrical connections or connections providing earthing continuity screwed into metal		P
	Screws not of insulating material if their replacement by a metal screw can impair supplementary or reinforced insulation		P
	For type X attachment, screws to be removed for replacement of supply cord or for user maintenance, not of insulating material if their replacement by a metal screw impairs basic insulation		N/A
	For screws and nuts; torque-test as specified in table 14	(see appended table)	P
28.2	Electrical connections and connections providing earthing continuity constructed so that contact pressure is not transmitted through non-ceramic insulating material liable to shrink or distort, unless		P
	there is resiliency in the metallic parts to compensate for shrinkage or distortion of the insulating material		N/A
	This requirement does not apply to electrical connections in circuits of appliances for which:		—
	30.2.2 is applicable and that carry a current not exceeding 0,5 A		N/A
	30.2.3 is applicable and that carry a current not exceeding 0,2 A		N/A
28.3	Space-threaded (sheet metal) screws only used for electrical connections if they clamp the parts together		P
	Thread-cutting (self-tapping) screws and thread rolling screws only used for electrical connections if they generate a full form standard machine screw thread		N/A
	Thread-cutting (self-tapping) screws not used if they are likely to be operated by the user or installer		N/A

IEC 60335-2-7			
Clause	Requirement + Test	Result - Remark	Verdict
	Thread-cutting, thread rolling and space threaded screws may be used in connections providing earthing continuity provided it is not necessary to disturb the connection:		—
	- in normal use,		N/A
	- during user maintenance,		N/A
	- when replacing a supply cord having a type X attachment, or		N/A
	- during installation		N/A
	At least two screws being used for each connection providing earthing continuity, unless		N/A
	the screw forms a thread having a length of at least half the diameter of the screw		N/A
28.4	Screws and nuts that make mechanical connection secured against loosening if they also make electrical connections or connections providing earthing continuity		P
	This requirement does not apply to screws in the earthing circuit if at least two screws are used, or		N/A
	if an alternative earthing circuit is provided		N/A
	Rivets for electrical connections or connections providing earthing continuity secured against loosening if the connections are subjected to torsion		N/A
29	CLEARANCES, CREEPAGE DISTANCES AND SOLID INSULATION		—
	Clearances, creepage distances and solid insulation withstand electrical stress		P
	For coatings used on printed circuits boards to protect the microenvironment (Type 1) or to provide basic insulation (Type 2), Annex J applies..... :		N/A
	The microenvironment is pollution degree 1 under type 1 protection		N/A
	For type 2 protection, the spacing between the conductors before the protection is applied is not less than the values specified in Table 1 of IEC 60664-3		N/A
	These values apply to functional, basic, supplementary and reinforced insulation :		N/A
29.1	Clearances not less than the values specified in table 16, taking into account the rated impulse voltage for the overvoltage categories of table 15, unless..... :	(see appended table)	P

IEC 60335-2-7			
Clause	Requirement + Test	Result - Remark	Verdict
	for basic insulation and functional insulation they comply with the impulse voltage test of clause 14		N/A
	However, if the distances are affected by wear, distortion, movement of the parts or during assembly, the clearances for rated impulse voltages of 1500V and above are increased by 0,5 mm and the impulse voltage test is not applicable		P
	For appliances intended for use at altitudes exceeding 2 000 m, the clearances in Table 16 is increased according to the relevant multiplier values in Table A.2 of IEC 60664-1		N/A
	Impulse voltage test is not applicable:		—
	- when the microenvironment is pollution degree 3, or		P
	- for basic insulation of class 0 and class 01 appliances		N/A
	- to appliances intended for use at altitudes exceeding 2 000 m		N/A
	Appliances are in overvoltage category II		P
	A force of 2 N is applied to bare conductors, other than heating elements		N/A
	A force of 30 N is applied to accessible surfaces		P
29.1.1	Clearances of basic insulation withstand the overvoltages, taking into account the rated impulse voltage		P
	The values of table 16 or the impulse voltage test of clause 14 are applicable	(see appended table)	P
	Clearance at the terminals of tubular sheathed heating elements may be reduced to 1,0 mm if the microenvironment is pollution degree 1		N/A
	Lacquered conductors of windings considered to be bare conductors		P
29.1.2	Clearances of supplementary insulation not less than those specified for basic insulation in table 16	(see appended table)	P
29.1.3	Clearances of reinforced insulation not less than those specified for basic insulation in table 16, using the next higher step for rated impulse voltage	(see appended table)	P

IEC 60335-2-7			
Clause	Requirement + Test	Result - Remark	Verdict
	For double insulation, with no intermediate conductive part between basic and supplementary insulation, clearances are measured between live parts and the accessible surface, and the insulation system is treated as reinforced insulation		P
29.1.4	Clearances for functional insulation are the largest values determined from:		—
	- table 16 based on the rated impulse voltage :	(see appended table)	P
	- table F.7a in IEC 60664-1, frequency not exceeding 30 kHz		N/A
	- clause 4 of IEC 60664-4, frequency exceeding 30 kHz		N/A
	If values of table 16 are largest, the impulse voltage test of clause 14 may be applied instead, unless		N/A
	the microenvironment is pollution degree 3, or		P
	the distances can be affected by wear, distortion, movement of the parts or during assembly		N/A
	However, clearances are not specified if the appliance complies with clause 19 with the functional insulation short-circuited		N/A
	Lacquered conductors of windings considered to be bare conductors		P
	However, clearances at crossover points are not measured		P
	Clearance between surfaces of PTC heating elements may be reduced to 1mm		N/A
29.1.5	Appliances having higher working voltages than rated voltage, clearances for basic insulation are the largest values determined from:		—
	- table 16 based on the rated impulse voltage :	(see appended table)	P
	- table F.7a in IEC 60664-1, frequency not exceeding 30 kHz		N/A
	- clause 4 of IEC 60664-4, frequency exceeding 30 kHz		N/A
	If clearances for basic insulation are selected from Table F.7a of IEC 60664-1 or Clause 4 of IEC 60664-4, the clearances of supplementary insulation are not less than those specified for basic insulation		N/A
	If clearances for basic insulation are selected from Table F.7a of IEC 60664-1, the clearances of reinforced insulation dimensioned as specified in Table F.7a are to withstand 160% of the withstand voltage required for basic insulation		N/A

IEC 60335-2-7			
Clause	Requirement + Test	Result - Remark	Verdict
	If clearances for basic insulation are selected from Clause 4 of IEC 60664-4, the clearances of reinforced insulation are twice the value required for basic insulation		N/A
	If the secondary winding of a step-down transformer is earthed, or if there is an earthed screen between the primary and secondary windings, clearances of basic insulation on the secondary side not less than those specified in table 16, but using the next lower step for rated impulse voltage		N/A
	Circuits supplied with a voltage lower than rated voltage, clearances of functional insulation are based on the working voltage used as the rated voltage in table 15		P
29.2	Creepage distances not less than those appropriate for the working voltage, taking into account the material group and the pollution degree :	(see appended table)	P
	Pollution degree 2 applies, unless		N/A
	- precautions taken to protect the insulation; pollution degree 1		N/A
	- insulation subjected to conductive pollution; pollution degree 3		P
	A force of 2 N is applied to bare conductors, other than heating elements		N/A
	A force of 30 N is applied to accessible surfaces		P
	In a double insulation system, the working voltage for both the basic and supplementary insulation is taken as the working voltage across the complete double insulation system		P
	Pollution degree 3, and the insulation with a CTI not less than 250, (IEC 60335-2-7)		P
	Unless the insulation is enclosed or located so that it is unlikely to be exposed to pollution during normal use of the appliance due to :		—
	- condensation produced by the appliance		N/A
	- chemicals, such as detergent or fabric conditioner		N/A
	Compliance is checked by inspection and measurements as specified		P
29.2.1	Creepage distances of basic insulation not less than specified in table 17 :	(see appended table)	P

IEC 60335-2-7			
Clause	Requirement + Test	Result - Remark	Verdict
	However, if the working voltage is periodic and has a frequency exceeding 30 kHz, the creepage distances are also determined from table 2 of IEC 60664-4, these values being used if exceeding the values in table 17..... :		N/A
	Except for pollution degree 1, corresponding creepage distance not less than the minimum specified for the clearance in table 16, if the clearance has been checked according to the test of clause 14 :		N/A
29.2.2	Creepage distances of supplementary insulation at least those specified for basic insulation in table 17, or..... :	(see appended table)	P
	Table 2 of IEC 60664-4, as applicable..... :		N/A
29.2.3	Creepage distances of reinforced insulation at least double those specified for basic insulation in table 17, or..... :	(see appended table)	P
	Table 2 of IEC 60664-4, as applicable..... :		N/A
29.2.4	Creepage distances of functional insulation not less than specified in table 18 :	(see appended table)	P
	However, if the working voltage is periodic and has a frequency exceeding 30 kHz, the creepage distances are also determined from table 2 of IEC 60664-4, these values being used if exceeding the values in table 18..... :		N/A
	Creepage distances may be reduced if the appliance complies with clause 19 with the functional insulation short-circuited		N/A
29.3	Supplementary and reinforced insulation have adequate thickness, or a sufficient number of layers, to withstand the electrical stresses		P
	Compliance checked:		—
	- by measurement, in accordance with 29.3.1, or		P
	- by an electric strength test in accordance with 29.3.2, or		N/A
	- for insulation, other than single layer internal wiring insulation, by an assessment of the thermal quality of the material combined with an electric strength test, in accordance with 29.3.3, and		N/A
	for accessible parts of reinforced insulation consisting of a single layer, by measurement in accordance with 29.3.4, or		N/A

IEC 60335-2-7			
Clause	Requirement + Test	Result - Remark	Verdict
	- by an assessment of the thermal quality of the material according to 29.3.3 combined with an electric strength test in accordance with 23.5, for each single layer internal wiring insulation touching each other, or		N/A
	- as specified in subclause 6.3 of IEC 60664-4 for insulation that is subjected to any periodic voltage having a frequency exceeding 30 kHz		N/A
29.3.1	Supplementary insulation have a thickness of at least 1 mm	Sleeving for supplementary insulation: 1,1 mm	P
	Reinforced insulation have a thickness of at least 2 mm	Control panel for reinforced insulation: 2,2 mm	P
29.3.2	Each layer of material withstand the electric strength test of 16.3 for supplementary insulation		N/A
	Supplementary insulation consist of at least 2 layers		N/A
	Reinforced insulation consist of at least 3 layers		N/A
29.3.3	The insulation is subjected to the dry heat test Bb of IEC 60068-2-2, followed by		N/A
	the electric strength test of 16.3		N/A
	If the temperature rise during the tests of clause 19 does not exceed the value specified in table 3, the test of IEC 60068-2-2 is not carried out		N/A
29.3.4	Thickness of accessible parts of reinforced insulation consisting of a single layer not less than specified in table 19 :		N/A
30	RESISTANCE TO HEAT AND FIRE		—
30.1	External parts of non-metallic material,		P
	parts supporting live parts, and		P
	parts of thermoplastic material providing supplementary or reinforced insulation		P
	sufficiently resistant to heat		P
	Ball-pressure test according to IEC 60695-10-2		P
	External parts tested at 40 °C plus the maximum temperature rise determined during the test of clause 11, or at 75 °C, whichever is the higher; temperature (°C) :	(see appended table)	P
	Parts supporting live parts tested at 40°C plus the maximum temperature rise determined during the test of clause 11, or at 125 °C, whichever is the higher; temperature (°C) :	(see appended table)	P

IEC 60335-2-7			
Clause	Requirement + Test	Result - Remark	Verdict
	Parts of thermoplastic material providing supplementary or reinforced insulation tested at 25 °C plus the maximum temperature rise determined during clause 19, if higher; temperature (°C) :		N/A
30.2	Parts of non-metallic material resistant to ignition and spread of fire		P
	This requirement does not apply to:		—
	parts having a mass not exceeding 0,5 g, provided the cumulative effect is unlikely to propagate flames that originate inside the appliance by propagating flames from one part to another, or		N/A
	decorative trims, knobs and other parts unlikely to be ignited or to propagate flames that originate inside the appliance		N/A
	Compliance checked by the test of 30.2.1, and in addition:		P
	- for attended appliances, 30.2.2 applies		N/A
	- for unattended appliances, 30.2.3 applies		P
	For appliances for remote operation, 30.2.3 applies		N/A
	For base material of printed circuit boards, 30.2.4 applies		N/A
	For appliances incorporating a programmer or a timer, 30.2.3 is applicable. (IEC 60335-2-7)		P
	For other appliances, 30.2.2 is applicable (IEC 60335-2-7)		N/A
30.2.1	Parts of non-metallic material subjected to the glow-wire test of IEC 60695-2-11 at 550 °C	(see appended table)	P
	However, test not carried out if the material is classified as having a glow-wire flammability index according to IEC 60695-2-12 of at least 550 °C, or		N/A
	the material is classified at least HB40 according to IEC 60695-11-10		N/A
	Parts for which the glow-wire test cannot be carried out need to meet the requirements in ISO 9772 for material classified HBF		N/A
30.2.2	Appliances operated while attended, parts of non-metallic material supporting current-carrying connections, and		N/A
	parts of non-metallic material within a distance of 3mm of such connections,		N/A
	subjected to the glow-wire test of IEC 60695-2-11		N/A

IEC 60335-2-7			
Clause	Requirement + Test	Result - Remark	Verdict
	The test severity is:		—
	- 750 °C, for connections carrying a current exceeding 0,5 A during normal operation		N/A
	- 650 °C, for other connections		N/A
	Glow-wire applied to an interposed shielding material, if relevant		N/A
	The glow-wire test is not carried out on parts of material classified as having a glow-wire flammability index according to IEC 60695-2-12 of at least:		—
	- 750 °C, for connections carrying a current exceeding 0,5 A during normal operation		N/A
	- 650 °C, for other connections		N/A
	The glow-wire test is also not carried out on small parts. These parts are to:		—
	- comprise material having a glow-wire flammability index of at least 750 °C, or 650 °C as appropriate, or		N/A
	- comply with the needle-flame test of Annex E, or		N/A
	- comprise material classified as V-0 or V-1 according to IEC 60695-11-10		N/A
	Glow-wire test not applicable to conditions as specified		N/A
30.2.3	Appliances operated while unattended, tested as specified in 30.2.3.1 and 30.2.3.2		P
	The tests are not applicable to conditions as specified		N/A
30.2.3.1	Parts of non-metallic material supporting connections carrying a current exceeding 0,2 A during normal operation, and	(see appended table)	P
	parts of non-metallic material, other than small parts, within a distance of 3 mm,		N/A
	subjected to the glow-wire test of IEC 60695-2-11 with a test severity of 850 °C		P
	Glow-wire applied to an interposed shielding material, if relevant		N/A
	The glow-wire test is not carried out on parts of material classified as having a glow-wire flammability index according to IEC 60695-2-12 of at least 850 °C		N/A
30.2.3.2	Parts of non-metallic material supporting connections, and		P

IEC 60335-2-7			
Clause	Requirement + Test	Result - Remark	Verdict
	parts of non-metallic material within a distance of 3mm,		N/A
	subjected to glow-wire test of IEC 60695-2-11		P
	The test severity is:		—
	- 750 °C, for connections carrying a current exceeding 0,2 A during normal operation	(see appended table)	P
	- 650 °C, for other connections		N/A
	Glow-wire applied to an interposed shielding material, if relevant		N/A
	However, the glow-wire test of 750 °C or 650 °C as appropriate, is not carried out on parts of material fulfilling both or either of the following classifications:		—
	- a glow-wire ignition temperature according to IEC 60695-2-13 of at least:		N/A
	775 °C, for connections carrying a current exceeding 0,2 A during normal operation		N/A
	675 °C, for other connections		N/A
	- a glow-wire flammability index according to IEC 60695-2-12 of at least:		N/A
	- 750 °C, for connections carrying a current exceeding 0,2 A during normal operation		N/A
	- 650 °C, for other connections		N/A
	The glow-wire test is also not carried out on small parts. These parts are to:		—
	- comprise material having a glow-wire ignition temperature of at least 775 °C or 675 °C as appropriate, or		N/A
	- comprise material having a glow-wire flammability index of at least 750 °C or 650 °C as appropriate, or		N/A
	- comply with the needle-flame test of Annex E, or		N/A
	- comprise material classified as V-0 or V-1 according to IEC 60695-11-10		N/A
	The consequential needle-flame test of Annex E applied to non-metallic parts that encroach within the vertical cylinder placed above the centre of the connection zone and on top of the non-metallic parts supporting current-carrying connections, and parts of non-metallic material within a distance of 3 mm of such connections if these parts are those:		—
	- parts that withstood the glow-wire test of IEC 60695-2-11 of 750 °C or 650 °C as appropriate, but produce a flame that persist longer than 2 s, or		N/A

IEC 60335-2-7			
Clause	Requirement + Test	Result - Remark	Verdict
	- parts that comprised material having a glow-wire flammability index of at least 750 °C or 650 °C as appropriate, or		N/A
	- small parts, that comprised material having a glow-wire flammability index of at least 750 °C or 650 °C as appropriate, or		N/A
	- small parts for which the needle-flame test of Annex E was applied, or		N/A
	- small parts for which a material classification of V-0 or V-1 was applied		N/A
	However, the consequential needle-flame test is not carried out on non-metallic parts, including small parts, within the cylinder that are:		—
	- parts having a glow-wire ignition temperature of at least 775 °C or 675 °C as appropriate, or		N/A
	- parts comprising material classified as V-0 or V-1 according to IEC 60695-11-10, or		N/A
	- parts shielded by a flame barrier that meets the needle-flame test of Annex E or that comprises material classified as V-0 or V-1 according to IEC 60695-11-10		N/A
30.2.4	Base material of printed circuit boards subjected to the needle-flame test of Annex E		N/A
	Test not applicable to conditions as specified :		N/A
31	RESISTANCE TO RUSTING		—
	Relevant ferrous parts adequately protected against rusting		P
	Tests specified in part 2 when necessary		P
32	RADIATION, TOXICITY AND SIMILAR HAZARDS		—
	Appliance does not emit harmful radiation or present a toxic or similar hazard due to their operation in normal use		P
	Compliance is checked by the limits or tests specified in part 2, if relevant		P
A	ANNEX A (INFORMATIVE) ROUTINE TESTS		—
	Description of routine tests to be carried out by the manufacturer		N/A
B	ANNEX B (NORMATIVE) APPLIANCES POWERED BY RECHARGEABLE BATTERIES THAT ARE RECHARGED IN THE APPLIANCE		—

IEC 60335-2-7			
Clause	Requirement + Test	Result - Remark	Verdict
	The following modifications to this standard are applicable for appliances powered by batteries that are recharged in the appliance		N/A
	Three forms of construction covered:		—
	a) Appliance supplied directly from the supply mains or a renewable energy source, the battery charging circuitry and other supply unit circuitry incorporated within the appliance		N/A
	b) The part of the appliance incorporating the battery is supplied from the supply mains or a renewable energy source, via a detachable supply unit. The battery charging circuitry is incorporated within the part of the appliance containing the battery		N/A
	c) The part of the appliance incorporating the battery is supplied from the supply mains or a renewable energy source, via a detachable supply unit. The battery charging circuitry is incorporated within the detachable supply unit		N/A
	This annex does not apply to battery chargers		N/A
3.1.9	Appliance operated under the following conditions:		—
	- the appliance, supplied by its fully charged battery, operated as specified in relevant part 2		N/A
	- the battery is charged, the battery being initially discharged to such an extent that the appliance cannot operate		N/A
	-if possible, the appliance is supplied from the supply mains through its battery charger, the battery being initially discharged to such an extent that the appliance cannot operate. The appliance is operated as specified in relevant part 2		N/A
	- if the appliance incorporates inductive coupling between two parts that are detachable from each other, the appliance is supplied from the supply mains with the detachable part removed		N/A
3.6.2	Part to be removed in order to discard the battery is not considered to be detachable		N/A
5.B.101	Appliances supplied from the supply mains tested as specified for motor-operated appliances		N/A
7.1	Battery compartment for batteries intended to be replaced by the user, marked with battery voltage and polarity of the terminals		N/A

IEC 60335-2-7			
Clause	Requirement + Test	Result - Remark	Verdict
	The positive terminal indicated by symbol IEC 60417-5005 and the negative terminal by symbol IEC 60417-5006		N/A
	Appliances intending to be supplied from a detachable supply unit marked with symbol IEC 60417-6181 and its type reference along with symbol ISO 7000-0790 (2004-01), or		N/A
	use only with <model designation> supply unit :		N/A
7.6	Symbols 60417-5005 and IEC 60417-5006		N/A
7.12	The instructions give information regarding charging		N/A
	The instructions for appliances incorporating batteries intended to be replaced by the user includes required information		N/A
	Details about how to remove batteries containing materials hazardous to the environment given		N/A
	Instructions for appliances containing non-user-replaceable batteries state the substance of the following:		—
	This appliance contains batteries that are only replaceable by skilled persons		N/A
	Instructions for appliances containing non-replaceable batteries shall state the substance of the following:		—
	This appliance contains batteries that are non-replaceable		N/A
	For appliances intending to be supplied from a detachable supply unit for the purposes of recharging the battery, the type reference of the detachable supply unit is stated along with the following:		—
	WARNING: For the purposes of recharging the battery, only use the detachable supply unit provided with this appliance		N/A
	If the symbol for detachable supply unit is used, its meaning is explained		N/A
7.15	Markings placed on the part of the appliance connected to the supply mains		N/A
	The type reference of the detachable supply unit is placed in close proximity to the symbol		N/A
8.2	Appliances having batteries that according to the instruction may be replaced by the user need only have basic insulation between live parts and the inner surface of the battery compartment		N/A
	If the appliance can be operated without batteries, double or reinforced insulation required		N/A

IEC 60335-2-7			
Clause	Requirement + Test	Result - Remark	Verdict
11.7	The battery is charged for the period stated in the instructions or 24 h		N/A
11.8	Temperature rise of the battery surface does not exceed the limit in the battery manufacturer's specification; measured (K); limit (K)		N/A
	If no limit specified, the temperature rise does not exceed 20 K; measured (K)		N/A
19.1	Appliances subjected to tests of 19.B.101, 19.B.102 and 19.B.103		N/A
19.10	Not applicable		N/A
19.B.101	Appliances supplied at rated voltage for 168 h, the battery being continually charged		N/A
19.B.102	For appliances having batteries that can be removed without the aid of a tool, short-circuit of the terminals of the battery, the battery being fully charged,		N/A
19.B.103	Appliances having batteries replaceable by the user supplied at rated voltage under normal operation with the battery removed or in any position allowed by the construction		N/A
19.13	The battery does not rupture or ignite		N/A
21.B.101	Appliances having pins for insertion into socket-outlets have adequate mechanical strength		N/A
	Part of the appliance incorporating the pins subjected to the free fall test, procedure 2, of IEC 60068-2-31, the number of falls being:		—
	- 100, if the mass of the part does not exceed 250 g (g).....		N/A
	- 50, if the mass of the part exceeds 250 g		N/A
	After the test, the requirements of 8.1, 15.1.1, 16.3 and clause 29 are met		N/A
22.3	Appliances having pins for insertion into socket-outlets tested as fully assembled as possible		N/A
25.13	An additional lining or bushing not required for interconnection cords in class III appliances or class III constructions operating at safety extra-low voltage not containing live parts		N/A
30.2	For parts of the appliance connected to the supply mains during the charging period, 30.2.3 applies		N/A
	For other parts, 30.2.2 applies		N/A
C	ANNEX C (NORMATIVE) AGEING TEST ON MOTORS		—

IEC 60335-2-7			
Clause	Requirement + Test	Result - Remark	Verdict
	Tests, as described, carried out when doubt with regard to the temperature classification of the insulation of a motor winding		N/A
	Test conditions as specified		N/A
D	ANNEX D (NORMATIVE) THERMAL MOTOR PROTECTORS		—
	Applicable to appliances having motors that incorporate thermal motor protectors necessary for compliance with the standard		P
	Test conditions as specified	(see appended table)	P
E	ANNEX E (NORMATIVE) NEEDLE-FLAME TEST		—
	Needle-flame test carried out in accordance with IEC 60695-11-5, with the following modifications:		—
7	Severities		—
	The duration of application of the test flame is 30 s ± 1 s		N/A
9	Test procedure		—
9.1	The specimen so arranged that the flame can be applied to a vertical or horizontal edge as shown in the examples of Figure 1		N/A
9.2	The first paragraph does not apply		N/A
	If possible, the flame is applied at least 10 mm from a corner		N/A
9.3	The test is carried out on one specimen		N/A
	If the specimen does not withstand the test, the test may be repeated on two additional specimens, both withstanding the test		N/A
11	Evaluation of test results		—
	The duration of burning not exceeding 30 s		N/A
	However, for printed circuit boards, the duration of burning not exceeding 15 s		N/A
F	ANNEX F (NORMATIVE) CAPACITORS		—
	Capacitors likely to be permanently subjected to the supply voltage, and used for radio interference suppression or voltage dividing, comply with the following clauses of IEC 60384-14, with the following modifications:		—
1.5	Terms and definitions		—
1.5.3	Class X capacitors tested according to subclass X2		N/A

IEC 60335-2-7			
Clause	Requirement + Test	Result - Remark	Verdict
1.5.4	This subclause is applicable		N/A
1.6	Marking		—
	Items a) and b) are applicable		N/A
3.4	Approval testing		—
3.4.3.2	Table 3 is applicable as described		N/A
4.1	Visual examination and check of dimensions		—
	This subclause is applicable		N/A
4.2	Electrical tests		—
4.2.1	This subclause is applicable		N/A
4.2.5	This subclause is applicable		N/A
4.2.5.2	Only table 11 is applicable		N/A
	Values for test A apply		N/A
	However, for capacitors in heating appliances the values for test B or C apply		N/A
4.12	Damp heat, steady state		—
	This subclause is applicable		N/A
	Only insulation resistance and voltage proof are checked		N/A
4.13	Impulse voltage		—
	This subclause is applicable		N/A
4.14	Endurance		—
	Subclauses 4.14.1, 4.14.3, 4.14.4 and 4.14.7 are applicable		N/A
4.14.7	Only insulation resistance and voltage proof are checked		N/A
	No visible damage		N/A
4.17	Passive flammability test		—
	This subclause is applicable		N/A
4.18	Active flammability test		—
	This subclause is applicable		N/A
G	ANNEX G (NORMATIVE) SAFETY ISOLATING TRANSFORMERS		—
	The following modifications to this standard are applicable for safety isolating transformers:		—
7	Marking and instructions		—

IEC 60335-2-7			
Clause	Requirement + Test	Result - Remark	Verdict
7.1	Transformers for specific use marked with:		—
	-name, trademark or identification mark of the manufacturer or responsible vendor		N/A
	-model or type reference		N/A
17	Overload protection of transformers and associated circuits		—
	Fail-safe transformers comply with subclause 15.5 of IEC 61558-1		N/A
22	Construction		—
	Subclauses 19.1 and 19.1.2 of IEC 61558-2-6 are applicable		N/A
29	Clearances, creepage distances and solid insulation		—
29.1, 29.2, 29.3	The distances specified in items 2a, 2c and 3 in table 13 of IEC 61558-1 apply		N/A
	For insulated winding wires complying with subclause 19.12.3 of IEC 61558-1 there are no requirements for clearances or creepage distances		N/A
	For windings providing reinforced insulation, the distance specified in item 2c of table 13 of IEC 61558-1 is not assessed		N/A
	For safety isolating transformers subjected to periodic voltages with a frequency exceeding 30 kHz, the clearances, creepage distances and solid insulation values specified in IEC 60664-4 are applicable, if greater than the values specified in items 2a, 2c and 3 in table 13 of IEC 61558-1		N/A
H	ANNEX H (NORMATIVE) SWITCHES		—
	Switches comply with the following clauses of IEC 61058-1, as modified below:		—
	The tests of IEC 61058-1 carried out under the conditions occurring in the appliance		P
	Before being tested, switches are operated 20 times without load		P
8	Marking and documentation		—
	Switches are not required to be marked		N/A
	However, a switch that can be tested separately from the appliance marked with the manufacturer's name or trade mark and the type reference		P
13	Mechanism		—
	The tests may be carried out on a separate sample		P
15	Insulation resistance and dielectric strength		—

IEC 60335-2-7			
Clause	Requirement + Test	Result - Remark	Verdict
15.1	Not applicable		P
15.2	Not applicable		P
15.3	Applicable for full disconnection and micro-disconnection		P
17	Endurance		—
	Compliance is checked on three separate appliances or switches		N/A
	For 17.2.4.4, the number of cycles declared according to 7.1.4 is 10 000, unless	The maximum current < 20 mA	N/A
	otherwise specified in 24.1.3 of the relevant part 2 of IEC 60335..... :		N/A
	Switches for operation under no load and which can be operated only by a tool, and		N/A
	switches operated by hand that are interlocked so that they cannot be operated under load,		N/A
	are not subjected to the tests		N/A
	However, switches without this interlock are subjected to the test of 17.2.4.4 for 100 cycles of operation		N/A
	Subclauses 17.2.2 and 17.2.5.2 not applicable		N/A
	The ambient temperature during the test is that occurring in the appliance during the test of Clause 11 in IEC 60335-1		N/A
	The temperature rise of the terminals not more than 30 K above the temperature rise measured in clause 11 of IEC 60335-1 (K) :		N/A
20	Clearances, creepage distances, solid insulation and coatings of rigid printed board assemblies		—
	Clause 20 is applicable to clearances across full disconnection and micro-disconnection		N/A
	It is also applicable to creepage distances for functional insulation, across full disconnection and micro-disconnection, as stated in table 24		N/A
I	ANNEX I (NORMATIVE) MOTORS HAVING BASIC INSULATION THAT IS INADEQUATE FOR THE RATED VOLTAGE OF THE APPLIANCE		—
	The following modifications to this standard are applicable for motors having basic insulation that is inadequate for the rated voltage of the appliance:		—
8	Protection against access to live parts		—

IEC 60335-2-7			
Clause	Requirement + Test	Result - Remark	Verdict
8.1	Metal parts of the motor are considered to be bare live parts		N/A
11	Heating		—
11.3	The temperature rise of the body of the motor is determined instead of the temperature rise of the windings		N/A
11.8	The temperature rise of the body of the motor, where in contact with insulating material, not exceeding values in table 3 for the relevant insulating material		N/A
16	Leakage current and electric strength		—
16.3	Insulation between live parts of the motor and its other metal parts is not subjected to the test		N/A
19	Abnormal operation		—
19.1	The tests of 19.7 to 19.9 are not carried out		N/A
19.1.101	Appliance operated at rated voltage with each of the following fault conditions:		—
	- short circuit of the terminals of the motor, including any capacitor incorporated in the motor circuit		N/A
	- short circuit of each diode of the rectifier		N/A
	- open circuit of the supply to the motor		N/A
	- open circuit of any parallel resistor, the motor being in operation		N/A
	Only one fault simulated at a time, the tests carried out consecutively		N/A
22	Construction		—
22.1.101	For class I appliances incorporating a motor supplied by a rectifier circuit, the d.c. circuit being insulated from accessible parts of the appliance by double or reinforced insulation		N/A
	Compliance checked by the tests specified for double and reinforced insulation		N/A
J	ANNEX J (NORMATIVE) COATED PRINTED CIRCUIT BOARDS		—
	Testing of protective coatings of printed circuit boards carried out in accordance with IEC 60664-3 with the following modifications:		—
5.7	Conditioning of the test specimens		—
	When production samples are used, three samples of the printed circuit board are tested		N/A
5.7.1	Cold		—

IEC 60335-2-7			
Clause	Requirement + Test	Result - Remark	Verdict
	The test is carried out at -25 °C		N/A
5.7.3	Rapid change of temperature		—
	Severity 1 is specified		N/A
5.9	Additional tests		—
	This subclause is not applicable		N/A
K	ANNEX K (NORMATIVE) OVERVOLTAGE CATEGORIES		—
	The information on overvoltage categories is extracted from IEC 60664-1		P
	Overvoltage category is a numeral defining a transient overvoltage condition		P
	Equipment of overvoltage category IV is for use at the origin of the installation		N/A
	Equipment of overvoltage category III is equipment in fixed installations and for cases where the reliability and the availability of the equipment is subject to special requirements		N/A
	Equipment of overvoltage category II is energy consuming equipment to be supplied from the fixed installation		P
	If such equipment is subjected to special requirements with regard to reliability and availability, overvoltage category III applies		N/A
	Equipment of overvoltage category I is equipment for connection to circuits in which measures are taken to limit transient overvoltages to an appropriate low level		N/A
L	ANNEX L (INFORMATIVE) GUIDANCE FOR THE MEASUREMENT OF CLEARANCES AND CREEPAGE DISTANCES		—
	Information for the determination of clearances and creepage distances		P
M	ANNEX M (NORMATIVE) POLLUTION DEGREE		—
	The information on pollution degrees is extracted from IEC 60664-1		P
	Pollution		—
	The microenvironment determines the effect of pollution on the insulation, taking into account the macroenvironment		P

IEC 60335-2-7			
Clause	Requirement + Test	Result - Remark	Verdict
	Means may be provided to reduce pollution at the insulation by effective enclosures or similar		P
	Minimum clearances specified where pollution may be present in the microenvironment		N/A
	Degrees of pollution in the microenvironment		—
	For evaluating creepage distances, the following degrees of pollution in the microenvironment are established:		—
	- pollution degree 1: no pollution or only dry, non-conductive pollution occurs. The pollution has no influence		N/A
	- pollution degree 2: only non-conductive pollution occurs, except that occasionally a temporary conductivity caused by condensation is to be expected		N/A
	- pollution degree 3: conductive pollution occurs or dry non-conductive pollution occurs that becomes conductive due to condensation that is to be expected		P
	- pollution degree 4: the pollution generates persistent conductivity caused by conductive dust or by rain or snow		N/A
N	ANNEX N (NORMATIVE) PROOF TRACKING TEST		—
	The proof tracking test is carried out in accordance with IEC 60112 with the following modifications:		—
7	Test apparatus		—
7.3	Test solutions		—
	Test solution A is used		P
10	Determination of proof tracking index (PTI)		—
10.1	Procedure		—
	The proof voltage is 100V, 175V, 400V or 600V .. :	250 V	P
	The test is carried out on five specimens		P
	In case of doubt, additional test with proof voltage reduced by 25V, the number of drops increased to 100		P
10.2	Report		—
	The report states if the PTI value was based on a test using 100 drops with a test voltage of (PTI-25) V		N/A

IEC 60335-2-7			
Clause	Requirement + Test	Result - Remark	Verdict
O	ANNEX O (INFORMATIVE) SELECTION AND SEQUENCE OF THE TESTS OF CLAUSE 30		—
	Description of tests for determination of resistance to heat and fire		P
P	ANNEX P (INFORMATIVE) GUIDANCE FOR THE APPLICATION OF THIS STANDARD TO APPLIANCES USED IN WARM DAMP EQUABLE CLIMATES		—
	Modifications applicable for class 0 and 01 appliances having a rated voltage exceeding 150V, intended to be used in countries having a warm damp equable climate and that are marked WDaE		—
	Modifications may also be applied to class 1 appliances having a rated voltage exceeding 150V, intended to be used in countries having a warm damp equable climate and that are marked WDaE, if liable to be connected to a supply mains that excludes the protective earthing conductor		—
5.7	The ambient temperature for the tests of clauses 11 and 13 is 40 +3/0 °C		N/A
7.1	The appliance marked with symbol IEC 60417-6332		N/A
7.12	The instructions state that the appliance is to be supplied through a residual current device (RCD) having a rated residual operating current not exceeding 30 mA		N/A
	The instructions state that the appliance is considered to be suitable for use in countries having a warm damp equable climate, but may also be used in other countries		N/A
	If symbol IEC 60417-6332 is used, its meaning is explained		N/A
11.8	The values of Table 3 are reduced by 15 K		N/A
13.2	The leakage current for class I appliances not exceeding 0,5 mA		N/A
15.3	The value of t is 37 °C		N/A
16.2	The leakage current for class I appliances not exceeding 0,5 mA (mA):		N/A
19.13	The leakage current test of 16.2 is applied in addition to the electric strength test of 16.3		N/A
Q	ANNEX Q (INFORMATIVE) SEQUENCE OF TESTS FOR THE EVALUATION OF ELECTRONIC CIRCUITS		—
	Description of tests for appliances incorporating electronic circuits		P
R	ANNEX R (NORMATIVE) SOFTWARE EVALUATION		—

IEC 60335-2-7			
Clause	Requirement + Test	Result - Remark	Verdict
	Programmable electronic circuits requiring software incorporating measures to control the fault/error conditions specified in table R.1 or R.2 validated in accordance with the requirements of this annex		N/A
R.1	Programmable electronic circuits using software		—
	Programmable electronic circuits requiring software incorporating measures to control the fault/error conditions specified in table R.1 or R.2 constructed so that the software does not impair compliance with the requirements of this standard		N/A
R.2	Requirements for the architecture		—
	Programmable electronic circuits requiring software incorporating measures to control the fault/error conditions specified in table R.1 or R.2 use measures to control and avoid software-related faults/errors in safety-related data and safety-related segments of the software		N/A
R.2.1.1	Programmable electronic circuits requiring software incorporating measures to control the fault/error conditions specified in table R.2 have one of the following structures:		—
	- single channel with periodic self-test and monitoring		N/A
	- dual channel (homogenous) with comparison		N/A
	- dual channel (diverse) with comparison		N/A
	Programmable electronic circuits requiring software incorporating measures to control the fault/error conditions specified in table R.1 have one of the following structures:		—
	- single channel with functional test		N/A
	- single channel with periodic self-test		N/A
	- dual channel without comparison		N/A
R.2.2	Measures to control faults/errors		—
R.2.2.1	When redundant memory with comparison is provided on two areas of the same component, the data in one area is stored in a different format from that in the other area		N/A
R.2.2.2	Programmable electronic circuits with functions requiring software incorporating measures to control the fault/error conditions specified in table R.2 and that use dual channel structures with comparison, have additional fault/error detection means for any fault/errors not detected by the comparison		N/A

IEC 60335-2-7			
Clause	Requirement + Test	Result - Remark	Verdict
R.2.2.3	For programmable electronic circuits with functions requiring software incorporating measures to control the fault/error conditions specified in table R.1 or R.2, means are provided for the recognition and control of errors in transmissions to external safety-related data paths		N/A
R.2.2.4	For programmable electronic circuits with functions requiring software incorporating measures to control the fault/error conditions specified in table R.1 or R.2, the programmable electronic circuits incorporate measures to address the fault/errors in safety-related segments and data indicated in table R.1 and R.2 as appropriate		N/A
R.2.2.5	For programmable electronic circuits with functions requiring software incorporating measures to control the fault/error conditions specified in Table R.1 or Table R.2, detection of a fault/error shall occur before compliance with Clauses 19, 20.104, 20.105 , 22.101 and 22.108 is impaired (IEC 60335-2-7)		N/A
R.2.2.6	The software is referenced to relevant parts of the operating sequence and the associated hardware functions		N/A
R.2.2.7	Labels used for memory locations are unique		N/A
R.2.2.8	The software is protected from user alteration of safety-related segments and data		N/A
R.2.2.9	The software and safety-related hardware under its control shall be initialized and shall terminate before compliance with Clauses 19, 20.104, 20.105 ,22.101 and 22.108 is impaired. (IEC 60335-2-7)		N/A
R.3	Measures to avoid errors		—
R.3.1	General		—
	For programmable electronic circuits with functions requiring software incorporating measures to control the fault/error conditions specified in table R.1 or R.2, the following measures to avoid systematic fault in the software are applied		—
	Software that incorporates measures used to control the fault/error conditions specified in table R.2 is inherently acceptable for software required to control the fault/error conditions specified in table R.1		N/A
R.3.2	Specification		—
R.3.2.1	Software safety requirements:		N/A
	The specification of the software safety requirements includes the descriptions listed		N/A

IEC 60335-2-7			
Clause	Requirement + Test	Result - Remark	Verdict
R.3.2.2	Software architecture		—
R.3.2.2.1	The specification of the software architecture includes the aspects listed - techniques and measures to control software faults/errors (refer to R.2.2); - interactions between hardware and software; - partitioning into modules and their allocation to the specified safety functions; - hierarchy and call structure of the modules (control flow); - interrupt handling; - data flow and restrictions on data access; - architecture and storage of data; - time-based dependencies of sequences and data		N/A
R.3.2.2.2	The architecture specification is validated against the specification of the software safety requirements by static analysis		N/A
R.3.2.3	Module design and coding		—
R.3.2.3.1	Based on the architecture design, software is suitably refined into modules		N/A
	Software module design and coding is implemented in a way that is traceable to the software architecture and requirements		N/A
R.3.2.3.2	Software code is structured		N/A
R.3.2.3.3	Coded software is validated against the module specification by static analysis		N/A
	The module specification is validated against the architecture specification by static analysis		N/A
R.3.3.3	Software validation		—
	The software is validated with reference to the requirements of the software safety requirements specification		N/A
	Compliance is checked by simulation of:		—
	- input signals present during normal operation		N/A
	- anticipated occurrences		N/A
	- undesired conditions requiring system action		N/A

TABLE R.1 – GENERAL FAULT/ERROR CONDITIONS						
Component ₁₎	Fault/error	Acceptable measures _{2) 3)}	Definitions	Document reference	Document reference	Verdict

IEC 60335-2-7						
Clause	Requirement + Test		Result - Remark		Verdict	
				for applied measure	for applied test	
1 CPU						
1.1 Registers	Stuck at	Functional test, or periodic self-test using either: - static memory test, or - word protection with single bit redundancy	H.2.16.5 H.2.16.6 H.2.19.6 H.2.19.8.2	—	—	NA
1.2 VOID						—
1.3 Programme counter	Stuck at	Functional test, or Periodic self-test, or Independent time-slot monitoring, or Logical monitoring of the programme sequence	H.2.16.5 H.2.16.6 H.2.18.10.4 H.2.18.10.2	—	—	N/A
2 Interrupt handling and execution	No interrupt or too frequent interrupt	Functional test, or time-slot monitoring	H.2.16.5 H.2.18.10.4	—	—	N/A
3 Clock	Wrong frequency (for quartz synchronized clock: harmonics/sub-harmonics only)	Frequency monitoring, or time slot monitoring	H.2.18.10.1 H.2.18.10.4	—	—	N/A
4. Memory						
4.1 Invariable memory	All single bit faults	Periodic modified checksum, or multiple checksum, or word protection with single bit redundancy	H.2.19.3.1 H.2.19.3.2 H.2.19.8.2	—	—	N/A
4.2 Variable memory	DC fault	Periodic static memory test, or word protection with single bit redundancy	H.2.19.6 H.2.19.8.2	—	—	N/A
4.3 Addressing (relevant to	Stuck at	Word protection with single bit redundancy including the address	H.2.19.8.2	—	—	N/A

IEC 60335-2-7						
Clause	Requirement + Test		Result - Remark		Verdict	
variable and invariable memory)						
5 Internal data path	Stuck at DC fault	Word protection with single bit redundancy Comparison of redundant CPUs by either: - reciprocal comparison - independent hardware comparator	H.2.19.8.2 H.2.18.15 H.2.18.3	—	—	N/A
5.1 VOID						—
5.2 Addressing	Wrong address	Word protection with single bit redundancy including the address	H.2.19.8.2	—	—	N/A
6 External communication	Hamming distance 3	Word protection with multi-bit redundancy, or CRC – single work, or Transfer redundancy, or Protocol test	H.2.19.8.1 H.2.19.4.1 H.2.18.2.2 H.2.18.14	—	—	N/A
6.1 VOID						—
6.2 VOID						—
6.3 Timing	Wrong point in time Wrong sequence	Time-slot monitoring, or scheduled transmission Time-slot and logical monitoring, or Comparison of redundant communication channels by either: - reciprocal comparison - independent hardware comparator Logical monitoring, or time-slot monitoring, or Scheduled transmission (same options as for wrong point in time)	H.2.18.10.4 H.2.18.18 H.2.18.10.3 H.2.18.15 H.2.18.3 H.2.18.10.2 H.2.18.10.4 H.2.18.18	—	—	N/A
7 Input/output periphery	Fault conditions specified in 19.11.2	Plausibility check Comparison of redundant communication channels by either:	H.2.18.13	—	—	N/A

IEC 60335-2-7						
Clause	Requirement + Test		Result - Remark		Verdict	
		- reciprocal comparison - independent hardware comparator	H.2.18.15 H.2.18.3			
7.1 VOID						—
7.2 Analog I/O 7.2.1 A/D and D/A-converter	Fault conditions specified in 19.11.2	Plausibility check	H.2.18.13	—	—	N/A
7.2.2 Analog multiplexer	Wrong addressing	Plausibility check	H.2.18.13	—	—	N/A
8 VOID						—
9 Custom chips ⁴⁾ e.g. ASIC, GAL, Gate array	Any output outside the static and dynamic functional specification	Periodic self-test	H.2.16.6	—	—	N/A
NOTE A Stuck-at fault model denotes a fault model representing an open circuit or a non-varying signal level. A DC fault model denotes a stuck-at fault model incorporating short circuit between signal lines. ¹⁾ For fault/error assessment, some components are divided into their sub-functions. ²⁾ For each sub-function in the table, the Table R.2 measure will cover the software fault/error. ³⁾ Where more than one measure is given for a sub-function, these are alternatives. ⁴⁾ To be divided as necessary by the manufacturer into sub-functions.						

S	ANNEX S (NORMATIVE) BATTERY OPERATED APPLIANCES POWERED BY BATTERIES THAT ARE NON-RECHARGEABLE OR NOT RECHARGED IN THE APPLIANCE				—	
	The following modifications to this standard are applicable for battery-operated appliances where the batteries are either non-rechargeable (primary batteries), or				N/A	
	rechargeable batteries (secondary batteries) that are not recharged in the appliance				N/A	
5.8.1	If the supply terminals for the connection of the battery have no indication of polarity, the more unfavourable polarity is applied				N/A	

IEC 60335-2-7			
Clause	Requirement + Test	Result - Remark	Verdict
5.S.101	Appliances intended for use with a battery box are tested with the battery box supplied with the appliance or with the battery box recommended in the instructions		N/A
5.S.102	Appliances are tested as motor-operated appliances.		N/A
7.1	Appliances marked with the battery voltage (V) and the polarity of the terminals, unless :		N/A
	the polarity is irrelevant		N/A
	Appliances also marked with:		—
	– name, trade mark or identification mark of the manufacturer or responsible vendor :		N/A
	– model or type reference :		N/A
	– IP number according to degree of protection against ingress of water, other than IPX0 :		N/A
	– type reference of battery or batteries :		N/A
	If relevant, the positive terminal is indicated by the symbol IEC 60417-5005 and the negative terminal by the symbol IEC 60417-5006		N/A
	If appliances use more than one battery, they are marked to indicate correct polarity connection of the batteries		N/A
7.6	Additional symbols		N/A
7.12	The instructions contain the following, as applicable:		—
	– the types of batteries that may be used :		N/A
	– how to remove and insert the batteries		N/A
	– non-rechargeable batteries are not to be recharged		N/A
	– rechargeable batteries are to be removed from the appliance before being charged		N/A
	– different types of batteries or new and used batteries are not to be mixed		N/A
	– batteries are to be inserted with the correct polarity		N/A
	– exhausted batteries are to be removed from the appliance and safely disposed of		N/A
	– if the appliance is to be stored unused for a long period, the batteries are removed		N/A
	– the supply terminals are not to be short-circuited		N/A
11.5	Appliances are supplied with the most unfavourable supply voltage between		—
	– 0,55 and 1,0 times the battery voltage, if the appliance can be used with non-rechargeable batteries		N/A
	– 0,75 and 1,0 times battery voltage, if the appliance is designed for use with rechargeable batteries only		N/A

IEC 60335-2-7			
Clause	Requirement + Test	Result - Remark	Verdict
	The values specified in Table S.101 for the internal resistance per cell of the battery is taken into account		N/A
19.1	The tests are carried out with the battery fully charged unless otherwise specified		N/A
19.13	The battery does not rupture or ignite		N/A
19.S.101	Appliances are supplied with the voltage specified in 11.5. The supply terminals having an indication of polarity are connected to the opposite polarity, unless		N/A
	such a connection is unlikely to occur due to the construction of the appliance		N/A
19.S.102	For appliances with provision for multiple batteries, one or more of the batteries are reversed and the appliance is operated, if reversal of batteries is allowed by the construction		N/A
25.5	The flexible leads or flexible cord used to connect an external battery or battery box in is connected to the appliance by a type X attachment		N/A
25.13	This requirement is not applicable to the flexible leads or flexible cord connecting external batteries or a battery box with an appliance		N/A
25.S.101	Appliances have suitable means for connection of the battery. If the type of battery is marked on the appliance, the means of connection is suitable for this type of battery		N/A
26.5	Terminal devices in an appliance for the connection of the flexible leads or flexible cord connecting an external battery or battery box are so located or shielded that there is no risk of accidental connection between supply terminals		N/A
30.2.3.2	There is no battery in the area of the vertical cylinder used for the consequential needle flame test, unless		N/A
	the battery is shielded by a barrier that meets the needle flame test of Annex E, or		N/A
	that comprises material classified as V-0 or V-1 according to IEC 60695-11-10		N/A
T	ANNEX T (NORMATIVE) UV-C RADIATION EFFECT ON NON-METALLIC MATERIALS		—
	Requirements for non-metallic materials subject to direct or reflected UV-C radiation exposure and whose mechanical and electrical properties are relied upon for compliance with the		N/A
	Does not apply to glass, ceramic and similar materials		N/A
	Tested as specified in ISO 4892-1 and ISO 4892-2, with the following modifications:		—
	Modifications to ISO 4892-1:		N/A

IEC 60335-2-7			
Clause	Requirement + Test	Result - Remark	Verdict
5.1.6	The UV-C emitter is a low pressure mercury lamp with a quartz envelope having a continuous spectral irradiance of 10 W/m ² at 254 nm		N/A
	Subclause 5.1.6.1 and Table 1 are not applicable		N/A
5.2.4	The black-panel temperature shall be 63 °C +/- 3 °C		N/A
5.3.1	Humidification of the chamber air is specified in part 2 when necessary		N/A
9	This clause is not applicable		N/A
	Modifications to ISO 4892-2:		N/A
7.1	At least three test specimens are tested		N/A
	Ten samples of internal wiring is tested		N/A
7.2	The specimens are attached to the specimen holders such that they are not subject to any stress		N/A
7.3	Apparatus prepared as specified		N/A
	The test specimens and, if used, the irradiance-measuring instrument are exposed for 1 000 h		N/A
7.4	If used, a radiometer is mounted and calibrated such that it measures the irradiance at the exposed surface of the test specimen		N/A
7.5	Material properties and test methods for parts providing mechanical support or impact resistance as specified in Table T.1		N/A
	Material properties and test method for electrical insulation of internal wiring as specified in Table T.2		N/A
8	This clause is not applicable		N/A
AA	ANNEX AA (NORMATIVE) DETERGENT (IEC 60335-2-7)		—
	Detergent: composition, reference		P
BB	ANNEX BB (NORMATIVE) AGEING TEST FOR ELASTOMERIC PARTS (IEC 60335-2-7)		—
	Test carried out by measuring hardness and mass before and after immersion in a solutions of detergent and rinsing agent at elevated temperature		N/A
	Test is carried out on at least three samples of each part as specified in ISO 1817, with the following modifications :		N/A
5	Test liquids		N/A

IEC 60335-2-7			
Clause	Requirement + Test	Result - Remark	Verdict
	Two test liquids are used: – one liquid is obtained by dissolving 5 g of the detergent specified in Annex AA per litre of distilled water; – the other liquid is composed of 0,6 ml of rinsing agent as specified in Annex AA per litre of distilled water.		N/A
	Care is to be taken to ensure that the total mass of the test pieces immersed does not exceed 100 g for each litre of solution, that the test pieces are completely immersed and that their entire surface is freely exposed to the solution. During the tests, the test pieces are not to be exposed to direct light. Test pieces of different compounds are not to be immersed at the same time in the same solution		N/A
6	Test Pieces		N/A
6.4	Conditioning		N/A
	Temperature : $23^{\circ}\text{C} \pm 2^{\circ}\text{C}$		N/A
	Relative humidity : $(50 \pm 5)\%$		N/A
7	Immersion in the test liquid		N/A
7.1	Temperature		N/A
	Solution heated within 1h with test pieces immersed to $75 \pm 0.5^{\circ}\text{C}$ and maintained at this value		N/A
	Solution renewed every 24h		N/A
7.2	duration		N/A
	Immersion during periods as specified		N/A
8	Procedure		N/A
8.2	Change in mass		N/A
	Increase in mass of the test pieces, not exceeding 10 % of the value determined before immersion		N/A
8.6	Change in hardness		N/A
	Micro-test for hardness applies		N/A
	Hardness of the test pieces has not been changed by more than 8 IRHD		N/A
	Surface not sticky and no crack visible to the naked eye or any other deterioration		N/A
CC	ANNEX CC (NORMATIVE) DETERGENT FREE ELECTROLYSER WASHING MACHINES (IEC 60335-2-7)		—

IEC 60335-2-7			
Clause	Requirement + Test	Result - Remark	Verdict
	Washing machines for household and similar use that incorporate an electrolyte process employing an electrolyte instead of detergent		N/A
CC.3	Terms and definitions		N/A
3.1.9	Electrolyte specified in the instructions, amount, reference		N/A
CC.7	Marking and instructions		N/A
7.12	Instructions for appliances intended to be filled with electrolyte by the user shall contain details of the electrolyte,		N/A
	And the substance of the following: In order to avoid hazards, use only the electrolyte specified		N/A
7.12.1	Installation instructions shall state that the appliance shall be installed so that there is a distance of at least 200 mm between the appliance enclosure and external heat sources, such as appliances containing heating elements.		N/A
CC.15	Moisture resistance		N/A
15.2	Appliances are operated under the clause of cl. 11 but without clothes load.		N/A
	When the maximum water level is reached, the inlet valve is held open and the filling is continued for 15 min after first evidence of overflow or until the inflow is automatically stopped by other means.		N/A
CC.19	Abnormal operation		N/A
CC.19.201	Appliances shall be constructed so that foaming does not affect electrical insulation.		N/A
	Test carried out immediately after 15.2		N/A
	Test carried out immediately after 15.2		N/A
	After the test the appliance shall withstand the electric strength test of 16.3		N/A
CC.22	Construction		—
22.6	A solution composed of 5 g of the detergent specified in Annex AA per litre of distilled water is used. is used instead of coloured water		N/A
22.17	Spacers intended to prevent the electrolyser aperture being blocked by walls shall be fixed so that it is not possible to remove them from the outside of the appliance by hand or by means of screwdriver or a spanner.		N/A

IEC 60335-2-7			
Clause	Requirement + Test	Result - Remark	Verdict
CC.22.201	Appliances fitted with an electrolyser, consisting of cathodic and anodic chambers separated by an electrolytic separator, shall be constructed so that the electrolyser is always open to the atmosphere through an aperture of at least 5 mm in diameter, or 20 mm ² in area with a width of at least 3 mm.		N/A
	The aperture shall be located so that it is unlikely to be obstructed in normal use.		N/A
CC.22.202	During normal use of the appliance, the chemical reaction in the electrolyser shall not produce hydrogen gas that is released in hazardous amounts into areas		—
	-where electrical components that produce arcs and sparks during normal operation or abnormal operation are mounted, unless		N/A
	These components have been tested and found at least to comply with IEC 60079-15 for group IIC gases, or		N/A
	-that contain surfaces with a temperature exceeding 460°C during normal operation or abnormal operation and that may be exposed to the released hydrogen gas		N/A
	Compliance is checked by inspection, by measuring the temperature of the relevant surfaces during normal operation or abnormal operation, and by measuring the concentration of hydrogen gas (shall not exceed 50% of the LFL of hydrogen)		N/A
CC.22.203	During normal use of the appliance, the chemical reaction in the electrolyser shall not produce wash water that causes corrosion due to the PH value of the wash water.		N/A
	Compliance is checked by the salt mist test of IEC 60068-2-52, severity 2 being applicable.		N/A
	After the test, the appliance shall not have deteriorated to such an extent that compliance with this standard, in particular with cl. 8 and 27 is impaired. The coating shall not be broken and shall not have loosened the surface.		N/A
CC.29	Clearances, creepage distances and solid insulation		N/A
29.2	Pollution degree 3, and the insulation with a CTI not less than 250,		N/A
	Unless the insulation is enclosed or located so that it is unlikely to be exposed to pollution during normal use of the appliance due to :		N/A

IEC 60335-2-7			
Clause	Requirement + Test	Result - Remark	Verdict
	- condensation produced by the appliance		N/A
	- chemicals, such as electrolyte or fabric conditioner		N/A
CC.32	Radiation, toxicity and similar hazards		N/A
32	The ozone concentration produced by the chemical reactions in the electrolyser not be excessive.		N/A
	Compliance is checked by test as described		N/A
	The percentage of ozone shall not exceed 5×10^{-6}		N/A
Annex BB	Instead of the solution containing detergent, a solution of the electrolysed portion of the wash water obtained under the conditions of cl. 11 is used.		N/A
DD	WASHING MACHINES INCORPORATING A POWER DRIVEN WRINGER (IEC 60335-2-7)		—
DD.7	Radiation, toxicity and similar hazards		N/A
7.1	The safety release mechanism of power-driven wringers shall be marked to indicate its method of operation, unless		N/A
	Its operating means to be continuously actuated by the user.		N/A
7.12	The instructions shall draw attention to the potential hazards involved when operating the wringer,		N/A
	And shall state that : -the wringer must be disengaged or switched off when not in use; -the appliance must not be operated by children		N/A
DD.11	Heating		N/A
11.7	Appliance is operated for 3 cycles (washing following by wringing), with a rest period of 4 min between cycles. Duration of each wringing: 8 min. The wringer is loaded by passing a board through the rollers once a minute, the roller pressure being adjusted to the maximum value. The board is approximately 20 mm thick and 80 cm long, its width being at least equal to three-quarters of the effective length of the rollers. The board is uniformly tapered at each end down to a thickness of approximately 3 mm, over a distance of 20 cm.		N/A
DD.19	Abnormal operation		N/A
19.7	Moving parts of a wringer are locked even if a trip bar prevents rotation of the roller		N/A
DD.20	Stability and mechanical hazards		N/A

IEC 60335-2-7			
Clause	Requirement + Test	Result - Remark	Verdict
20.201	Power-driven wringers constructed so that the pressure between the rollers has to be maintained by the user, unless a readily accessible safety release or other means of protection is incorporated		N/A
	The release mechanism shall operate easily without violent ejection of any part and shall release pressure on the rollers immediately. The rollers shall separate either by at least 45 mm at both ends or by at least 25 mm at one end and 75 mm at the other		N/A
	The safety release shall be operable by a person standing in any normal working position relative to the wringer, even if the fingers of both hands are trapped between the rollers.		N/A
	Power-driven wringers shall be constructed to prevent fingers being squeezed between a roller and the frame		N/A
	Power-driven wringers shall be controlled by an easily accessible switch		N/A

10.1	TABLE: Power input deviation					P
Input deviation of/at:	P rated (W)	P measured (W)	dP (W, %)	Required dP (W, %)	Remark	
230 V, 50 Hz	170	156,2	-8,1%	+20%	Model XPB25-800D assembled with motor XPD-50	
230 V, 50 Hz	240	201,7	-16,0%	+20%	Model XPB48-800D assembled with motor XPD-90	
230 V, 50 Hz	320	270,0	-50 W	60 W	Model XPB62-800D assembled with motor XPD-120	
230 V, 50 Hz	400	360,0	-40 W	60 W	Model XPB78-800D assembled with motor XPD-150	
Supplementary information: N/A						

10.2	TABLE: Current deviation					N/A
Current deviation of/at:	I rated (A)	I measured (A)	dI (A, %)	Required dI (A, %)	Remark	
—	—	—	—	—	—	
Supplementary information: N/A						

11.8-1	TABLE: Heating test, thermocouple measurements			P
	Test voltage (V)	254,4 V; 50 Hz		—
	Ambient (°C)	T1=24,4 °C, T2=24,3 °C		—
Thermocouple locations		Max. temperature rise measured, dT (K)	Max. temperature rise limit, dT (K)	
Supply cord		29,8	50	
Cord sheath		28,2	35	
Internal wire		34,1	50	
Fuse holder		34,6	For cl.30.1	
Handle		18,9	60	
Drum		21,0	For cl.30.1	
Wash timer		8,6	60(T85)	
Knob		7,9	60	
Main motor winding		105,3	115(Class 155(F))	
X2 capacitor		16,4	60(T85)	
Motor running capacitor		16,0	45(T70)	
Wire connector		28,2	125(T150)	
Control panel		1,5	60	
Enclosure		9,6	60	

Test corner	8,2	65
Supplementary information: Model XPB25-800D assembled with motor XPD-50 and the most unfavorable results were record here.		

11.8-1	TABLE: Heating test, resistance method					P
	Test voltage (V)	254,4 V				—
	Ambient, t1 (°C).....	24,4 °C				—
	Ambient, t2 (°C).....	24,3 °C				—
Temperature rise of winding		R1 (Ω)	R2 (Ω)	dT (K)	Max. dT (K)	Insulation class
Primary winding of wash motor		61,4	87,5	110,2	115	Class 155 (F)
Secondary winding of wash motor		61,2	87,3	110,5	115	Class 155 (F)
Supplementary information: Model XPB25-800D assembled with motor XPD-50 and the most unfavorable results were record here.						

11.8-2	TABLE: Heating test, thermocouple measurements		P
	Test voltage (V) : :	254,4 V	—
	Ambient (°C)..... : :	T1=24,3 °C, T2=25,0 °C	—
Thermocouple locations		Max. temperature rise measured, dT (K)	Max. temperature rise limit, dT (K)
Supply cord		36,0	50
Cord sheath		34,5	35
Internal wire		37,3	50
Fuse holder		40,3	For cl.30.1
Handle		27,5	60
Drum		15,0	For cl.30.1
Wash timer		6,9	60(T85)
Knob		7,6	60
Main motor winding		66,3	115(Class 155(F))
X2 capacitor		24,4	60(T85)
Motor running capacitor		33,4	45(T70)
Wire connector		30,8	125(T150)
Control panel		12,2	60
Enclosure		8,6	60
Test corner		8,5	65
Supplementary information: Model XPB48-800D assembled with motor XPD-90 and the most unfavorable results were record here.			

11.8-2	TABLE: Heating test, resistance method					P
	Test voltage (V)		254,4 V			—
	Ambient, t1 (°C)		24,3 °C			—
	Ambient, t2 (°C)		25,0 °C			—
Temperature rise of winding		R1 (Ω)	R2 (Ω)	dT (K)	Max. dT (K)	Insulation class
Primary winding of wash motor		27,5	35,7	76,5	115	Class 155 (F)
Secondary winding of wash motor		26,8	35,2	80,4	115	Class 155 (F)
Supplementary information: Model XPB48-800D assembled with motor XPD-90 and the most unfavorable results were record here.						

11.8-3	TABLE: Heating test, thermocouple measurements		P
	Test voltage (V) : :	254,4 V	—
	Ambient (°C)..... : :	T1=23,4 °C, T2=24,0 °C	—
Thermocouple locations		Max. temperature rise measured, dT (K)	Max. temperature rise limit, dT (K)
Supply cord		32,4	50
Cord sheath		32,8	35
Internal wire		37,2	50
Fuse holder		44,4	For cl.30.1
Handle		25,2	60
Drum		37,0	For cl.30.1
Wash timer		23,1	60(T85)
Knob		17,7	60
Main motor winding		92,3	115(Class 155(F))
X2 capacitor		20,6	60(T85)
Motor running capacitor		43,5	45(T70)
Wire connector		34,6	125(T150)
Control panel		26,1	60
Enclosure		29,6	60
Test corner		8,2	65
Supplementary information: Model XPB62-800D assembled with motor XPD-120 and the most unfavorable results were record here.			

11.8-3	TABLE: Heating test, resistance method					P
	Test voltage (V)		254,4 V			—

	Ambient, t1 (°C)..... :	23,4 °C			—
	Ambient, t2 (°C)..... :	24,0 °C			—
Temperature rise of winding	R1 (Ω)	R2 (Ω)	dT (K)	Max. dT (K)	Insulation class
Primary winding of wash motor	27,1	37,5	98,4	115	Class 155 (F)
Secondary winding of wash motor	26,9	37,2	98,1	115	Class 155 (F)
Supplementary information: Model XPB62-800D assembled with motor XPD-120 and the most unfavorable results were record here.					

11.8-4	TABLE: Heating test, thermocouple measurements		P
	Test voltage (V) : :	254,4 V	—
	Ambient (°C)..... :	T1=23,0 °C, T2=23,0 °C	—
Thermocouple locations		Max. temperature rise measured, dT (K)	Max. temperature rise limit, dT (K)
Supply cord		24,9	50
Cord sheath		24,1	35
Internal wire		43,9	50
Fuse holder		34,6	For cl.30.1
Handle		18,9	60
Drum		11,2	For cl.30.1
Wash timer		6,1	60(T85)
Select switch		6,1	30(T55)
Knob		7,9	60
Main motor winding		88,2	115(Class 155(F))
X2 capacitor		17,2	60(T85)
Motor running capacitor		30,1	45(T70)
Wire connector		19,5	125(T150)
Control panel		5,2	60
Enclosure		5,2	60
Test corner		6,8	65
Supplementary information: Model XPB78-800D assembled with motor XPD-150 and the most unfavorable results were record here.			

11.8-4	TABLE: Heating test, resistance method			P
	Test voltage (V) :	254,4 V	—	

	Ambient, t1 (°C)..... :	23,4 °C			—
	Ambient, t2 (°C)..... :	24,0 °C			—
Temperature rise of winding	R1 (Ω)	R2 (Ω)	dT (K)	Max. dT (K)	Insulation class
Primary winding of wash motor	33,7	44,9	85,6	115	Class 155 (F)
Secondary winding of wash motor	33,5	44,5	84,6	115	Class 155 (F)
Supplementary information: Model XPB78-800D assembled with motor XPD-150 and the most unfavorable results were record here.					

13.2	TABLE: Leakage current		P
	Heating appliances: 1.15 x rated input (W)..... :	N/A	—
	Motor-operated and combined appliances: 1.06 x rated voltage (V)..... :	254,4 V	—
Leakage current between		I (mA)	Max. allowed I (mA)
Model XPB25-800D assembled with motor XPD-50			
L/N and the earthed metal		0,08	3,5
L/N and plastic enclosure		0,02	0,35 peak
Model XPB48-800D assembled with motor XPD-90			
L/N and the earthed metal		0,07	3,5
L/N and plastic enclosure		0,01	0,35 peak
Model XPB62-800D assembled with motor XPD-120			
L/N and the earthed metal		0,09	3,5
L/N and plastic enclosure		0,04	0,35 peak
Model XPB78-800D assembled with motor XPD-150			
L/N and the earthed metal		0,11	3,5
L/N and plastic enclosure		0,03	0,35 peak
Supplementary information: The most unfavourable results were recorded here.			

13.3	TABLE: Electric strength			P
Test voltage applied between:		Voltage (V)	Breakdown (Yes/No)	
Live parts and earthed metal		1060	No	
Basic insulation and accessible plastic parts		1810	No	
Live parts and accessible plastic parts		3120	No	
Supplementary information: The most unfavourable results were recorded here.				

14	TABLE: Transient overvoltages					N/A
Clearance between:	CI (mm)	Required CI (mm)	Rated impulse voltage (V)	Impulse test voltage (V)	Flashover (Yes/No)	

—	—	—	—	—	—
Supplementary information: N/A					

16.2	TABLE: Leakage current			P
	Single phase appliances: 1.06 x rated voltage (V)	254,4	—	
	Three phase appliances 1.06 x rated voltage divided by $\sqrt{3}$ (V).....	N/A	—	
Leakage current between		I (mA)	Max. allowed I (mA)	
Live parts and the earthed metal		0,09	3,5	
Live parts and plastic enclosure		0,01	0,25	
Supplementary information: N/A				

16.3	TABLE: Electric strength			P
Test voltage applied between:		Voltage (V)	Breakdown (Yes/No)	
Live parts and earthed metal		1310	No	
Basic insulation and accessible plastic parts		1810	No	
Live parts and accessible plastic parts		3120	No	
Supplementary information: N/A				

17	TABLE: Overload protection, temperature rise			P
	Test voltage (V)	254,4	—	
Thermocouple locations		T (°C)	Max. T (°C)	
—		—	—	
Supplementary information: N/A				

17	TABLE: Overload protection, resistance method					N/A
	Test voltage (V)		—		—	
	Ambient, t1 (°C).....		—		—	
	Ambient, t2 (°C).....		—		—	
Temperature of winding		R1 (Ω)	R2 (Ω)	dT (K)	T (°C)	Max. T (°C)
—		—	—	—	—	—
Supplementary information: N/A						

19	Abnormal operation conditions			P
Operational characteristics		YES/NO	Operational conditions	
Are there electronic circuits to control the appliance operation?		YES	Electronic circuits control the appliance operation when plug in	

Are there "off" or "stand-by" position?			YES	Off position when plug in			
The unintended operation of the appliance results in dangerous malfunction?			NO	No possible dangerous malfunction			
Sub-clause	Operating conditions description	Test results description	PEC description	EMP 19.11.4	Software type required	19.11.3 PEC	Final result
19.2	N/A	N/A	N/A	N/A	N/A	N/A	N/A
19.3	N/A	N/A	N/A	N/A	N/A	N/A	N/A
19.4	N/A	N/A	N/A	N/A	N/A	N/A	N/A
19.5	N/A	N/A	N/A	N/A	N/A	N/A	N/A
19.6	N/A	N/A	N/A	—	N/A	N/A	N/A
19.7	Abnormal conditions: lock motor	Temperature rise not exceed limited value	N/A	—	N/A	N/A	P
19.8	N/A	N/A	N/A	N/A	N/A	N/A	N/A
19.9	N/A	N/A	N/A	N/A	N/A	N/A	N/A
19.10	N/A	N/A	N/A	N/A	N/A	N/A	N/A
19.11.2	N/A	N/A	N/A	N/A	N/A	N/A	N/A
19.11.4.8	N/A	N/A	N/A	N/A	N/A	N/A	N/A
19.101	N/A	N/A	N/A	N/A	N/A	N/A	N/A
19.102	N/A	N/A	N/A	—	N/A	N/A	N/A

19.7 & Annex D	TABLE: Abnormal operation, locked rotor/moving parts						P
	Test voltage (V) :			230 V; 60 Hz			—
	Ambient, t1 (°C) :			22,2			—
	Ambient, t2 (°C) :			23,3			—
Temperature of winding		R1 (Ω)	R2 (Ω)	dT (K)	T (°C)	Max. T (°C)	
Model XPB25-800D assembled with motor XPD-50							
Motor winding (motor capacitor normal)		—	—	—	129,6	190 (Class 155 (F))	
Motor winding (motor capacitor open circuit)		—	—	—	142,3	190 (Class 155 (F))	
Model XPB48-800D assembled with motor XPD-90							
Motor winding (motor capacitor normal)		—	—	—	149,7	190 (Class 155 (F))	
Motor winding		—	—	—	104,9	190 (Class 155 (F))	

(motor capacitor open circuit)					
Model XPB62-800D assembled with motor XPD-120					
Motor winding (motor capacitor normal)	—	—	—	131,8	190 (Class 155 (F))
Motor winding (motor capacitor open circuit)	—	—	—	128,1	190 (Class 155 (F))
Model XPB78-800D assembled with motor XPD-150					
Motor winding (motor capacitor normal)	—	—	—	147,2	190 (Class 155 (F))
Motor winding (motor capacitor open circuit)	—	—	—	156,4	190 (Class 155 (F))
Supplementary information: The most unfavourable results were recorded here.					

19.9	TABLE: Abnormal operation, running overload					N/A
	Test voltage (V)		—			—
	Ambient, t1 (°C)		—			—
	Ambient, t2 (°C)		—			—
Temperature of winding	R1 (Ω)	R2 (Ω)	dT (K)	T (°C)	Max. T (°C)	
—	—	—	—	—	—	—
Supplementary information: N/A						

19.13	TABLE: Abnormal operation, temperature rises			P
Thermocouple locations		Max. temperature rise measured, dT (K)	Max. temperature rise limit, dT (K)	
Plastic enclosure		11,3	For cl. 30.1	
Supplementary information: The most unfavorable results were recorded here.				

24.1	Table: components				P
Object / part No.	Manufacturer/ trademark	Type / model	Technical data	Standard ²⁾	Mark(s) of conformity ¹⁾
Plug	Ningbo Ousheng Electric Appliance Co., Ltd.	S03	250 V ~, 16 A	VDE 0620-1 IEC 60884-1	VDE 40023763
Alt.	Ningbo Ousheng Electric Appliance Co., Ltd.	OS13	250 V~, 13 A	BS 1363-1 IEC 60884-1	ASTA 1176
Alt.	Ningbo Ousheng Electric Appliance Co., Ltd.	OS05A	250V~, 7,5A	AS/NZS 3112	SAA 121130EA
Supply Cord	Ningbo Ousheng Electric Appliance Co., Ltd.	H05VV-F 60227 IEC 53	3G 0,75 mm ²	EN 50252-2-11 IEC 60227	VDE 40021137

Internal wire	Xiaoshan Haoguang Electric Wire & Cable Co., Ltd.	H05S-K	0,5 mm ² 1,0 mm ²	EN 50252-2-11 IEC 60227	Tested with appliance
Alt.	Cixi Haosheng Wire& Cable Co., LTD	60227 IEC 08(RV-90)	0,5 mm ² 0,75 mm ²	IEC/EN 60335-1 IEC/EN 60335-2-7	CQC 2008010105 271905 + Tested with appliance
Washing switch	Cixi City Songkai Electric Factory	XZK	220V-250 V AC, 3,5 A	IEC/EN 61058-1	CN 43486
Washing timer	Cixi City Songkai Electric Factory	DXT15	220V-250 V AC, 3,5 A	IEC/EN 60730-1 IEC/EN 60730-2-7	CN 43509
Wire connector	Heavy Power Co., Ltd.	CE2	T150	IEC/EN 60335-1 IEC/EN 60335-2-7	UL E113650+ Tested with appliance
Fuse	Zhenjiang Baoxiang Electronics Co., Ltd.	RF1-20	F, 5AL, 250 V	IEC/EN 60127-1	CQC 2019010207 192091
X2 capacitor	Cixi Yuandong Electronics Co., Ltd.	MPX	275 V, 0,047 uF -1,0 uF, T85	IEC/EN 60384-14	VDE 40009966
Wash motor (XPBy-800D (y=15, 18, 20, 25))	Zhejiang Weikang Motor Co., Ltd.	XPD-50	220-240 V, 50/60 Hz, Class 155(F), 50 W	IEC/EN 60335-1 IEC/EN 60335-2-7	Tested with appliance
Motor running capacitor	Cixi Riyi Capacitor Factory	CBB65A-S4	AC 450 V, 50/60 Hz, 4 uF, T70, P2	IEC/EN 60252-1	TUV R 50244741
Alt.	Ningguo Lonch Electric Co., Ltd	CBB61	AC 450 V, 50/60 Hz, 4 uF, T85	IEC/EN 60252-1	TUV R 50351707
Wash motor (XPBy-800D (y=28, 30, 35, 38, 42, 48))	Zhejiang Weikang Motor Co., Ltd.	XPD-90	220-240 V, 50/60 Hz, Class 155(F), 90 W	IEC/EN 60335-1 IEC/EN 60335-2-7	Tested with appliance
Motor running capacitor	Ningbo Zhenhai Longrong Electronic Component Factory	CBB65	AC 450 V, 50/60 Hz, 6 uF, T70, P2	IEC/EN 60252-1	TUV R 50280410
Alt.	Ningguo Lonch Electric Co., Ltd	CBB61	450 VAC, 50/60 Hz, 6 uF, 40/85/21 ZHASH	IEC/EN 60252-1	TUV R 50351707
Alt.	Cixi Riyi Capacitor Factory	CBB65A-S4	AC 450 V, 50/60 Hz, 6 uF, T70, P2	IEC/EN 60252-1	TUV R 50244741

Wash motor (XPBy-800D (y=52, 58, 62))	Zhejiang Weikang Motor Co., Ltd.	XPD-120	220-240 V, 50/60 Hz, Class 155(F), 120 W	IEC/EN 60335-1 IEC/EN 60335-2-7	Tested with appliance
Motor running capacitor	Ningbo Zhenhai Longrong Electronic Component Factory	CBB65	AC 450 V, 50/60 Hz, 10 µF, T70, P2	IEC/EN 60252-1	TUV R 50280410
Alt.	Cixi Riyi Capacitor Factory	CBB65A-S4	AC 450 V, 50/60 Hz, 10 µF, T70, P2	IEC/EN 60252-1	TUV R 50244741
Alt.	Ningguo Lonch Electric Co., Ltd	CBB61	450 VAC 50/60 Hz, 10 uF 40/85/21	IEC/EN 60252-1	TUV R 50351707
Wash motor (XPBy-800D (y=68, 78))	Zhejiang Weikang Motor Co., Ltd.	XPD-150	220-240 V, 50/60 Hz, Class 155(F), 150 W	IEC/EN 60335-1 IEC/EN 60335-2-7	Tested with appliance
Motor running capacitor	Ningbo Zhenhai Longrong Electronic Component Factory	CBB65	AC 450 V, 50/60 Hz, 12 µF, T70, P2	IEC/EN 60252-1	TUV R 50280410
Alt.	Cixi Riyi Capacitor Factory	CBB65A-S4	AC 450 V, 50/60 Hz, 12 µF, T70, P2	IEC/EN 60252-1	TUV R 50244741
Enclosure PP	Shanghai Oil & Chemical Industry Co., Ltd.	PA-765(+)	Min. Thick. 2,2 mm	IEC/EN 60335-1 IEC/EN 60335-2-7	Tested with appliance
Enclosure ABS	Ningbo Lejin Yongxing Chemical Industry Co., Ltd.	EFR63(b)	Min. Thick. 2,2 mm	IEC/EN 60335-1 IEC/EN 60335-2-7	Tested with appliance
Motor protector	Jiangsu Changsheng Electric Appliance Co., Ltd.	BR-A2D	250 V, 6 A, Tf135	IEC/EN 60730-1	VDE 40015893

Supplementary information:

- 1) Provided evidence ensures the agreed level of compliance. See OD-2039
- 2) License available upon request.

28.1	TABLE: Threaded part torque test			P
Threaded part identification	Diameter of thread (mm)	Column number (I, II, or III)	Applied torque (Nm)	
Screw to fix enclosure	3,90	II	1,2	
Screw to fix earthing wire	3,90	II	1,2	
Supplementary information: N/A				

29.1	TABLE: Clearances			P
	Overvoltage category.....	II		—

		Type of insulation:				
Rated impulse voltage (V):	Min. cl (mm)	Basic (mm)	Supplementary (mm)	Reinforced (mm)	Functional (mm)	Verdict / Remark
330	0,2* / 0,5 / 0,8**	—	—	—	—	N/A
500	0,2* / 0,5 / 0,8**	—	—	—	—	N/A
800	0,2* / 0,5 / 0,8**	—	—	—	—	N/A
1 500	0,5 / 0,8** / 1,0***	—	—	—	—	N/A
2 500	<u>1,5 / 2,0***</u>	B1 B2 B3 B4	S1	—	F1	P
4 000	<u>3,0 / 3,5***</u>	—	—	R1	—	P
6 000	5,5 / 6,0***	—	—	—	—	N/A
8 000	8,0 / 8,5***	—	—	—	—	N/A
10 000	11,0 / 11,5***	—	—	—	—	N/A

Supplementary information:

*) For tracks on printed circuit boards if pollution degree 1 and 2

**) For pollution degree 3

***) If the construction is affected by wear, distortion, movement of the parts or during assembly

Basic insulation (B):

B1: Between the motor's winding and the iron core: Cl.=5,0 mm;

B2: Between the motor's winding and the iron core: Cl.=5,2 mm;

B3: Between the motor's winding and the iron core: Cl.=5,3 mm;

B4: Between the motor's winding and the iron core: Cl.=5,1 mm;

Supplementary insulation (S):

S1: Between the internal wires and the accessible positions: Cl.= 9,6 mm;

Function insulation (F):

F1: Between two poles of motor connector terminal: Cl.=6,0 mm;

Reinforce insulation (R):

R1: Between accessible part on timer knob and live parts: Cl.=22,0 mm.

29.2	TABLE: Creepage distances, basic, supplementary and reinforced insulation										P
Working voltage (V)	Creepage distance (mm) Pollution degree							Type of insulation			
	1	2			3						
		Material group			Material group						
		I	II	IIIa/IIIb	I	II	IIIa/IIIb*)	B**)	S**)	R**)	Verdict
≤50	0,18	0,6	0,85	1,2	1,5	1,7	1,9		—	—	N/A
≤50	0,18	0,6	0,85	1,2	1,5	1,7	1,9	—		—	N/A
≤50	0,36	1,2	1,7	2,4	3,0	3,4	3,8	—	—		N/A

125	0,28	0,75	1,05	1,5	1,9	2,1	2,4		—	—	N/A
125	0,28	0,75	1,05	1,5	1,9	2,1	2,4	—		—	N/A
125	0,56	1,5	2,1	3,0	3,8	4,2	4,8	—	—		N/A
250	0,56	1,25	1,8	2,5	3,2	3,6	4,0		—	—	P
250	0,56	1,25	1,8	2,5	3,2	3,6	4,0	—		—	P
250	1,12	2,5	3,6	5,0	6,4	7,2	8,0	—	—		P
400	1,0	2,0	2,8	4,0	5,0	5,6	6,3(2.0 for motor only)	B1 B2 B3 B4	—	—	P
400	1,0	2,0	2,8	4,0	5,0	5,6	6,3	—	S1	—	N/A
400	2,0	4,0	5,6	8,0	10,0	11,2	12,6	—	—	R1	N/A
500	1,3	2,5	3,6	5,0	6,3	7,1	8,0		—	—	N/A
500	1,3	2,5	3,6	5,0	6,3	7,1	8,0	—		—	N/A
500	2,6	5,0	7,2	10,0	12,6	14,2	16,0	—	—		N/A
>630 and ≤800	1,8	3,2	4,5	6,3	8,0	9,0	10,0		—	—	N/A
>630 and ≤800	1,8	3,2	4,5	6,3	8,0	9,0	10,0	—		—	N/A
>630 and ≤800	3,6	6,4	9,0	12,6	16,0	18,0	20,0	—	—		N/A
>800 and ≤1000	2,4	4,0	5,6	8,0	10,0	11,0	12,5		—	—	N/A
>800 and ≤1000	2,4	4,0	5,6	8,0	10,0	11,0	12,5	—		—	N/A
>800 and ≤1000	4,8	8,0	11,2	16,0	20,0	22,0	25,0	—	—		N/A
>1000 and ≤1250	3,2	5,0	7,1	10,0	12,5	14,0	16,0		—	—	N/A
>1000 and ≤1250	3,2	5,0	7,1	10,0	12,5	14,0	16,0	—		—	N/A
>1000 and ≤1250	6,4	10,0	14,2	20,0	25,0	28,0	32,0	—	—		N/A
>1250 and ≤1600	4,2	6,3	9,0	12,5	16,0	18,0	20,0		—	—	N/A
>1250 and ≤1600	4,2	6,3	9,0	12,5	16,0	18,0	20,0	—		—	N/A
>1250 and ≤1600	8,4	12,6	18,0	25,0	32,0	36,0	40,0	—	—		N/A
>1600 and ≤2000	5,6	8,0	11,0	16,0	20,0	22,0	25,0		—	—	N/A
>1600 and ≤2000	5,6	8,0	11,0	16,0	20,0	22,0	25,0	—		—	N/A
>1600 and ≤2000	11,2	16,0	22,0	32,0	40,0	44,0	50,0	—	—		N/A
>2000 and ≤2500	7,5	10,0	14,0	20,0	25,0	28,0	32,0		—	—	N/A
>2000 and ≤2500	7,5	10,0	14,0	20,0	25,0	28,0	32,0	—		—	N/A
>2000 and ≤2500	15,0	20,0	28,0	40,0	50,0	56,0	64,0	—	—		N/A
>2500 and ≤3200	10,0	12,5	18,0	25,0	32,0	36,0	40,0		—	—	N/A
>2500 and ≤3200	10,0	12,5	18,0	25,0	32,0	36,0	40,0	—		—	N/A
>2500 and ≤3200	20,0	25,0	36,0	50,0	64,0	72,0	80,0	—	—		N/A

>3200 and ≤4000	12,5	16,0	22,0	32,0	40,0	45,0	50,0		—	—	N/A
>3200 and ≤4000	12,5	16,0	22,0	32,0	40,0	45,0	50,0	—		—	N/A
>3200 and ≤4000	25,0	32,0	44,0	64,0	80,0	90,0	100,0	—	—		N/A
>4000 and ≤5000	16,0	20,0	28,0	40,0	50,0	56,0	63,0		—	—	N/A
>4000 and ≤5000	16,0	20,0	28,0	40,0	50,0	56,0	63,0	—		—	N/A
>4000 and ≤5000	32,0	40,0	56,0	80,0	100,0	112,0	126,0	—	—		N/A
>5000 and ≤6300	20,0	25,0	36,0	50,0	63,0	71,0	80,0		—	—	N/A
>5000 and ≤6300	20,0	25,0	36,0	50,0	63,0	71,0	80,0	—		—	N/A
>5000 and ≤6300	40,0	50,0	72,0	100,0	126,0	142,0	160,0	—	—		N/A
>6300 and ≤8000	25,0	32,0	45,0	63,0	80,0	90,0	100,0		—	—	N/A
>6300 and ≤8000	25,0	32,0	45,0	63,0	80,0	90,0	100,0	—		—	N/A
>6300 and ≤8000	50,0	64,0	90,0	126,0	160,0	180,0	200,0	—	—		N/A
>8000 and ≤10000	32,0	40,0	56,0	80,0	100,0	110,0	125,0		—	—	N/A
>8000 and ≤10000	32,0	40,0	56,0	80,0	100,0	110,0	125,0	—		—	N/A
>8000 and ≤10000	64,0	80,0	112,0	160,0	200,0	220,0	250,0	—	—		N/A
>10000 and ≤12500	40,0	50,0	71,0	100,0	125,0	140,0	160,0		—	—	N/A
>10000 and ≤12500	40,0	50,0	71,0	100,0	125,0	140,0	160,0	—		—	N/A
>10000 and ≤12500	80,0	100,0	142,0	200,0	250,0	280,0	320,0	—	—		N/A

Supplementary information:

*) Material group IIIb is allowed if the working voltage does not exceed 50 V

**) B = Basic insulation, S = Supplementary insulation, R = Reinforced insulation

Basic insulation (B):

B1: Between the motor's winding and the iron core: Cr.= 5,0 mm;

B2: Between the motor's winding and the iron core: Cr.= 5,2 mm;

B3: Between the motor's winding and the iron core: Cr.= 5,3 mm;

B4: Between the motor's winding and the iron core: Cr.= 5,1 mm;

Supplementary insulation (S):

S1: Between the internal wires and the accessible positions: Cr.= 9,6 mm;

Reinforce insulation (R):

R1: Between accessible part on timer knob and live parts: Cr.=28,0 mm

29.2	TABLE: Creepage distances, functional insulation							P
Working voltage (V)	Creepage distance (mm) Pollution degree							
	1	2			3			
		Material group			Material group			
		I	II	IIIa/IIIb	I	II	IIIa/IIIb*)	Verdict / Remark
≤10	0,08	0,4	0,4	0,4	1,0	1,0	1,0	N/A

50	0,16	0,56	0,8	1,0	1,4	1,6	1,8	N/A
125	0,25	0,71	1,0	1,4	1,8	2,0	2,2	N/A
250	0,42	1,0	1,4	2,0	2,5	2,8	3,2	P: F1
250	0,42	1,0	1,4	2,0	2,5	2,8	3,2	N/A
400	0,75	1,6	2,2	3,2	4,0	4,5	5,0	N/A
500	1,0	2,0	2,8	4,0	5,0	5,6	6,3	N/A
>630 and ≤800	1,8	3,2	4,5	6,3	8,0	9,0	10,0	N/A
>800 and ≤1000	2,4	4,0	5,6	8,0	10,0	11,0	12,5	N/A
>1000 and ≤1250	3,2	5,0	7,1	10,0	12,5	14,0	16,0	N/A
>1250 and ≤1600	4,2	6,3	9,0	12,5	16,0	18,0	20,0	N/A
>1600 and ≤2000	5,6	8,0	11,0	16,0	20,0	22,0	25,0	N/A
>2000 and ≤2500	7,5	10,0	14,0	20,0	25,0	28,0	32,0	N/A
>2500 and ≤3200	10,0	12,5	18,0	25,0	32,0	36,0	40,0	N/A
>3200 and ≤4000	12,5	16,0	22,0	32,0	40,0	45,0	50,0	N/A
>4000 and ≤5000	16,0	20,0	28,0	40,0	50,0	56,0	63,0	N/A
>5000 and ≤6300	20,0	25,0	36,0	50,0	63,0	71,0	80,0	N/A
>6300 and ≤8000	25,0	32,0	45,0	63,0	80,0	90,0	100,0	N/A
>8000 and ≤10000	32,0	40,0	56,0	80,0	100,0	110,0	125,0	N/A
>10000 and ≤12500	40,0	50,0	71,0	100,0	125,0	140,0	160,0	N/A

Supplementary information:

*) Material group IIb is allowed if the working voltage does not exceed 50 V

Function insulation (F):

F1: Between two poles of motor connector terminal: Cr.=6,0 mm;

30.1	TABLE: Ball Pressure Test of Thermoplastics			P
Allowed impression diameter (mm) :		2,0		—
Object/ Part No./ Material	Manufacturer/ trademark	Test temperature (°C)	Impression diameter (mm)	
Enclosure	See table 24.1	75	0,7	
Control panel	—	75	0,5	
Wash timer	Cixi City Songkai Electric Factory	125	0,8	
Select switch	Cixi City Songkai Electric Factory	125	0,8	
Fuse holder	Zhenjiang Baoxiang Electronics Co., Ltd.	125	0,3	
Motor running capacitor	See table 24.1	125	0,3	
Motor bobbin	Zhejiang Weikang Motor Co., Ltd.	125	0,8	

Wire connector	Heavy Power Co., Ltd.	125	0,8
X2 capacitor	Cixi Yuandong Electronics Co., Ltd.	125	0,8
Terminal block	—	125	1,0
Supplementary information: The ball pressure test was performed on each type listed above. The most unfavourable results were recorded here.			

30.2	TABLE: Resistance to heat and fire - Glow wire tests							P
Object/ Part No./ Material	Manufacturer/ trademark	Glow wire test (GWT); (°C)						Verdict
		550	650		750		850	
			te	ti	te	ti		
Enclosure	See table 24.1	X	—	—	—	—	—	P
Control panel	—	X	—	—	—	—	—	P
Washing timer	Cixi City Songkai Electric Factory	X	—	—	—	—	—	P
Washing switch	Cixi City Songkai Electric Factory	—	—	—	0s	0s	X	P
Fuse holder	Zhenjiang Baoxiang Electronics Co., Ltd.	—	—	—	0s	0s	X	P
Motor running capacitor	See table 24.1	—	—	—	0s	0s	X	P
Motor bobbin	Zhejiang Weikang Motor Co., Ltd.	—	—	—	0s	0s	X	P
Wire connector	Heavy Power Co., Ltd.	—	—	—	0s	0s	X	P
X2 capacitor	Cixi Yuandong Electronics Co., Ltd.	—	—	—	0s	0s	X	P
Terminal block	—	—	—	—	0s	0s	X	P
Object/ Part No./ Material	Manufacture r/ trademark	Glow-wire flammability index (GWFI), °C				GW ignition temp. (GWIT), °C		Verdict
		550	650	750	850	675	775	
—	—	—	—	—	—	—	—	—
The test specimen passed the glow wire test (GWT) with no ignition [(te – ti) ≤ 2s] (Yes/No):								Yes
If no, then surrounding parts passed the needle-flame test of annex E (Yes/No)..... :								—
The test specimen passed the test by virtue of most of the flaming material being withdrawn with the glow-wire (Yes/No)?..... :								Yes
Ignition of the specified layer placed underneath the test specimen (Yes/No):								No

Supplementary information:

550 °C GWT not relevant (or applicable) to parts of material classified at least HB40 or if relevant HBF
The GWIT pre-selection option, the 850 °C GWFI pre-selection option, and the 850 °C GWT are not relevant (or applicable) for attended appliances.

30.2.4	TABLE: Needle- flame test (NFT)					P
Object/ Part No./ Material	Manufacturer/ trademark	Duration of application of test flame (ta); (s)	Ignition of specified layer Yes/No	Duration of burning (tb) (s)	Verdict	
—	—	—	—	—	—	

Supplementary information:

NFT not relevant (or applicable) for Parts of material classified as V-0 or V-1

NFT not relevant (or applicable) for Base material of PCBs classified as V-0 or if relevant VTM-0.

The NFT test was performed on each type separately. The most unfavourable results were recorded here.

--- End of Report ---

Type of equipment, model: Single-tub Washing Machine (Mini Washing Machine)
XPBy-800D
(y=15, 18, 20, 25, 28, 30, 35, 38, 42, 48, 52, 58, 62, 68, 78)

Details of: XPB15-800D and XPB18-800D: Front view



Details of: XPB15-800D and XPB18-800D: Rear view and marking plate




Details of: XPB15-800D and XPB18-800D: Left view



Details of: XPB15-800D and XPB18-800D: Right view



Details of: XPB15-800D and XPB18-800D: Top view



Details of: XPB15-800D, XPB18-800D and XPB20-800D: Open view



Details of: XPB15-800D and XPB18-800D: Control panel and wash timer knob

View:


- ☒ general
- ☐ front
- ☐ rear
- ☐ right
- ☐ left
- ☐ top
- ☐ bottom



Details of: XPB15-800D, XPB18-800D and XPB20-800D: Bottom view

View:

- ☐ general
- ☐ front
- ☐ rear
- ☐ right
- ☐ left
- ☐ top
- ☒ bottom



Details of: XPB20-800D: Front view



Details of: XPB20-800D: Rear view



Details of: XPB20-800D: Left view

View:

- ☐ general
- ☐ front
- ☐ rear
- ☐ right
- ☒ left
- ☐ top
- ☐ bottom



Details of: XPB20-800D: Right view

View:

- ☐ general
- ☐ front
- ☐ rear
- ☒ right
- ☐ left
- ☐ top
- ☐ bottom



Details of:

XPB20-800D: Top view, control panel, wash timer knob
and CAUTION: do not connect to the hot water supply

View:

- ☐ general
- ☐ front
- ☐ rear
- ☐ right
- ☐ left
- ☒ top
- ☐ bottom



Details of:

XPB20-800D: Internal view of control panel and wash timer

View:

- ☒ general
- ☐ front
- ☐ rear
- ☐ right
- ☐ left
- ☐ top
- ☐ bottom



Details of: XPB25-800D: Front view

View:

- ☐ general
- ☒ front
- ☐ rear
- ☐ right
- ☐ left
- ☐ top
- ☐ bottom



Details of: XPB25-800D: Rear view

View:

- ☐ general
- ☐ front
- ☒ rear
- ☐ right
- ☐ left
- ☐ top
- ☐ bottom



Details of: XPB25-800D: Left view

View:

- ☐ general
- ☐ front
- ☐ rear
- ☐ right
- ☒ left
- ☐ top
- ☐ bottom



Details of: XPB25-800D: Right view

View:

- ☐ general
- ☐ front
- ☐ rear
- ☒ right
- ☐ left
- ☐ top
- ☐ bottom



Details of: XPB25-800D: Top view and CAUTION: do not connect to the hot water supply

View:


- ☐ general
- ☐ front
- ☐ rear
- ☐ right
- ☐ left
- ☒ top
- ☐ bottom



Details of: XPB25-800D: Internal view of control panel and wash timer

View:

- ☐ general
- ☐ front
- ☐ rear
- ☐ right
- ☐ left
- ☒ top
- ☐ bottom



Details of: XPB25-800D: Open view

View:

- ☒ general
- ☐ front
- ☐ rear
- ☐ right
- ☐ left
- ☐ top
- ☐ bottom



Details of: XPB25-800D: Bottom view

View:

- ☐ general
- ☐ front
- ☐ rear
- ☐ right
- ☐ left
- ☐ top
- ☒ bottom



Details of: XPB15-800D, XPB18-800D, XPB20-800D and XPB25-800D: Internal view

View:


- ☒ general
- ☐ front
- ☐ rear
- ☐ right
- ☐ left
- ☐ top
- ☐ bottom



Details of: XPB15-800D, XPB18-800D, XPB20-800D and XPB25-800D: Wash motor XPD-50

View:

- ☒ general
- ☐ front
- ☐ rear
- ☐ right
- ☐ left
- ☐ top
- ☐ bottom



Details of: XPB28-800D, XPB30-800D and XPB35-800D: Front and top view



Details of: XPB38-800D: Front view



Details of: XPB38-800D: Left view

View:


- ☐ general
- ☐ front
- ☐ rear
- ☐ right
- ☒ left
- ☐ top
- ☐ bottom



Details of: XPB38-800D: Right view

View:


- ☐ general
- ☐ front
- ☐ rear
- ☒ right
- ☐ left
- ☐ top
- ☐ bottom



Details of: XPB38-800D: Top view and CAUTION: do not connect to the hot water supply

View:

- ☐ general
- ☐ front
- ☐ rear
- ☐ right
- ☐ left
- ☒ top
- ☐ bottom



Details of: XPB38-800D: Open view

View:

- ☒ general
- ☐ front
- ☐ rear
- ☐ right
- ☐ left
- ☐ top
- ☐ bottom



Details of: XPB38-800D: Wash timer knob and select switch knob

View:

- ☒ general
- ☐ front
- ☐ rear
- ☐ right
- ☐ left
- ☐ top
- ☐ bottom



Details of: XPB38-800D: Internal view of control panel

View:

- ☐ general
- ☐ front
- ☐ rear
- ☐ right
- ☐ left
- ☐ top
- ☒ bottom



Details of: XPB38-800D: Internal view of control panel, wash timer and select switch

View:

- ☐ general
- ☒ front
- ☐ rear
- ☐ right
- ☐ left
- ☐ top
- ☐ bottom



Details of: XPB42-800D and XPB48-800D: Front view

View:

- ☐ general
- ☒ front
- ☐ rear
- ☐ right
- ☐ left
- ☐ top
- ☐ bottom



Details of: XPB42-800D and XPB48-800D: Rear view



Details of: XPB42-800D and XPB48-800D: Left view




Details of: XPB42-800D and XPB48-800D: Right view




Details of: XPB42-800D and XPB48-800D: Top view



Details of: XPB42-800D and XPB48-800D: Open view and CAUTION: do not connect to the hot water supply



Details of: XPB28-800D, XPB30-800D, XPB35-800D, XPB38-800D, XPB42-800D and XPB48-800D:
Wash motor XPD-90



Details of: XPB52-800D, XPB58-800D and XPB62-800D: Front view




Details of: XPB52800D, XPB58-800D and XPB62-800D: Rear view
and CAUTION: do not connect to the hot water supply




Details of: XPB52-800D, XPB58-800D and XPB62-800D: Left view



Details of: XPB52-800D, XPB58-800D and XPB62-800D: Right view



Details of: XPB52-800D, XPB58-800D and XPB62-800D: Top view



Details of: XPB52-800D, XPB58-800D and XPB62-800D: Open view



Details of: XPB52-800D, XPB58-800D and XPB62-800D: Open view and high water level



Details of: XPB52-800D, XPB58-800D and XPB62-800D: Bottom view



Details of: XPB52-800D, XPB58-800D and XPB62-800D: Wash motor XPD-120



Details of: XPB68-800D and XPB78-800D: Front view



Details of: XPB68-800D and XPB78-800D: Rear view and marking plate

View:


- ☐ general
- ☐ front
- ☒ rear
- ☐ right
- ☐ left
- ☐ top
- ☐ bottom



Details of: XPB68-800D and XPB78-800D: Left view

View:

- ☐ general
- ☐ front
- ☐ rear
- ☐ right
- ☒ left
- ☐ top
- ☐ bottom



Details of: XPB68-800D and XPB78-800D: Right view



Details of: XPB68-800D: Top view and CAUTION: do not connect to the hot water supply



Details of: XPB78-800D: Top view and CAUTION: do not connect to the hot water supply



Details of: XPB68-800D and XPB78-800D: Open view



Details of: XPB68-800D: Another colour



Details of: XPB68-800D and XPB78-800D: Internal view of control panel, wash timer and select switch



Details of: XPB68-800D and XPB78-800D: Wash motor XPD-150

View:


- ☐ general
- ☐ front
- ☐ rear
- ☐ right
- ☐ left
- ☐ top
- ☒ bottom




Details of: All models: Fuse holder and terminal block

View:

- ☒ general
- ☐ front
- ☐ rear
- ☐ right
- ☐ left
- ☐ top
- ☐ bottom




Details of: All models: Terminal block




Details of: All models: X2 capacitor



-- End of Attachment 1 --



Circuit diagram for all models except for XPB58-800D



Circuit diagram of model XPB58-800D

-- End of Attachment 2 --

IEC60335_2_7K – ATTACHMENT 3			
Clause	Requirement - Test	Result - Remark	Verdict

ATTACHMENT TO TEST REPORT IEC 60335-2-7 EUROPEAN GROUP DIFFERENCES AND NATIONAL DIFFERENCES Household and similar electrical appliances – Safety – Part 2: Particular requirements for washing machines	
Differences according to:	EN 60335-2-7: 2010 + A1: 2013 + A11: 2013 +A2:2019 used in conjunction with EN 60335-1: 2012 + A11: 2014
Attachment Form No.:	EU_GD _IEC60335_2_7K
Attachment Originator:	LCIE
Master Attachment:	2015-08
Copyright © 2015 IEC System for Conformity Testing and Certification of Electrical Equipment (IECEE), Geneva, Switzerland. All rights reserved.	

IEC60335_2_7K – ATTACHMENT 3			
Clause	Requirement - Test	Result - Remark	Verdict

	CENELEC COMMON MODIFICATIONS		
6.1	Delete “class 0” and “class 01”		P
7.1	Single-phase appliances to be connected to the supply mains: 230 V covered		P
	Multi-phase appliances to be connected to the supply mains: 400 V covered		N/A
7.10	The accessible switch required by 22.40 shall be distinguished from other manual devices by means of shape, or size, or surface texture, or position, etc. (EN 60335-2-7)	Timer	P
	An indication that the device has been operated is given by:		—
	• a tactile feedback, or		P
	• an audible and visual feedback		N/A
7.12	The instructions include the substance of the following:		—
	- this appliance can be used by children aged from 8 years and above and persons with reduced physical, sensory or mental capabilities or lack of experience and knowledge if they have been given supervision or instruction concerning use of the appliance in a safe way and understand the hazards involved		P
	- children shall not play with the appliance		P
	- cleaning and user maintenance shall not be made by children without supervision		P
	Children of less than 3 years should be kept away unless continuously supervised (EN 60335-2-7)		P
7.12.Z1	The specific instructions related to the safe operation of this appliance is collated together in the front section of the user instructions		P
	The height of the characters, measured on the capital letters, is at least 3 mm		P
	These instructions are also available in an alternative format, e.g. on a website	website	P
8.1.1	Also test probe 18 of EN 61032 is applied		P
	The appliance being in every possible position during the test		P
	The force on the probe in the straight position is increased to 10 N when probe 18 is used		P

IEC60335_2_7K – ATTACHMENT 3			
Clause	Requirement - Test	Result - Remark	Verdict
	When using test probe 18 the appliance is fully assembled as in normal use without any parts removed, and		P
	parts intended to be removed for user maintenance are also not removed		N/A
8.2	Compliance is checked by applying the test probes of EN 61032		P
	For built-in appliances and fixed appliances, the test probe B and probe 18 of EN 61032 are applied only after installation		N/A
11.3	For flat surfaces, temperature rises of the accessible front surface are measured using the probe of Figure Z101. The probe is applied with a force of $4\text{ N} \pm 1\text{ N}$ to the surface in such a way that the best possible contact between the probe and the surface is ensured. (EN 60335-2-7)		P
11.7	Rest period has a duration of 4 min (EN 60335-2-7)		P
11.8	“During the test, the temperature rises are monitored continuously and shall not exceed the values shown in Table 3 and Table Z101 in accordance with 11.Z101”. (EN 60335-2-7)		P
	Footnotes to “External enclosure of motor-operated appliances” to be taken into account		N/A
11.Z101	Temperature rises are not measured: (EN 60335-2-7) – on the underside of appliances intended to be used on a working surface or floor; – on the rear surface of appliances which, according to the instructions, shall be placed against a wall.		P
15.1.2	Appliances with an automatic cord reel tested with the cord in the most unfavourable position so that the reeling of the wet cord may affect electrical insulation during operation, the cord not being dried before reeling		N/A
15.2	For appliances having a working surface, the test is repeated with the appliance tilted at an angle of 2° in relation to the position of normal use in the direction which is likely to be the most unfavourable. The lid of top loading appliances is considered as a working surface if it is flat enough to put something on (EN 60335-2-7)		P
18.101	After the test, compliance with 20.103 and 20.104 shall not be impaired..... (EN 60335-2-7)		N/A

IEC60335_2_7K – ATTACHMENT 3			
Clause	Requirement - Test	Result - Remark	Verdict
19.13	The appliance shall comply with 20.103 and 20.104 if it can still be operated. (EN 60335-2-7)		N/A
20.2	When using the test probe similar to test probe B with a circular stop face, the accessories and detachable covers are removed		N/A
	Test probe 18 applied with a force of 2,5N on the appliance fully assembled		N/A
20.101	For appliances of the drum type, the drum drive motor shall be de-energized before the opening of the lid or door exceeds 50 mm. (EN 60335-2-7)		N/A
	If a removable or sliding lid is provided, the motor shall be de-energized as soon as the lid is removed or displaced and it shall not be possible to start the motor unless the lid is in the closed position.		N/A
20.Z101	For appliances with a front opening door having a dimension exceeding 200 mm and a drum having a volume exceeding 60 dm ³ , it shall not be possible to start or recommence the washing cycle until a separate means which controls the movement of the drum is operated manually even after the door has been opened and closed again. (EN 60335-2-7)		N/A
20.103	For appliances of the drum type, it shall only be possible to energize the drum drive motor when the lid or door is in the closed position. (EN 60335-2-7)		N/A
	Compliance is checked by inspection and by manual test using test probe B of IEC 61032 in an attempt to override the locking function.		N/A
20.104	It shall not be possible to open the lid or door of the appliance while the speed exceeds 60 r/min (EN 60335-2-7)		N/A
21.101.2	After the test, the appliance shall not be damaged or deformed to such an extent that compliance with 20.103 and 20.104 is impaired (EN 60335-2-7)		N/A
21.102	A force of 50 N is applied to the open lid in the most unfavourable direction and position. Test carried out 3 times , after which the hinges shall not have worked loose and the appliance shall not be damaged or deformed to such an extent that compliance with 20.103 and 20.104 is impaired (EN 60335-2-7)		N/A
22.40	Washing machines shall be fitted with an accessible switch to stop all operational functions of the appliance. (EN 60335-2-7)		P
24.1	Components comply with the safety requirements specified in the relevant standards as far as they reasonably apply		P

IEC60335_2_7K – ATTACHMENT 3			
Clause	Requirement - Test	Result - Remark	Verdict
	The requirements of Clause 29 of this standard apply between live parts of components and accessible parts of the appliance.		P
	The requirements of 30.2 of this standard apply to parts of non-metallic material in components including parts of non-metallic material supporting current-carrying connections inside components		P
	Components that have not been previously tested or do not comply with the standard for the relevant component are tested according to the requirements of 30.2		N/A
	Components that have been previously tested and shown to comply with the resistance to fire requirements in the standard for the relevant component need not be retested provided that:		—
	- the severity specified in the component standard is not less than the severity specified in 30.2, and		N/A
	- the test report for the component states whether it complied with the standard for the relevant component with or without flame, flames not exceeding 2 s during the test are ignored		N/A
	Unless components have been previously tested and found to comply with the relevant standard for the number of cycles specified, they are tested in accordance with 24.1.1 to 24.1.9		N/A
	For components mentioned in 24.1.1 to 24.1.9, no additional tests specified in the relevant standard for the component are necessary other than those specified in 24.1.1 to 24.1.9		N/A
	Components that have not been separately tested and found to comply with the relevant standard, and		N/A
	components that are not marked or not used in accordance with their marking,		N/A
	are tested in accordance with the conditions occurring in the appliance, the number of samples being that required by the relevant standard		N/A
	Lamp holders and starter holders that have not been previously tested and found to comply with the relevant standard are tested as a part of the appliance and additionally comply with the gauging and interchangeability requirements of the relevant standard under the conditions occurring in the appliance		N/A

IEC60335_2_7K – ATTACHMENT 3			
Clause	Requirement - Test	Result - Remark	Verdict
	Where the relevant standard specifies these gauging and interchangeability requirements at elevated temperatures, the temperatures measured during the tests of Clause 11 are used		N/A
	Plugs and socket-outlets and other connecting devices of interconnection cords are not interchangeable with plugs and socket-outlets listed in IEC/TR 60083 or IEC 60906-1, or		P
	with connectors and appliance inlets complying with the standard sheets of IEC 60320-1,		N/A
	if direct supply to these parts from the supply mains gives rise to a hazard		N/A
24.1.7	If the remote operation of the appliance is via a telecommunication network, the relevant standard for the telecommunication interface circuitry in the appliance is EN 41003		N/A
	Compliance with Clause 8 of this standard is not impaired by connecting the appliance to a device covered by EN 41003		N/A
24.Z1	For motor running capacitors (IEC 60252-1 type P2) with a metallic enclosure having an overpressure fuse the flame testing of internal plastic parts supporting current carrying connections as required in 30.2.2 and 30.2.3.1 is not necessary		N/A
25.6	Supply cords of single-phase portable appliances having a rated current not exceeding 16 A, fitted with a plug complying with the following standard sheets of IEC/TR 60083:		—
	- for Class I appliances: standard sheet C2b, C3b or C4 :		N/A
	- for Class II appliances: standard sheet C5 or C6 :		N/A
25.7	Rubber sheathed cords (60245 IEC 53) are not suitable for appliances intended to be used outdoors or when they are liable to be exposed to significant amount of ultraviolet radiation		N/A
	Halogen-free thermoplastic compound sheathed supply cords have properties at least those of:		—
	halogen-free thermoplastic compound sheathed cords (H03Z1Z1H2-F or H03Z1Z1-F), for appliances having a mass not exceeding 3 kg		N/A
	halogen-free thermoplastic compound sheathed cords (H05Z1Z1H2-F or H05Z1Z1-F), for other appliances		N/A

IEC60335_2_7K – ATTACHMENT 3			
Clause	Requirement - Test	Result - Remark	Verdict
	Cross-linked halogen-free compound sheathed supply cords have properties at least those of cross-linked halogen-free compound sheathed cords (H07ZZ-F)		N/A
26.11	Conductors connected by soldering are not considered to be positioned or fixed so that reliance is not placed upon the soldering alone to maintain them in position unless they are held in place near the terminals independently of the solder		P
29.3.Z1	Appliance constructed so that if there is a possibility of damaging the insulation during installation, the insulation withstands the scratch and penetration test of 21.2		N/A
32	Compliance regarding electromagnetic fields is checked according to EN 50366 or EN 62233		P
Annex I, 19.1.101	The appliance is supplied at rated voltage and operated under normal operation with each of the fault conditions specified		N/A
	The duration of the test is as specified in 19.7		N/A

IEC60335_2_7K – ATTACHMENT 3			
Clause	Requirement - Test	Result - Remark	Verdict
ZA	ANNEX ZA (NORMATIVE) SPECIAL NATIONAL CONDITIONS		—
	Norway		N/A
19.5	The test is also applicable to appliances intended to be permanently connected to fixed wiring		—
	Norway		—
22.2	The second paragraph of this subclause, dealing with single-phase, permanently connected class I appliances having heating elements, is not applicable due to the supply system		N/A
	All CENELEC countries		—
25.6 and 25.25	Information concerning National plug and socket-outlets is available from the CENELEC website. Normative national requirements concerning plug and socket-outlets are shown in the relevant National standard		P
	Ireland and United Kingdom		—
25.8	In the table, the lines for 10 A and 16 A are replaced by:		—
	> 10 and ≤ 13 1,25		N/A
	> 13 and ≤ 16 1,5		N/A
ZB	ANNEX ZB (INFORMATIVE) A-DEVIATIONS		—
	Ireland		—
25.6	These regulations apply to all plugs for domestic use at a voltage of not less than 200 V and in general allow only plugs complying with I.S. 401:1997, or equivalent, to be fitted to domestic appliances		N/A
	United Kingdom		—
25.6	These regulations apply to all plugs for domestic use at a voltage of not less than 200 V and in general allow only plugs to BS 1363 to be fitted to domestic appliances. It also allows plugs to BS 4573 and EN 50075 to be fitted to shavers and toothbrushes		N/A
ZC	ANNEX ZC (NORMATIVE) NORMATIVE REFERENCES TO INTERNATIONAL PUBLICATIONS WITH THEIR CORRESPONDING EUROPEAN PUBLICATIONS		—
	A list of referenced documents in this standard	Replace by A13:2017	P
ZD	ANNEX ZD (INFORMATIVE) IEC and CENELEC CODE DESIGNATIONS FOR FLEXIBLE CORDS		—

IEC60335_2_7K – ATTACHMENT 3			
Clause	Requirement - Test	Result - Remark	Verdict
	A table with IEC and CENELEC code designations for flexible cords		P
ZE	ANNEX ZE (INFORMATIVE) SPECIFIC ADDITIONAL REQUIREMENTS FOR APPLIANCES AND MACHINES INTENDED FOR COMMERCIAL USE		—
7.1	Business name and full address of the manufacturer and, where applicable, his authorized representative.....:		N/A
	Model or type reference.....:		N/A
	Serial number, if any.....:		N/A
	Production year		N/A
	Designation of the appliance.....:		N/A
7.12	Instructions provided with the appliance so that the appliance can be used safely		N/A
	The instructions contain at least the following information:		—
	- the business name and full address of the manufacturer and, where applicable, his authorized representative		N/A
	- model or type reference of the appliance as marked on the appliance itself, except for the serial number		N/A
	- the designation of the appliance together with its explanation in case it is given by a combination of letters and/or numbers		N/A
	- the general description of the appliance, when needed due to the complexity of the appliance		N/A
	- specific precautions if required during installation, operation, adjusting, user maintenance, cleaning, repairing or moving		N/A
	- when needed drawings, diagrams, descriptions and explanations necessary for the safe use and user maintenance of the appliance		N/A
	- the possible reasonably foreseeable misuse and, whenever relevant, a warning against the effects it may have on the safe use of the appliance		N/A
	The words “Original instructions” appear on the language version(s) verified by the manufacturer or by the authorized representative		N/A

IEC60335_2_7K – ATTACHMENT 3			
Clause	Requirement - Test	Result - Remark	Verdict
	When a translation of the original instructions has been provided by a person introducing the appliance on the market; the meaning of the sentence "Translation of the original instructions" appear in the relevant instructions delivered with the appliance		N/A
	The instructions for maintenance/service to be done by specialized personnel, mandated by the manufacturer or the authorized representative may be supplied in only one Community language which the specialized personnel understand		N/A
	The instructions indicate the type and frequency of inspections and maintenance required for safe operation including the preventive maintenance measures		N/A
7.12.ZE1	If needed for specific appliances, the following information to be given:		—
	on use, transportation, assembly, dismantling when out of service, testing or foreseeable breakdowns, if these operations have consequences on stability of the appliance in order to avoid overturning, falling or uncontrolled movements of the appliance or of its component parts		N/A
	on how to maintain adequate mechanical stability when in use, during transportation, assembly, dismantling, scrapping and any other action involving the appliance		N/A
	on the protective measures to be taken by the user, including, where appropriate, the personal protective equipment to be provided		N/A
	on the operating method to be followed in the event of accident or breakdown; if a blockage is likely to occur the operating method to safely unblock the appliance		N/A
	on the specifications on the spare parts to be used, when these affect the health and safety of the operator		N/A
	on airborne noise emissions, determined and declared in accordance with the relevant Part 2, which includes:		—
	70 - the A-weighted emission sound pressure level at workstations, where this exceeds dB(A);		N/A
	dB(A), - where this level does not exceed 70 this fact is indicated		N/A

IEC60335_2_7K – ATTACHMENT 3			
Clause	Requirement - Test	Result - Remark	Verdict
	- the peak C-weighted instantaneous sound pressure value at workstations, where this exceeds 63 Pa (130 dB in relation to 20 µPa)		N/A
	- the A-weighted sound power level emitted by the machinery, where the A-weighted emission sound pressure level at workstations exceeds 80 dB(A)		N/A
7.12.ZE2	The instructions includes a warning to disconnect the appliance from its power source during service and when replacing parts		N/A
	If the removal of the plug is foreseen, it is clearly indicated that the removal of the plug has to be such that an operator can check from any of the points to which he has access that the plug remains removed		N/A
	If this is not possible, due to the construction of the appliance or its installation, a disconnection with a locking system in the isolated position is provided		N/A
19.11.4.8	The appliance continues to operate, without causing any hazard to the user, from the same point in its operating cycle at which the voltage fluctuation occurred, or		N/A
	a manual operation is required to restart it		N/A
20.1	Appliances and their components and fittings have adequate mechanical stability during transportation, assembly, dismantling and any other action involving the appliance		N/A
20.2	Dangerous moving transmission parts safeguarded either by design or guards		N/A
	When guards are used, they are fixed guards, interlocking movable guards or protective devices		N/A
	Moving parts directly involved in the function of the appliance which cannot be made completely inaccessible fitted with:		—
	- fixed guards or interlocking movable guards preventing access to those sections of the parts that are not used in the work, and		N/A
	- adjustable guards restricting access to those sections of the moving parts where access is necessary		N/A
	Interlocking movable guards used where frequent access is required		N/A

IEC60335_2_7K – ATTACHMENT 3			
Clause	Requirement - Test	Result - Remark	Verdict
21.1	Appliances and their components and fittings have adequate mechanical strength and is constructed to withstand such rough handling that may be expected in normal use, during transportation, assembly, dismantling, scrapping and any other action involving the appliance		N/A
22.ZE.1	For appliances provided with a seat, the seat gives adequate stability		N/A
	The distance between the seat and the control devices capable of being adapted to the operator		N/A
22.ZE.2	For appliances provided with separate devices for the start and the stop functions, the stop function is unambiguously identifiable and does always override the start function		N/A
	For appliances provided with one device performing the start and the stop function, the stop function is unambiguously identifiable and does always override the start function		N/A
22.ZE.3	Appliances designed in such a way that incorrect mounting is avoided, if this can lead to an unsafe situation		N/A
	If this is not possible, information on the correct mounting is given directly on the part and/or the enclosure		N/A
22.ZE.4	Where the weight, size or shape prevents appliances from being moved manually, they are fitted with attachments for lifting gear, or		N/A
	so designed that they can be fitted with such attachments, or		N/A
	be shaped in such a way that standard lifting gear can easily be used		N/A
	Appliances to be moved manually are constructed or equipped so that they can be moved easily and safely		N/A
22.ZE.5	The fixing systems of fixed guards which prevent access to dangerous moving transmission parts only removable with the use of tools		N/A
	If such guards have to be removed by the user for routine cleaning or maintenance their fixing systems remain attached to the fixed guards or to the machine after removal		N/A
	Where possible, guards are incapable of remaining in place without their fixings		N/A

IEC60335_2_7K – ATTACHMENT 3			
Clause	Requirement - Test	Result - Remark	Verdict
	This does not apply if, after removal of the screws, or if the component is incorrectly repositioned, the appliance becomes inoperative		N/A
	Movable guards are interlocked		N/A
	The interlocking devices prevent the start of hazardous appliance functions until the guards are fixed in their position, and give a stop command whenever they are no longer closed		N/A
	Where it is possible for an operator to reach the danger zone before the risk due to hazardous appliance functions has ceased, movable guards associated with a guard locking device in addition to an interlocking device that:		—
	- prevents the start of hazardous appliance functions until the guard is closed and locked, and		N/A
	- keeps the guard closed and locked until the risk of injury from the hazardous appliance functions has ceased		N/A
	Interlocking movable guards remain attached to the appliance when open, and		N/A
	they are designed and constructed in such a way that they can be adjusted only by means of an intentional action		N/A
22.ZE.6	Interlocking movable guards designed in such a way that the absence or failure of one of their components prevents starting or stops the hazardous appliance functions		N/A
	The guard is opened to the extent needed to cause the interlocking to operate and is then closed, the number of operations being defined in the specific Part 2..... :		N/A
	After this test any defect that may be expected in normal use is applied to the interlock system, including interruption of the supply, only one defect being simulated at a time		N/A
	After these tests the interlock system is fit for further use		N/A
22.ZE.7	Adjustable guards restricting access to areas of the moving parts strictly necessary for the work are:		—
	- adjustable manually or automatically, depending on the type of work involved, and		N/A
	- readily adjustable without the use of tools		N/A
22.ZE.8	In case of interruption, re-establishment after an interruption or fluctuation in whatever manner of the power supply, the appliance does not restart		N/A

IEC60335_2_7K – ATTACHMENT 3			
Clause	Requirement - Test	Result - Remark	Verdict
	However, automatic restarting of the operation is allowed if the appliance may continue to operate, without causing any hazard to the user, from the same point in its operating cycle at which the voltage interruption or fluctuation occurred		N/A
22.ZE.9	Appliances fitted with means to isolate them from all energy sources		N/A
	Such isolators are clearly identified, and		N/A
	they are capable of being locked if reconnection endanger persons		N/A
	After the energy source is disconnected, it is possible to dissipate any energy remaining or stored in the circuits of the appliance without risk to persons		N/A
ZF	ANNEX ZF (INFORMATIVE) CRITERIA APPLIED FOR THE ALLOCATION OF PRODUCTS COVERED BY STANDARDS IN THE EN 60335 SERIES UNDER LVD OR MD		—
	List of standards under CENELEC/TC61 with the allocation under the LVD (Low Voltage Directive) or the MD (Machinery Directive) :	LVD	P
ZG	ANNEX ZG (NORMATIVE) UV APPLIANCES		—
	The following modifications to this standard apply to appliances having UV emitters		N/A
	This annex is not applicable to appliances covered by the scopes of IEC 60335-2-27, IEC 60335-2-59 or IEC 60335-2-109		N/A
7.12.ZG	The instructions for appliances incorporating UVC emitters include the substance of the following: WARNING — This appliance contains a UV emitter. Do not stare at the light source		N/A
32	For appliances incorporating UV emitters the manufacturer delivers a declaration providing evidence that the plastic material exposed to the radiation is UV resistant		N/A
ZZ	ANNEX ZZ (INFORMATIVE) COVERAGE OF ESSENTIAL REQUIREMENTS OF EC DIRECTIVES		—
	Description of the relation between this European standard and the LVD (Low Voltage Directive, 2006/95/EC) and the MD (Machinery Directive, 2006/42/EC)		N/A

IEC60335_2_7K – ATTACHMENT 3			
Clause	Requirement - Test	Result - Remark	Verdict

Annex EN 62233:2008			
Clause	Requirement + Test	Result - Remark	Verdict
EMF- ELECTROMAGNETICS FIELDS			
	The tested product also complies with the requirements of EN 62233:2008		—
	Limit100%	Measured max.: 1,4 %	P

— End of Attachment 3 —

ATTACHMENT TO TEST REPORT IEC 60335-1
EUROPEAN GROUP DIFFERENCES AND NATIONAL DIFFERENCES
Household and similar electrical appliances – Safety –
Part 1: GENERAL REQUIREMENTS

Differences according to: EN 60335-1:2012/A13: 2017

Clause	Requirement - Test	Result - Remark	Verdict
	Replace Annex ZC of EN 60335-1:2012 with the following:		--
Annex ZC	ANNEX ZC (NORMATIVE) NORMATIVE REFERENCES TO INTERNATIONAL PUBLICATIONS WITH THEIR CORRESPONDING EUROPEAN PUBLICATIONS		--
	A list of referenced documents in this standard		P
	<i>Delete Annex ZZ of EN 60335-1:2012 and replace by the following new annexes:</i>		--
Annex ZZA	Relationship between this European standard and the safety objectives of Directive 2014/35/EU [2014 OJ L96] aimed to be covered		--
	This European Standard has been prepared under a Commission's standardization request relating to harmonized standards in the field of the Low Voltage Directive, M/511, to provide one voluntary means of conforming to safety objectives of Directive 2014/35/EU of the European Parliament and of the Council of 26 February 2014 on the harmonization of the laws of the Member States relating to the making available on the market of electrical equipment designed for use within certain voltage limits [2014 OJ L96].		P
	Once this standard is cited in the Official Journal of the European Union under that Directive, compliance with the normative clauses of this standard given in Table ZZA.1 confers, within the limits of the scope of this standard, a presumption of conformity with the corresponding safety objectives of that Directive, and associated EFTA regulations.		P
	Compliance with this Part 1 when used together with the relevant Part 2 provides one means of conformity with the safety objectives.		P
Table ZZA.1	Table ZZA.1 – Correspondence between this European standard and Annex I of Directive 2014/35/EU [2014OJ L96]		--



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC (Shanghai) Technical Services Co., Ltd.
Testing Center E&E Energy Laboratory

NO.588 West Jindu Road, Songjiang District, Shanghai, China 201612 t (86-21) 61915666 f (86-21) 61915678 www.sgs.com.cn
中国·上海·松江区金都西路588号 邮编: 201612 t (86-21) 61915666 f (86-21) 61915678 e sgs.china@sgs.com

Member of the SGS Group (SGS SA)

Clause	Requirement - Test	Result - Remark	Verdict
Annex ZZB	Relationship between this European standard and the essential requirements of Directive 2006/42/EC aimed to be covered		--
	This European Standard has been prepared under a Commission's standardization request relating to Mandate for standardization in the field of machinery "M/396" to provide one voluntary means of conforming to essential requirements of EU Directive 2006/42/EC.		N/A
	Once this standard is cited in the Official Journal of the European Union under that EU Directive compliance with the normative clauses of this standard given in Table ZZB.1 confers, within the limits of the scope of this standard, a presumption of conformity with the corresponding essential requirements of that Directive and associated EFTA regulations.		N/A
	Compliance with this Part 1 when used together with the relevant Part 2 provides one means of conformity with the relevant essential health and safety requirements.		N/A
Table ZZB.1	Table ZZB.1 – Correspondence between this European standard and Annex I of Directive 2006/42/EC. [OJ No L 157]		--

-- End of attachment 4 --

ATTACHMENT TO TEST REPORT IEC 60335-1
EUROPEAN GROUP DIFFERENCES AND NATIONAL DIFFERENCES
Household and similar electrical appliances – Safety –
Part 1: GENERAL REQUIREMENTS

Differences according to: EN 60335-1:2012/A1:2019 + A14:2019 + A2:2019

EN 60335-1:2012/A1:2019

Clause	Requirement - Test	Result - Remark	Verdict
11.8	Comment to be retained in the amendment:		—
	The deletion of the second sentence in the first paragraph was carried out in the existing common modifications.		N/A
	In Table 3 delete footnotes za, zb, zc, zd.		N/A
24	Comment to be retained in the amendment: The following text replaces common modification text in the existing standard by the IEC text including changes in A1. It also includes the paragraph from the EN 60335-1:2012 starting by "Plugs and socket-outlets and their connecting devices...."		—
	Replace the existing text by the following:		—
24.1	Components shall comply with the safety requirements specified in the relevant EN standards as far as they reasonably apply.		P
	Compliance with the EN standard for the relevant component does not necessarily ensure compliance with the requirements of this standard.		P
	Motors are not required to comply with EN 60034-1. They are tested as part of the appliance according to this standard.		P
	Relays shall be tested as part of the appliance according to this standard. They may be alternatively tested to EN 60730-1, in which case they shall also meet the additional requirements in EN 60335-1.		N/A
	Unless otherwise specified, the requirements of Clause 29 of this standard apply between live parts of components and accessible parts of the appliance. Unless otherwise specified, components may comply with the requirements for clearances and creepage distances for functional insulation as specified in the relevant component standard.		P
	Unless otherwise specified, the requirements of 30.2 of this standard apply to parts of non-metallic material in components including parts of non-metallic material supporting current-carrying connections inside components.		P
	Components that have not been previously tested and shown to comply with the EN standard for the relevant component are tested according to the requirements of 30.2 of this standard.		P

Clause	Requirement - Test	Result - Remark	Verdict
	Components that have been previously tested and shown to comply with the resistance to fire requirements in the EN standard for the relevant component need not be retested provided that		—
	— the severity specified in the component standard is not less than the severity specified in 30.2 of this standard, and		N/A
	— unless the pre-selection alternatives in 30.2 are used, the test report for the component states the values of t_e and t_i as required by EN 60695-2-11.		N/A
	If the above two conditions are not satisfied, the component is tested as part of the appliance.		P
	Power electronic converter circuits are not required to comply with EN 62477-1. They are tested as part of the appliance according to this standard.		N/A
	Unless components have been previously tested and found to comply with the relevant EN standard for the number of cycles specified, they are tested in accordance with 24.1.1 to 24.1.9. For components mentioned in 24.1.1 to 24.1.9, no additional tests specified in the relevant EN standard for the component are necessary other than those specified in 24.1.1 to 24.1.9.		P
	Components that have not been separately tested and found to comply with the relevant EN standard and components that are not marked or not used in accordance with their marking, are tested in accordance with the conditions occurring in the appliance, the number of samples being that required by the relevant standard.		P
	NOTE 2 For automatic controls, marking includes documentation and declaration as specified in Clause 7 of EN 60730-1.		P
	Lamp-holders and starter-holders that have not been previously tested and found to comply with the relevant EN standard are tested as a part of the appliance and shall additionally comply with the gauging and interchangeability requirements of the relevant EN standard under the conditions occurring in the appliance. Where the relevant EN standard specifies these gauging and interchangeability requirements at elevated temperatures, the temperatures measured during the tests of Clause 11 are used.		N/A
	There are no additional tests specified for nationally standardized plugs such as those detailed in IEC/TR 60083 or connectors complying with the standard sheets of EN 60320-1 and EN 60309, unless they are specifically mentioned in the text of this standard.		P

Clause	Requirement - Test	Result - Remark	Verdict
	Plugs and socket-outlets and other connecting devices of interconnection cords shall not be interchangeable with plugs and socket-outlets listed in IEC/TR 60083 or IEC 60906-1 or with connectors and appliance inlets complying with the standard sheets of EN 60320-1, if direct supply to these parts from the supply mains could give rise to a hazard.		N/A
	When an EN standard does not exist for a component, there are no additional tests specified		P
Annex ZC	Normative references to international publications with their corresponding European publications		P

EN 60335-1:2012/A14:2019

Clause	Requirement - Test	Result - Remark	Verdict
7	Marking and instructions		—
7.10	Add the following text after the first paragraph of the addition:		—
	A push-push button switch used for start and stop the operation shall not be used for other functions such as changing the motor speed.		N/A
	For hand-held appliances with rated power input 50 W or lower it is acceptable to have a push-push button for different functions including on / off if there is an immediate feedback to the user e.g. by tactile feedback or audible and visible feedback.		N/A
	NOTE Z1 An example of such a function is: slow/fast / off.		N/A
	Where a push button can cycle through various modes during a prolonged push this is allowed as long as the appliance will switch off with a single short push action.		N/A
	Renumber the current NOTE Z1 and NOTE Z2 by NOTE Z2 and NOTE Z3.		P
	Replace the first sentence of NOTE Z2 (was NOTE Z1) by the following:		P
	Audible feedback is any audible response got immediately after the operation of the switch. The click of a switch can be accepted as an audible feedback provided that it is originated inside the switch that is operated and can be heard at a distance of 77 cm from the switch. The sound of the motor is regarded as an audible feedback.		P
	Add the following text after the third paragraph of the addition:		—
	Constructions with switches that have two different stable positions (meaning that it can be seen or felt when they have been pressed or rotated) are considered to have a tactile feedback.		P
8	Protection against access to live parts		—
8.1.1	Replace the first sentence of the replacement of the 3rd paragraph with the following:		—
	Test probe B and probe 18 of EN 61032 are applied with a force not exceeding 1 N, the appliance being in every possible position, except that appliances normally used on the floor and having a mass exceeding 40 kg are not tilted. ³		P
8.1.3	Add the text “ , test probe 18” after “test probe B,”		P
15	Moisture resistance		—
15.1.2	Put the text of the addition in italics		N/A
20	Stability and mechanical hazards		—

Clause	Requirement - Test	Result - Remark	Verdict
20.2	In the second paragraph replace the word "movable" by "moving" and replace "main function" by "working function".		P
22	Construction		—
22.12	Add to the first paragraph:		—
	Other parts that are intended to be detached during use, maintenance or cleaning (examples are batteries, battery covers, lids, attachments, steam nozzles) are not considered as parts providing a similar function as handles, knobs, grips, levers.		N/A
22.17	Add a new sentence to the requirement:		—
	This is not applicable to built-in appliances.		N/A
24	Components		—
24.1	Add before the last paragraph the following:		—
	NOTE Z3 For details of plugs used in CENELEC countries listed in IEC TR 60083 see Annex ZH.		P
25	Supply connection and external flexible cords		—
25.1	Addition		—
	Plugs and pins for insertion into socket outlets shall follow the relevant standards sheets in Annex ZH.		P
25.6	Delete the addition.		N/A
25.25	Replace the second sentence of the first paragraph and add the note:		—
	Dimensions of the pins and engagement face of plugs of appliances that are inserted into socket-outlets are to be in accordance with the dimensions of the relevant plug standard.		P
	NOTE Z1 Common plugs and socket-outlets types in CENELEC countries as shown in Annex ZH.		P
32	Radiation, toxicity and similar hazards		—
	Delete in the third paragraph "EN 50366 or"		P
Annex ZA	Special national conditions		
7.12.8	Denmark, Sweden, Norway and Finland		—
	The maximum inlet water pressure shall be at least 1,0 MPa		N/A
22.47	Denmark		—
	The maximum inlet water pressure shall be at least 1,0 MPa		N/A
25.8	Ireland and United Kingdom		—
	In the table, replace the line ">10A and ≤16A" with:		—
	> 10 and ≤ 13 1,25 (1,0)		N/A
	> 13 and ≤ 16 1,5 (1,0)		N/A

Clause	Requirement - Test	Result - Remark	Verdict
Annex ZB	A-deviations		—
	Replace the reference to subclause 25.6 by 25.1 and 25.25 for Ireland and United Kingdom A-deviations.		N/A
	Delete the note.		N/A
Annex ZD	IEC and CENELEC code designations for flexible cords		—
	Replace Table ZD.1		P
Annex ZF	Criteria applied for the allocation of products covered by standards in the EN 60335 series under LVD or MD		—
	Replace the Table ZF.1	LVD	P
Annex ZH	Common plug and socket-outlet types in CENELEC countries		—
ZH.1	General		—
	In general, supply cords of single-phase appliances having a rated current not exceeding 16 A shall be fitted with a plug complying with the following standard sheets:		—
	— for class I appliances or class II appliances with functional earth		—
	standard sheet EU2, EU3 or EU4;		P
	— for class II appliances		—
	standard sheet EU5, EU6 or EU7.		N/A
	Some exemptions or differences in certain CENELEC countries:		N/A
ZH.2	General national data		—
	Plugs according to standard sheet EU2 are not allowed in Belgium, France and the United Kingdom.		P
	Plugs according to standard sheet EU3 are not allowed in Austria, Finland, Germany, Iceland, Ireland, Italy, Luxembourg, Netherlands, Portugal, Spain, Sweden, Switzerland and the United Kingdom.		P
ZH.3	Specific country data.		—
ZH.3.1	Belgium		—
	Only plugs and socket-outlets according to NBN C 61-112-1 (–2 and –3) are allowed, taking into account the class of the appliance and the rated current and voltage.		P
	These plugs are shown in IEC/TR 60083 as BE1, BE2 and BE3.		P
	They correspond with plug designations: EU3, EU4, EU5, EU6 and EU7.		P
ZH.3.2	Cyprus		—

Clause	Requirement - Test	Result - Remark	Verdict
	Only plugs according to British Standards BS 1363 and BS 4573 are allowed.		P
	These plugs are shown in IEC/TR 60083 as GB1 and GB6.		P
	They correspond with plug designations: EU9 and EU10.		P
ZH.3.3	Denmark		—
	Plugs and socket-outlets for household and similar purposes shall be in accordance with DS 60884-2-D1"		N/A
	Plugs and Socket-outlets for household and similar purposes - Requirements for Danish systems".		N/A
	For single-phased appliances with rated current above 13 A and supplied via a plug in accordance with DS 60884-2-D1 " Plugs and socket-outlets for household and similar purposes - Requirements for Danish systems" the following warning shall be given in the installation instructions:		—
	— Inden apparatet tilsluttes skal det sikres at installationen er egnet til apparater med en mærkestrøm der overstiger 13 A. I tvivlstilfælde bør en autoriseret el-installatør kontaktes.		N/A
ZH.3.4	Finland		—
	Only plugs according to Publications SFS 5610 and SFS-EN 50075 are allowed.		P
	These plugs are shown in IEC/TR 60083 as FI2, FI3, FI4, FI5 and FI7.		P
	They correspond with plug designations: EU2, EU 4, EU5, EU6 and EU7.		P
ZH.3.5	Germany		—
	Plugs allowed in Germany are specified in DIN 49440.		P
	These plugs are shown in IEC/TR 60083 as DE1, DE2, DE3 and DE4.		P
	They correspond with plug designations: EU2, EU 4, EU5, EU6, EU7 and EU8.		P
ZH.3.6	Greece		—
	Special national conditions based on regulations applicable to plugs: Government Gazette No 67/B/28-1-2000		N/A
	National Standards applicable to plugs:		—
	— ELOT EN 50075:1992 "Flat non-rewirable two-pole plugs, 2,5 A, 250 V, with cord, for the connection of class II equipment for household and similar purposes" (identical to EN 50075:1990)		N/A
	— ELOT 294:1997 (identical to CEE 7)		N/A

Clause	Requirement - Test	Result - Remark	Verdict
	— ELOT 294:1997 (identical to CEE 7)		N/A
	— ELOT 1413-1:1999 “Plugs and socket-outlets for household and similar purposes (identical to IEC 60884-1:1994 +A1:1994+A2:1995) (tests are performed with the current edition of IEC 60884-1 and ELOT 1413-1).		N/A
	Characteristics of the plugs		N/A
	Characteristics of the socket-outlets:		N/A
	In the Greek market mainly socket outlets with side earth contacts EU2 can be found, but also socket outlets with pin earth EU3 and Italian style socket outlets can be found.		N/A
ZH.3.7	Ireland		—
	Only plugs according to standard sheets EU9, EU6 and EU5 are allowed.		N/A
ZH.3.8	Italy		—
	Only plugs according to the Standard CEI 23-50 and CEI EN 50075 are allowed.		P
	These plugs are shown in IEC/TR 60083 as IT1, IT2, IT3, IT4, IT5, IT6 and IT7.		P
	They correspond with plug designations: EU2, EU4, and EU7.		P
ZH.3.9	Netherlands		—
	Only plugs according to NEN 1020 are allowed, standard sheets:		—
	— IV 10/16 A 250 V class I plug (L+N+PE) with side earthing [= TR IEC 60083 - NL 2 / EU2]		P
	— VII 10/16 A 250 V class I plug (L+N+PE) with side and pin earthing [= TR IEC 60083 - NL 2 / EU4]		P
	— XVI 2,5 A 250 V class II plug (L+N):		—
	— Variant I = round [= TR IEC 60083 - NL 3 / EU5]		N/A
	— Variant II = flat [= TR IEC 60083 - NL 5 / EU6]		N/A
	— XVII 10/16 A 250 V class II plug (L+N) [TR IEC 60083 - NL 4 / EU7]		N/A
	Or plugs according IEC 60884, standard sheet DIN 49446		—
	— Perilex 16 A 230/400 V class I plug L1/L2/L3+N+PE [= EU8]		N/A
	These plugs are shown in IEC/TR 60083 as NL2, NL3, NL4, NL5 and DE4.		P
	They correspond with plug designations: EU 2, EU4, EU5, EU6, EU7 and EU8.		P

Clause	Requirement - Test	Result - Remark	Verdict
ZH.3.10	Norway		—
	Only plugs according to standard sheets NO 2, NO 4, NO 5 and NO 6 of IEC/TR 60083 are allowed.		P
	They correspond with plug designations: EU 2, EU4, EU5, EU6 and EU7.		P
ZH.3.11	Slovenia		—
	Only plugs and socket-outlets according to SIST 1050:2010 are allowed.		N/A
ZH.3.12	Spain		—
	For appliances for household use, only the following plugs are allowed:		—
	— according to UNE 20315: ESC 10b, ESB 25b, ESB 32b, EU2, EU4 or EU7;		P
	These plugs are shown in IEC/TR 60083 as ES1, ES2, ES3, ES4, ES5, ES6 and ES7.		P
	They correspond with plug designations: EU2, EU4, EU6 and EU7.		P
ZH.3.13	Sweden		—
	Only plugs according to standard sheets SE 2, SE 3, and SE 4 of IEC/TR 60083 are allowed.		P
	They correspond with plug designation EU 2, EU 4, EU5, EU6 and EU7.		P
	National implementation of a plug corresponding to EU 8 is also allowed.		N/A
ZH.3.14	Switzerland		—
	Supply cords of portable household and similar electrical appliances having a rated current not exceeding 16 A shall be provided with a plug complying with SEV 1011:		—
	SEV 5932-2:2009 Plug Type 25 3L + N + PE 250 V/440 V, 16 A		N/A
	SEV 5933-2:2009 Plug Type 21 L + N 250 V, 16 A		N/A
	SEV 5934-2:2009 Plug Type 23 L + N + PE 250 V, 16 A		N/A
	SEV 6532-2:2009 Plug Type 15 3L + N + PE 250 V/440 V, 10 A		N/A
	SEV 6533-2:2009 Plug Type 11 L + N 250 V, 10 A		N/A
	SEV 6534-2:2009 Plug Type 12 L + N + PE 250 V, 10 A		N/A
	Or EN 50075 Plug L+N L + N 250V, 2,5A [EU6]		N/A
	These plugs are shown in IEC/TR 60083 as CH1, CH2, CH3, CH4, CH5 and CH6.		N/A
ZH.3.15	United Kingdom		—
	Only plugs according to standard sheets GB1, GB6 and GB7 of IEC/TR 60083 are allowed.		N/A

Clause	Requirement - Test	Result - Remark	Verdict
	They correspond with plug designations: EU9, EU6 and EU10.		N/A
ZH.4	List of country codes		—
	A list of country codes		N/A
ZI	Information on the application of A11:2014 to EN 60335-1:2012 CENELEC CLC/TC 61(SEC)2096A		—
	The publication of A11 to EN 60335-1:2012 implies an important change in the application of the dow of this standard and the corresponding Parts 2. The intention of this A11 is to clarify some possible doubts on if a Part 2 shall be applied with 2002 or 2012 version of EN 60335-1, and the present document helps to clarify.		P

EN 60335-1:2012/A2:2019

Clause	Requirement - Test	Result - Remark	Verdict
7	Marking and instructions		—
7.10	Delete the paragraphs starting with “Devices used to start/stop....” until the end of the requirement “.....by vulnerable persons.”. This includes Notes Z1 and Z2.		N/A
7.12	Delete the sub clause		N/A
7.14	Delete Note Z1.		N/A
22	Construction		—
22.12	Delete Note Z1		N/A
24	Components		—
24.Z1	Replacement		—
	Type S2 and S3 capacitors according to EN 60252-1 are not required to undergo the testing as required by 30.2.2 and 30.2.3.1.		N/A
25	Supply connection and external flexible cords		—
25.7	Delete the existing text starting “Halogen free thermoplastic.....” until “.....designation H07ZZ-F). “		N/A
Annex ZC	Normative references to international publications with their corresponding European publications		—
Annex ZD	IEC and CENELEC code designations for flexible cords		—
	Add an additional row in the Table ZD.1 of Annex ZD.		P

-- End of attachment 5 --